PROJECT TIMELINE

Municipality of Anchorage ct Management & Engineering Department

IMAGE DRIVE / REFLECTION DRIVE AREA ROAD RECONSTRUCTION

CONSTRUCTION

* Construction for this project is not yet funded.

65%

Design

Agency Review

Final Design

> Design Study Report

- We are here






IMAGE DRIVE / REFLECTION DRIVE **AREA ROAD RECONSTRUCTION**

SUMMARY OF PROPOSED IMPROVEMENTS

- Roadway base and asphalt pavement
- Curb and gutter
- Piped drainage system

- Pedestrian facilities
- Street lighting
- Traffic calming elements





QUESTIONNAIRE RESPONSES


(MAILED TO RESIDENTS IN JUNE 2016)


- 1 Have you ever experienced groundwater problems in your crawl space? No (35), Yes (15)
- 2 Do you have a foundation drain or sump pump? No (36), Yes (12)
- 3 Are you aware of any drainage problems within the project area that need to be corrected?
 Yes (25), No (22)
- 4 Do you have any concerns about speeding in your neighborhood? Yes (34), No (16)
- Do you think additional space in the roadway is required for on-street parking? No (36), Yes (13)
- 6 Are you aware of any sight distance problems that may need to be corrected as part of the project? No (39), Yes (11)
- Do you feel there is a need to construct additional sidewalks in the neighborhood? No (38), Yes (11)



IMAGE DRIVE / REFLECTION DRIVE AREA ROAD RECONSTRUCTION

Municipality of Anchorage Project Management & Engineering Department









Justin Keene

From: Image/Reflection Area Road Reconstruction Project <cevans@crweng.ccsend.com> on

behalf of Image/Reflection Area Road Reconstruction Project

<comments@crweng.com>

Sent: Wednesday, December 14, 2016 4:46 PM

To: Justin Keene

Subject: Image/Reflection Project - Open House #1 Materials on Website

Categories: Filed by Newforma



Thank You for Joining Us!

The project team would like to thank you for attending Open House #1 on December 8, 2016. If you were unable to attend or would like to review the materials again, we've posted the open house graphics and comments received on the project website.

www.ImageReflectionDrive.com

For more information and to sign up for e-mail updates, please visit the web page or contact:

Justin Keene, Project Manager
CRW Engineering Group LLC
562-3252 ● comments@crweng.com

Jennifer Noffke, Project Administrator Municipality of Anchorage 343-8130 ● noffkejl@muni.org

CRW Engineering Group LLC, 3940 Arctic Boulevard, Suite 300, Anchorage, AK 99503

SafeUnsubscribe™ jkeene@crweng.com Forward this email | Update Profile | About our service provider Sent by comments@crweng.com in collaboration with



Try it free today



Alaska Communications Systems. 600 Telephone Avenue Anchoraga, AK 99503

Attn. Lamy Smith

Re: Image Drive/Reflection Drive Area Road Reconstruction

PM&E Project No. 14-50)

Dear Mr. Smith,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you plan any utility extensions or improvements in the project area so that utility work can be coordinated with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

Marliese von Huene, E.I.T.

CRW Engineering Group.

Project Engineer

E-Mail: myonhuene@crweng.com

Attachment: Project Area Map.



Libbs Datarion 33 00 image Reflection Area Reconstitution to CADICOL CISSOS DISRIPAged Area Map mod



IMAGE DRIVE/REFLECTION DRIVE AREA ROAD RECONSTRUCTION

PROJECT AREA MAP

Project No: 14-50

Drawn 8y: MvH

Scale: NTS

Date: April 2017

Figure: 1



Androrage Water & Wastewater CCTty 3000 Artik Sovieward Anthorage, Ad 99508

Attn: Joe Sanks

Re: Image Drive/Reflection Drive Area Road Reconstruction

(P.V.S.E. Project No. 14-50)

Dear Mr. Sanks,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you plan any utility extensions or improvements in the project area so that utility work can be coordinated with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

Wan to .

CRW Engineering Group,

Project Engineer

E-Mail: myonhuene@crweng.com

Attachment: Project Area Map



Chugach Bectric Association, Inc. P.O. Box 396300 Anchorage, AX 99616

Altin Lamet Boling

Re: Image Drive/Reflection Drive Area Boad Reconstruction.

[PMSE Project No. 14-50]

Dear Mr. Boling,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report [DSR] for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you plan any utility extensions or improvements in the project area so that utility work can be coordinated with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

Marliese von Huene, E.I.T.

CRW Engineering Group, LLC

Project Engineer

E-Mail: myonhuene@crweng.com

Attachment: Project Area Map



Enstar 401 Elinti Airport Road Anchorage, AX 9951 E

Attn lieff Beben.

lie:

Image Drive/Reflection Grive Area Road Reconstruction

PMSE Project No. 14-50)

Dear Mr. Hebert,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you plan any utility extensions or improvements in the project area so that utility work can be coordinated with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely.

COW Engineering Group, LLC

Marliese von Huene, E.I.

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



GCI 5151 Fairtanks Street

Altn: Rebecca Cofton

Arichorage, AX 99503.

Re: Image Orive/Reflection Drive Area Road Reconstruction

|Pht&E Project No. 34-50|

Dear Ms. Colton,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you plan any utility extensions or improvements in the project area so that utility work can be coordinated with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

Marliese von Huene, E.I.T.

CRW Engineering Group,

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



Municipality of Anchorage Fire Department 100 E. 4^o Avenue Anchorage, AK 59501

Attn: Chief Denis Lebiand

Re: Image Drive/Reflection Drive Area Road Reconstruction

JPMRE Project No. 14-50)

Dear Chief LeBlanc,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you have any comments or suggestions for the project area so that they can be considered with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

CAW Engineering Group, LLC

Marliese von Huene, E.I.T.

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



April 13, 2017

Municipality of Anchorage Police Department 4503 Elmore Road Anchorage, AX 99507

Attn: Chief Christopher Tolley

Re: mage Drive/Reflection Orive Area Road Reconstruction

(PM &E Project No. 14-50).

Dear Chief Tolley,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you have any comments or suggestions for the project area so that they can be considered with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

CRW Engineering Group, LLC

Marliese von Huene, E.I.T.

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



Anchorage School Bistrict Transportation Department 3580 Tudor Road Anchorage, AX 99507

Attn: Dan Memigan

Re: mage Drive/Reflection Drive Area Soad Reconstruction

(PM&E Project No. 14-50)

Dear Mr. Merrigan,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Drive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please notify us if you have any comments or suggestions for the project area so that they can be considered with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed [contact information shown below]. We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

CRW Engineering Group

Martiese von Huene, E.I.T.

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



Municipality of Anchorage Transit Department 3600 Ort Martin Luther Gng Jr. Avente Anchorage, AX 99507

Attn: Abu Hassan

Re: Image Drive/Reflection Orive Area Road Reconstruction

[PMR.5 Project 46, 14-50]

Dear Mr. Hassan,

CRW Engineering Group, LLC is currently under contract with the Municipality of Anchorage Project Management & Engineering Division to complete a design study report (DSR) for roadway and storm drainage improvements in the area of Image Orive and Reflection Drive from Defiance Street to Boniface Parkway. The project area is shown in the attached figure. The earliest construction could begin is during the summer of 2018.

At this time we are analyzing the improvements needed throughout the project area. In order to help address the comprehensive needs of adjacent property owners and businesses, utilities infrastructure, pedestrian facilities, and the community as a whole, we would greatly appreciate any comments from your department regarding the project. In particular, please mitify us if you have any comments or suggestions for the project area so that they can be considered with the roadway and storm drainage improvements. Comments can be mailed, faxed, or emailed (contact information shown below). We would like to include your comments in the project DSR and thank you in advance for your timely response. Please provide comments by Wednesday, May 17th.

Sincerely,

QRW Engineering Group, LLC

Marliese von Huene, EAT

Project Engineer

E-Mail: mvonhuene@crweng.com

Attachment: Project Area Map



Meeting Summary

Date: November 6, 2017; 1:30 – 2:30 pm

Attendees: Jennifer Noffke, Russ Oswald (PM&E); Steve Ellis (MOA WMS); Bill Johnson, Justin Keene (CRW)

Location: MOA PM&E Conference Room B

Project: Image Drive/ Reflection Drive Area Reconstruction

Project No: PM&E# 14-50 (CRW#10133.00)

Subject: Improvements in the Flood Plain

I. Purpose of Project, Background & Schedule

A. The purpose of the project is to reconstruct the failing storm drain system and upgrade the roadways to meet current MOA standards.

- B. MOA PM&E Riviera project replaced undersized culverts in project area and pipe outfall to South Fork Chester Creek in 2013. The flood plain was not re-mapped after project completion.
- C. No base flood elevation is established in project area on FEMA maps. However Steve Ellis stated that base flood elevation is 198.0' mean sea level within our project area.
- D. Currently working on Draft DSR, construction scheduled in 2019 or 2020 pending funding.

II. Existing Storm Drain Layout & Roadway Grade

- A. Existing storm drain pipes are corroded and failing which are causing roadway heaving in places.
- B. Two separate storm drain outfalls, both flow into Riviera storm drain pipe and outfall to Chester Creek:
 - 1. Image storm drain system discharge into Reflection Creek, submerged outlet
 - 2. Reflection storm drain system discharge into west bog
- C. Roadway is flat and less than 0.5% grade in many locations


III. Proposed Improvements in Flood Plain and Limitations

- A. Lift station can be installed in flood plain, but electrical control panel and all equipment in or supporting the lift station that cannot function submerged needs to be above elevation 198.0'.
- B. Roadway grade changes are okay in flood plain as long as the grade isn't raised within 30 feet of the Reflection Lake stream crossings at Image Drive and Reflection Drive.
- C. Sewer manhole covers within floodplain need to either be raised above elevation 198.0' or be sealed.
- D. Storm drain pipe, storm drain manholes/catch basins and footing drains will be replaced/installed but there are no limitations regarding placing these items in the flood plain.

IV. Reflection Lake Stream Culverts

A. If the Image/Reflection project needs to remove and re-install a portion of a culvert in order to facilitate construction, it can be replaced in kind since the MOA PM&E Riviera project recently replaced the culverts. The Image/Reflection project would still need to attain a flood hazard permit and other appropriate permits as required to perform work in the stream.

B. CRW confirmed after the meeting that the Reflection Lake stream culverts that were installed with the MOA PM&E Riviera project did have stream substrate installed in one of the culverts to facilitate fish passage (see Typical Culvert Crossing Detail from the plan set below).



V. Flood Plain Re-Mapping

A. Re-mapping the flood plain is not currently in the scope of the Image/Reflection project but if funds become available this work could be added.



Meeting Summary

Date: September 8, 2017; 9:00 – 10:00 am

Attendees: Jennifer Noffke, Russ Oswald (PM&E); Paul VanLandingham (MOA Street Maintenance); Bill

Johnson, Joey Hegna, Justin Keene (CRW)

Location: MOA PM&E Conference room B

Project: Image Drive/ Reflection Drive Area Reconstruction

Project No: 14-50 (CRW#10133.00)

Subject: Existing Drainage & Proposed Lift Station

I. Purpose of Project

A. The purpose of the project is to reconstruct the failing storm drain system and upgrade the roadways to meet current MOA standards.

II. Existing Storm Drain Layout

- A. Existing storm drain pipes are corroded and failing which are causing roadway heaving in places.
- B. Two separate storm drain outfalls, both flow into Riviera storm drain pipe and outfall to Chester Creek:
 - 1. Image storm drain system discharge into Reflection Creek, submerged outlet
 - 2. Reflection storm drain system discharge into west bog
- C. No existing storm drain piped system from Loon Cove currently, but new system proposed with MOA PM&E Loon Cove Drainage Improvements project
 - Reflection Lake is privately owned, thus Loon Cove flows cannot be routed to lake without owner approval. This is likely the reason designer opted to route flows to Reflection Drive system.
- D. Existing Riviera storm drain pipe capacity = 64.9 cfs (60" CMP with 2' stream substrate)

III. Proposed Typical Roadway Section

A. Subdrain installed below structural section results in existing outfalls being higher in elevation than the proposed subdrain which will require lift station to be installed.

IV. Proposed Lift Station

- A. Discussed the following location options:
 - 1. South of west bog, will discuss with Joe Sanks the existing manhole in the area to see if it has been located recently
 - 2. Mirage Circle dead end
 - 3. Will also consider within the roadway of Image/Reflection intersection
- B. Reviewed the initial matrix list of what the best/worst option is from CRW's opinion regarding options 1 and 2 above, attached to this summary
- C. Utilize detention systems listed below to minimize overall size of lift station and related components (wet well, pumps, etc.)

V. Proposed Drainage Concept

September 8, 2017
Image Drive/ Reflection Drive Area Reconstruction
Existing Drainage & Proposed Lift Station

- A. Goal of our project is to maintain pre-development flows into Riviera storm drain pipe.
- B. Reviewed options to maintain pre-development flow to alleviate capacity and flooding concerns of downstream systems (Riviera 60" CMP pipe):
 - Chamber System (Mirage Circle dead end), Paul mentioned that we should not replace with curb and pavement in this area. Could just provide maintenance access. Also CRW will investigate what the ideal pipe size is for cleaning a chamber system as well as access points.
 - a. CRW to review existing water line along east side of Mirage Circle dead end. Plans currently show pipe terminating at dead end, but need to verify and update in plans.
 - 2. Oversized Piping
 - 3. Sedimentation Basin Improvements (West Bog)
 - 4. Combination of stormwater controls
 - 5. Below ground vault with access hatches for cleaning
- C. Paul stated that whatever option we go with for detention it needs to account for being able to access it for maintenance/cleaning. Paul also stated that the project needs to provide any special equipment necessary for maintenance/cleaning to Street Maintenance.
 - 1. CRW will review O&M requirements for detention options and research if specialty equipment is necessary.
- D. Water Quality Treatment
 - 1. Sedimentation Basin
 - 2. OGS/Pre-treatment
 - 3. Location
 - 4. Meter flows into pump station
 - 5. Discharge to Sedimentation Basin

VI. Proposed Storm Drain Route

- A. CRW will investigate routing the proposed upper portion of the Reflection Drive gravity storm drain system near Defiance Street into the Image Drive system instead to reduce lift station flows.
- B. CRW will investigate routing force main storm drain piping on the property (Riviera Terrace Trailer Court) north of the project limits, including ensuring a gravity line won't be feasible to install and outfall all the way to Chester Creek.
- C. CRW will investigate utilizing the existing utility easement along the north side of the properties west of the Mirage Circle dead end to install force main storm drain piping.

VII. Drainage Analysis Results

Peak Flows: 10-Year, 24-hour Design Storm (Pipe Design)					
	Existing System	Existing System	Proposed System	Proposed System	
Map Location	(old storm)	(new storm)	(old storm)	(new storm)	Description
Design Point B	4.77 cfs	7.34 cfs*	-	-	Reflection Drive Outfall
Design Point C	3.74 cfs	6.26 cfs*	-	-	Image Drive Outfall
Design Point D	-	-	1.39 cfs	2.06 cfs	Proposed Loon Cove Project
Design Point E	-	-	8.51 cfs	15.25 cfs	Combined Outfall (B+C+D)

^{*} Overtopping conditions predicted by drainage model

Peak Flows: 50-Year, 24-Hour Design Storm (Stream Design)						
	Existing System Existing System Proposed System Proposed System					
Map Location	(old storm)	(new storm)	(old storm)	(new storm)	Description	
Design Point A	39 cfs*	50.2 cfs**	39 cfs*	50.2 cfs**	Reflection Creek Flows	
Design Point B	3 cfs*	8.16 cfs***	-	-	Reflection Drive Outfall	
Design Point C	4 cfs*	7.93 cfs***	-	-	Image Drive Outfall	
Design Point D	-	-	-	3.15 cfs	Proposed Loon Cove Project	
Design Point E	-	-	-	28.0 cfs****	Combined Outfall (B+C+D)	

^{*} Peak flow results from Riviera Terrace DSR

^{**} Estimated peak flow from Riviera Terrace DSR for new design storm (ratio of new storm over old storm)

^{***} Overtopping conditions predicted by drainage model

^{****} Surcharged conditions predicted by drainage model

^{60&}quot; SPP (Riviera Terrace System) Capacity = 64.9 cfs

	Lift Station Location Options				
Design Factor	Mirage Circle Dead End	South of West Bog			
Accessibility	1	0			
Minimal Site Work	1	0			
Outfall Pipe Drains to Lift					
Station	0	1			
Outfall Pipe					
Straightforward Route	0	1			
Allows Direct Outfall to					
West Bog	0	1			
Minimize Depth of Lift					
Station	1	0			
Utility Impacts	0	1			
Easements Required	0	1			
Cost	j	?			

3 5 Total

Rating Scale:

0 no (worst) 1 yes (best)



Meeting Summary

Date: September 6, 2017; 1:30 – 3:00 pm

Attendees: Jennifer Noffke, Russ Oswald (PM&E); Jeff Urbanus, Kristi Bischofberger (MOA WMS); Bill Johnson,

Joey Hegna, Justin Keene (CRW)

Location: MOA PM&E Conference room B

Project: Image Drive/ Reflection Drive Area Reconstruction

Project No: 14-50 (CRW#10133.00)

Subject: Existing Drainage & Proposed Lift Station

I. Purpose of Project

A. The purpose of the project is to reconstruct the failing storm drain system and upgrade the roadways to meet current MOA standards.

II. Existing Storm Drain Layout

- A. Existing storm drain pipes are corroded and failing which are causing roadway heaving in places.
- B. Two separate storm drain outfalls, both flow into Riviera storm drain pipe and outfall to Chester Creek:
 - 1. Image storm drain system discharge into Reflection Creek, submerged outlet
 - 2. Reflection storm drain system discharge into west bog
- C. No existing storm drain piped system from Loon Cove currently, but new system proposed with MOA PM&E Loon Cove Drainage Improvements project
 - Reflection Lake is privately owned, thus Loon Cove flows cannot be routed to lake without owner approval. This is likely the reason designer opted to route flows to Reflection Drive system.
- D. Existing Riviera storm drain pipe capacity = 64.9 cfs (60" CMP with 2' stream substrate)

III. Proposed Typical Roadway Section

A. Subdrain installed below structural section results in existing outfalls being higher in elevation than the proposed subdrain which will require lift station to be installed.

IV. Proposed Drainage Concept

- A. Goal of our project is to maintain pre-development flows into Riviera storm drain pipe.
- B. Reviewed options to maintain pre-development flow to alleviate capacity and flooding concerns of downstream systems (Riviera 60" CMP pipe):
 - 1. Chamber System (Mirage Circle dead end)
 - 2. Oversized Piping
 - 3. Sedimentation Basin Improvements (West Bog)
 - 4. Combination of stormwater controls
- C. Water Quality Treatment
 - 1. Sedimentation Basin
 - 2. OGS/Pre-treatment

D. There is an existing large undeveloped lot south of Keyann Circle that could help retain some of the storm drain flows. This lot is currently for sale. Upon further review it was determined that this lot may not help retain enough flow to make it worth pursuing to purchase it.

٧. **Proposed Lift Station**

- A. Utilize detention systems listed above to minimize overall size of lift station and related components (wet well, pumps, etc.)
 - 1. We discussed 2 possible locations: south of west bog & Mirage Circle dead end. There was also a question of whether two lift stations should be installed. CRW will investigate these options further.
 - 2. Meter flows into pump station
 - 3. Discharge to Sedimentation Basin

VI. **Proposed Storm Drain Route**

- A. CRW will investigate routing the proposed upper portion of the Reflection Drive gravity storm drain system near Defiance Street into the Image Drive system instead to reduce lift station flows.
- B. CRW will investigate routing force main storm drain piping on the property (Riviera Terrace Trailer Court) north of the project limits, including ensuring a gravity line won't be feasible to install and outfall all the way to Chester Creek.
- C. CRW will investigate utilizing the existing utility easement along the north side of the properties west of the Mirage Circle dead end to install force main storm drain piping.

VII. **Drainage Analysis Results**

Peak Flows: 10-Year, 24-hour Design Storm (Pipe Design)					
Existing System (old storm)	Existing System (new storm)	Proposed System (old storm)	Proposed System (new storm)	Description	
4.77 cfs	7.34 cfs*	-	-	Reflection Drive Outfall	
3.74 cfs	6.26 cfs*	-	-	Image Drive Outfall	
-	-	1.39 cfs	2.06 cfs	Proposed Loon Cove Project	
-	-	8.51 cfs	15.25 cfs	Combined Outfall (B+C+D)	
	Existing System (old storm) 4.77 cfs	Existing System (old storm) Existing System (new storm) 4.77 cfs 7.34 cfs*	Existing System (old storm) Existing System (new storm) Proposed System (old storm) 4.77 cfs 7.34 cfs* - 3.74 cfs 6.26 cfs* - - - 1.39 cfs	Existing System (old storm) Existing System (new storm) Proposed System (old storm) Proposed System (new storm) 4.77 cfs 7.34 cfs* - - 3.74 cfs 6.26 cfs* - - - - 1.39 cfs 2.06 cfs	

Peak Flows: 50-Year, 24-Hour Design Storm (Stream Design)					
	Existing System	Existing System	Proposed System	Proposed System	
Map Location	(old storm)	(new storm)	(old storm)	(new storm)	Description
Design Point A	39 cfs*	50.2 cfs**	39 cfs*	50.2 cfs**	Reflection Creek Flows
Design Point B	3 cfs*	8.16 cfs***	-	-	Reflection Drive Outfall
Design Point C	4 cfs*	7.93 cfs***	-	-	Image Drive Outfall
Design Point D	-	-	-	3.15 cfs	Proposed Loon Cove Project
Design Point E	-	-	-	28.0 cfs****	Combined Outfall (B+C+D)

^{*} Peak flow results from Riviera Terrace DSR

** Estimated peak flow from Riviera Terrace DSR for new design storm (ratio of new storm over old storm)

*** Overtopping conditions predicted by drainage model

**** Surcharged conditions predicted by drainage model

60" SPP (Riviera Terrace System) Capacity = 64.9 cfs






Image Drive / Reflection Drive Area Road Reconstruction
PM&E Project No. 14-50
Mailing Boundary Map

March 2016

Phone Call



PROJECT Image Reflection Area Reconstruction

DATE

3/15/2016 4:30 PM - 5:00 PM

10133.00

ORGANIZER Justin Keene SUBJECT

LOCATION

INVITEES Justin Keene

ATTENDEES

CC

MEETING COMMENTS

called me today regarding

- the Image/Reflection project. Her cell phone number is brief summary:
 - She lives on Reflection Drive and has been calling the MOA complaining about the failing roadway/sidewalk in front of her home since 2013 when she moved in.
 - She asked when construction may occur. I explained that there is no construction funding available currently for this project so it is unknown when construction may occur but the draft design study report is funded so we are making progress by moving the project forward. She was frustrated but understood the current economic challenges across the State of Alaska which affects funding to all municipalities in the state. I explained that this project may acquire additional funds through future MOA roadway bonds and encouraged her to vote. I also mentioned that the project may be constructed in phases depending on the construction funds.
 - She has a sump pump but doesn't have much water in her crawl space, she noted here home is higher than the roadway.
 - She has the following concerns:
 - o Roadway doesn't drain in front of her home, it pools up with water in the curb line.
 - o There are lots of heaves in the roadway and it is dangerous to drive. She thinks the heaves are getting worse every year.
 - There are many cracks in the sidewalk which are not safe for pedestrians.
 - She ideally would like two sidewalks included in the design.
 - I encouraged her to fill out the future questionnaire that we will be sending out this spring and also to attend the future open houses as
 - Overall she was pretty happy that the project is moving forward.

Draft Geotechnical Report

Appendix L





GEOTECHNICAL INVESTIGATION – IMAGE DRIVE / REFLECTION DRIVE AREA ROAD UPGRADE

Image Drive and Reflection Drive, Anchorage, Alaska (MOA PM&E Project No. 14-50)

Submitted To: Mr. Justin Keene, PE

CRW Engineering Group, LLC 3940 Arctic Blvd., Suite 300 Anchorage, AK 99503

Submitted By: Golder Associates Inc.

2121 Abbott Road, Suite 100 Anchorage, AK 99507 USA

Distribution:

4 Copies – CRW Engineering Group, LLC 2 Copies – Golder Associates Inc.

August 15, 2016

Golder Associates

1523636



Table of Contents

1.0	INTRODUCTION	1
2.0	HISTORICAL GEOTECHNICAL INVESTIGATIONS	2
3.0	SITE RECONNAISSANCE	3
4.0	FIELD INVESTIGATION	4
4.1	Subsurface Drilling	4
4.2	Sample Collection	4
4.3	Standpipes and Borehole Completion	5
4.4	Groundwater Monitoring	5
4.5	PID Field Testing	5
5.0	LABORATORY TESTING	6
6.0	SITE CONDITIONS	7
6.1	Surficial Geology	7
6.2	Subsurface Conditions	7
6.2	2.1 Potential Contaminated Soils	8
7.0	ENGINEERING DISCUSSION AND RECOMMENDATIONS	g
7.1	Road Structural Section Options	g
7.1	1.1 Minimum Section Thickness	g
7.1	1.2 Subdrainage	10
7.2	Board Insulation	11
7.3	Geotextiles	11
7.4	Subdrains	12
7.5	Site Preparation	12
7.6	Reuse of Material	12
7.7	Excavation Dewatering	12
7.8	Utility Excavations	13
7.9	Utility Bedding and Backfill	13
7.10	Potential for Contaminated Soils	13
8.0	USE OF REPORT	14
9.0	CLOSING	15
10 0	DEFEDENCES	16

i

List of Figures

Figure 1	Vicinity Map
Figure 2	Borehole Location Map
Figure 3	Typical Insulated Section with Subdrains
Figure 4	Typical Insulation Section with Perforated Storm Drain
Figure 5	Typical Insulation Section





List of Appendices

Appendix A Appendix B Appendix C Appendix D Appendix E Borehole Logs Laboratory Data Historic Photography Site Photographs

SGS Laboratory Test Results





1.0 INTRODUCTION

Golder Associates Inc. (Golder) is pleased to present our geotechnical study to support the design and construction of the proposed road upgrades of Image Drive and Reflection Drive in Anchorage, Alaska (Figure 1). We understand that the goal of this project is to reconstruct the existing local roads to current standards. Expected improvements include upgrades to the road structural section including subdrain systems, curb and gutter improvements, and improvements to the existing pedestrian facilities, which may include widening the sidewalk to meet current design standards. Upgrades to the existing storm drain system will also occur, including potentially replacing a storm drain outfall near the intersection of Reflection Drive and Image Drive. The project alignment begins north of the intersection of Reflection Drive and Defiance Street intersection (Figure 1).

Image Drive and Reflection Drive are characterized as local streets, and currently exist as two 14.5-foot wide paved lanes with Type 2 curb and gutter, and with 4-foot sidewalks on one side of the road. Storm drains exist along both Image Drive and Reflection Drive.

The work presented in this report was performed in general accordance with our agreement for professional services dated March 8, 2016 (10133.00 Image Drive/Reflection Drive Area Road Reconstruction) with CRW Engineering Group, LLC (CRW), who is preparing the project plans and specifications on behalf of the Municipality of Anchorage (MOA).

Our scope of work for this project included:

- Review historical geotechnical investigations within and near the project area
- Perform a site reconnaissance to identify areas of poor pavement performance or distress and observation of the roadway corridor for possible geotechnical concerns
- Perform a field investigation, which included advancing 15 boreholes and soil sampling (Appendix A – Borehole Logs)
- Install 10 standpipes to observe groundwater levels within the project area
- Laboratory testing, including moisture content analysis, grain size distribution by sieve analysis, and hydrometer analysis for frost classification (Appendix B Laboratory Data)
- Analysis of field observations and testing results, including thermal analysis for design of pavement sections, subdrain requirement evaluation, need for geotextiles, and consideration for reuse of existing materials





2.0 HISTORICAL GEOTECHNICAL INVESTIGATIONS

A search and review of publically available data was completed for the project. The following information presents a summary of applicable data.

- JMLamb and Associates, Inc. (1984): Two test pits were advanced on Keyann Circle, presumably for housing developments in the area. One test pit, TP-1, was advanced approximately 50 feet north of the existing paved section of Keyann Circle, and the other test pit, TP-2, was advanced in the center of the circle. Subsurface conditions in both test pits consisted of sand and gravel, with little to no fines encountered. The groundwater was measured at 9.5 feet in each test pit.
- 1984 through 1986 As-Built Records for Water, Sewer, and Storm Drain Improvements: As-built drawings for the utilities installed during the initial subdivision construction show 18 basic test hole logs in the current project area. The data on the test hole logs is limited to brief soil descriptions, and based on the information presented, the test holes appear to have been advanced prior to site development. The subsurface conditions depicted on the test hole logs show that the project area typically contained a layer of surficial peat that extended to depths up to 5 feet below ground surface (bgs). Below the peat layer, sand and gravel was noted in most areas. Groundwater was not indicated on all test hole logs, but where present, it was generally less than 5 feet bgs.
- Historical Imagery: Historical aerial photographs were reviewed to help identify the history of the development in the project area. The aerial photographs were provided by CRW or obtained from other public sources for the years 1973, 1985, 1988, 1996, 2002, and 2015, and copies are presented in Appendix C. The approximate location of boreholes drilled for this study are shown on the aerial photographs for reference.
 - Based on the reviewed photography, the project area appears to be undeveloped in 1973, and the stream flowing north from Reflection Lake through the subdivision is not evident. In the 1985 photograph, the existing stream channel is present, but the general project area is still not developed. The photograph from 1988 shows that Image Drive and Reflection Drive are both under construction, and several homes are built in the area. The 1996 photography shows that most of the homes in the area have been built, and there is little change in the area between 2002 and 2015.





3.0 SITE RECONNAISSANCE

Golder conducted a visual reconnaissance of the general roadway corridor conditions prior to commencing our field investigation. Image Drive and Reflection Drive provide access to residential, single-family properties. Photographs of the general road conditions are presented in Appendix D.

Both Image Drive and Reflection Drive currently have 4-foot wide sidewalks on one side of the road. The existing roadway surface width is approximately 33 feet wide (measured to back of curb), providing two lanes of vehicle traffic. Road conditions include moderate frost cracking, especially on the west and north parts of the project, as well as persistent transverse cracks in the pavement that are likely related to the many utility connections seen in the as-built plans and differential frost heave within the trench backfill. Insulation was noted on the as-built plans for Reflection Circle over a shallow storm drain. Differential movement between insulated and uninsulated areas may contribute to the observed pavement cracking in this area, but the extent of the insulation is unclear from the available data.

There are frequent pavement patches at manholes, indicative of movement of the manholes relative to the road surface, as well as periodic depressions along the curb and over the branch of Chester Creek culvert. In addition, the Portland cement concrete sidewalks are badly broken in many areas. The broken sidewalk is likely related to poor subgrade conditions or frost movement, which is exacerbated by vehicles that were seen parking on the sidewalks in some areas and any drainage from the lots that may concentrate water to the sidewalk areas.





4.0 FIELD INVESTIGATION

The field investigation consisted of drilling and sampling 15 geotechnical boreholes (BH-01 through BH-15) on March 22 and 23, 2016 at the locations shown in Figure 2. Borehole locations were selected in consultation with CRW and followed the guidelines presented in the 2007 MOA Project Management and Engineering (PM&E) Design Criteria Manual (DCM) (Section 1.7 – Soil Investigation Standards). Prior to drilling, borehole locations were cleared by local utilities.

4.1 Subsurface Drilling

Drilling was performed by Discovery Drilling Inc. (Discovery) of Anchorage, Alaska, using a truck-mounted CME-75 drill rig equipped with nominal 8-inch outside diameter (OD) hollow-stem augers. When drilling through the asphalt pavement, an approximately 12-inch diameter hole was cut in the pavement with a saw tooth bit prior to advancing the borehole.

Golder geologist, Ms. Jessica Feenstra, supervised the field exploration program. She logged the recovered soil samples and managed the field operations. Most boreholes were advanced to a nominal depth of 15 feet bgs. The borehole located north of the intersection of Reflection Drive and Image Drive (BH-1) was advanced to 25 feet bgs. Soil samples were visually classified in the field according to the Unified Soil Classification System (USCS), which is summarized in Figure A-1 of Appendix A. The frost classification of the soil samples are described using the designations summarized in Figure A-2, which are consistent with the classification system outline in the MOA DCM (DCM, 2007). Additional soil characteristics such as consistency, moisture, texture, and relative density are noted on the borehole logs, which are presented in Appendix A (Figures A-3 through A-17).

4.2 Sample Collection

Representative disturbed samples of the soils encountered were obtained by driving a split-spoon sampler into the soil ahead of the auger, 18-inch samples were attempted at 2.5-foot intervals to 10 feet bgs with additional samples collected at 5-foot intervals thereafter. In addition, auger cuttings were collected from the surface to 24 inches bgs to evaluate materials in the existing road structural section. Recovered soil samples were visually classified before being individually sealed in polyethylene bags and transported to Golder's Anchorage laboratory for further examination, classification, and testing.

Drive samples were collected using a 3-inch OD split-spoon sampler. The sampler was driven using an auto-hammer with a 340-pound drop weight and a free fall distance of 30 inches. The number of blows required to drive the sampler through each 6-inch interval of the sampling attempt, and the number of total blows required to advance the sampler, are recorded on the borehole logs. Blow counts shown on the borehole logs are field values that have not been corrected for overburden, sampler size, or other factors.





4.3 Standpipes and Borehole Completion

Following the completion of drilling and sampling, water level monitoring standpipes were installed in 10 boreholes (Boreholes BH-02 through BH-05, BH-07, BH-09 through BH-11, BH-13, and BH-14). The standpipes consist of 1-inch PVC pipe with hand-slotting starting approximately 5 feet above the water depth encountered during drilling and continued to the bottom of the PVC. The annular space around the standpipes was backfilled with cuttings to within 2 feet of the surface, with pea gravel added to the bottom of pavement. The holes were sealed by placing cold-patch asphalt around a 7-inch flush mounted cover. Boreholes where standpipes were not installed were completed by backfilling with drill cuttings and pea gravel, and then capped with cold patch asphalt matching the existing pavement surface. Several boreholes were advanced off the road surface. In these locations, native soil was placed at ground surface. Potentially contaminated soils were encountered in Borehole BH-08, and therefore, the borehole was backfilled with chipped bentonite that were allowed to hydrate in place.

4.4 Groundwater Monitoring

Groundwater was noted when observed while drilling. Additional groundwater levels in the standpipes were measured and recorded on April 5, 2016 and again on July 15, 2016. Groundwater measurements will be collected again in the fall. Groundwater levels observed during drilling and measurements made thus far are presented on the borehole logs in Appendix A, and also in Table 1.

4.5 PID Field Testing

Collected soil samples were screened immediately after being placed into a polyurethane bag with a Photo Ionization Detector (PID) to estimate the presence of volatile organic compounds (VOC). The PID was calibrated at the beginning of each field day with 100-parts per million (ppm) isobutylene calibration gas. The PID used was equipped with a 10.6-eV lamp. Prior to screening, each sample was shaken or agitated for 15 seconds to assist volatilization. After vapor development, the PID sampling probe was inserted to about one-half the headspace depth and the highest measurement was recorded, which was normally between 2 and 5 seconds after probe insertion. Care was taken when inserting the sampling probe into the bag to avoid uptake of any moisture or soil particles. The field PID measurements are presented on the borehole logs in Appendix A.





5.0 LABORATORY TESTING

Laboratory tests were performed to measure index properties of the soil samples, which are used to develop correlations with the engineering properties of the soil. Moisture content tests were run on each soil sample and were conducted according to procedures described in ASTM D 2216. In addition, the grain size distribution (ASTM D 6913), grain size distribution with a hydrometer (ASTM D 422), Atterberg Limits (ASTM D4318), and Organic Content (ASTM D2974) were determined for selected samples.

Laboratory test results are summarized in Appendix B, Table B-1. Selected laboratory testing results are also presented on the borehole logs. Results of particle size analyses tests are presented graphically in Figures B-2 through B-5.





6.0 SITE CONDITIONS

6.1 Surficial Geology

The Image Drive/Reflection Drive subdivision is situated along the South Branch of the South Fork of Chester Creek. Historically, this area was poorly drained with shallow groundwater and several feet of peat along portions of the road, as shown in utility drawings. The peat was probably removed during construction but may be present on some of the lots and near the back of the sidewalk and curb at some locations. Below the peat, geologic mapping by R.A. Combellick with the Alaska Division of Geologic and Geophysical Surveys in 1999 indicates the presence of alluvial material overlying glacial drift, which also bounds the area on the east and west. The alluvial material is expected to be relatively free draining compared to the glacial drift.

6.2 Subsurface Conditions

Subsurface conditions encountered along the alignment primarily consisted of sand and gravel with silt to silty sand with gravel fill to depths of about 5 feet, underlain by sand and gravel with varying silt contents. Isolated zones of organic material were observed in several boreholes below the fill material. Based on our review of historic geotechnical data in the project area, the fill material was likely imported to the project site after removal of organics from beneath the roadway. The only borehole that contained significantly different soil conditions was Borehole BH-01, which silt was observed from 12.5 to 26.5 feet bgs.

The average moisture content of the fill material was measured to be approximately 5 percent. The averages fines content of the tested fill material was approximately 12 percent, and ranged from approximately 8 to 16.5 percent.

Three boreholes, Borehole BH-06, BH-08 and BH-12, were advanced off the road section, beyond the curb on the side of the road. In these boreholes, granular material was observed to the depths explored. Organic material was observed intermixed with the granular material in two of the three boreholes.

Groundwater levels were observed at the time of drilling, and measured approximately two week after completion of drilling in the ten boreholes with installed PVC standpipes. Observed and measured groundwater levels are presented below in Table 1.





Table 1: Summary of Groundwater Measurements

Borehole Number	Borehole Depth (feet)	While Drilling ⁽¹⁾ Groundwater Depth (feet)	4/5/2016 Groundwater Depth (feet)	7/15/2016 Groundwater Depth (feet)
BH-01	26.5	Not Observed	No PVC installed	No PVC installed
BH-02	16.5	4	3.4	4.0
BH-03	16.5	5	4.4	5.5
BH-04	16.5	5.3	3.9	4.3
BH-05	16.5	4.5	3.0	3.7
BH-06	16.5	5.8	No PVC installed	No PVC installed
BH-07	16.5	3.7	3.6	3.7
BH-08	16.5	5	No PVC installed	No PVC installed
BH-09	16.5	5	2.9	3.1
BH-10	16.5	5	3.8	3.5
BH-11	16.5	7	3.5	3.6
BH-12	16.5	5	No PVC installed	No PVC installed
BH-13	16.5	5	4.8(2)	4.8
BH-14	16.5	7.5	5.9	6.0
BH-15	16.5	7.5	No PVC installed	No PVC installed

Notes:

- 1) Water level depth observations were collected while drilling.
- 2) Measured on 4/13/2016 due to access constraints on 4/5/2016.

6.2.1 Potential Contaminated Soils

During the geotechnical field program, indications of potential hydrocarbon contamination in the soil was observed in a sample collected from Borehole BH-08. The sample collected from 10 to 11.5 feet bgs (Sample # 5) had a PID reading of 33.8 ppm and had a slight petroleum hydrocarbon odor. CRW was contacted immediately after encountering the potentially contaminated soil, and after discussions with CRW, the borehole was backfilled with bentonite chips.

Our scope of services did not include collecting petroleum contaminated soil samples in accordance with Alaska Department of Environmental Conservation (ADEC) guidelines and requirements. However, at the request of CRW, we submitted to the SGS North America, Inc. (SGS) laboratory in Anchorage, Alaska for chemical analysis based on the elevated PID reading and slight petroleum hydrocarbon odor. The sample was submitted for chemical analysis approximately two weeks after sampling. The sample was analyzed for Gasoline Range Organics (GRO), Diesel Range Organics (DRO), Residual Range Organics (RRO) and Benzene, Toluene, Ethylbenzene, and total Xylenes (BTEX) using the respective methods AK101, AK102, AK103, and SW8021B. The chromatogram provided by SGS for this sample indicates that the fuel present is a weathered diesel fuel. Results of the testing are presented in Appendix E.



7.0 ENGINEERING DISCUSSION AND RECOMMENDATIONS

7.1 Road Structural Section Options

Based on the findings discussed previously, we developed several road structural section options, utilizing the current version of the DCM as the reference.

7.1.1 Minimum Section Thickness

Section 1.10, "Road Structural Fill Design", of the DCM states that the mandatory road structural section design objectives are to minimize frost penetration into frost susceptible subgrade soil, movement of fine-grained soil into the structural section, and differential frost heaving. Two design methodologies for determining the minimum structural section based on frost penetration are presented in the DCM and summarized below.

- Complete Protection Method this method involves estimating the depth of frost penetration in order to determine the depth of soil that should be removed in order to contain seasonal frost penetration within the structural section.
- Limited Subgrade Frost Penetration Method this method allows for limited frost penetration in to the subgrade soil, and is based on the assumption that limited subgrade frost penetration will restrict roadway surface movements to levels that will not adversely affect pavement life or surface quality. The DCM allows for frost penetration up to 10 percent of the pavement structural section design thickness.

The Berg2 computer software program was used to calculate the estimated total frost penetration depth and required section thickness necessary to comply with the requirements of the DCM. The program uses climate parameters for Anchorage along with typical thermal parameters for the soils encountered along the road alignment. The Berg2 analysis indicated the potential for up to 10 feet of frost penetration into the sand and gravel that is typical below the existing road section. However, rigid board insulation can be used to reduce the overall depth of gravel required in the structural section.

The calculated frost penetration is related to the design freezing indices used in the Berg 2 Program, and is also affected by the moisture content of the soil during freezing, which may vary with changes in groundwater level. In addition, the calculated depth of frost penetration does not account for the effects of convective heat transfer associated with groundwater flow and the details of the site hydrogeology that could be determined with additional field investigation.

Based on our experience in the Anchorage area we expect that a reconstructed road section incorporating insulation and allowing for insulation will be less costly than a road without insulation and replacement of in situ soil with non-frost susceptible (NFS) soil for the full depth of potential frost penetration. In addition, an uninsulated section will have more potential for differential frost heave than an insulated section. Therefore, we recommend the insulated structural sections shown in Figures 3 through 5 as a base case for design. The base case section includes a minimum two inch pavement thickness, which is required by the



Municipality of Anchorage Standard Specification (MASS) for roads like those in the project area that are classified as 'Secondary Streets'.

Base Case Structural Section to Limit Frost Penetration

Asphalt Pavement	2 inches
Leveling Course	2 inches
MOA Type II-A	18 inches
Board Insulation	2 inches
MOA Type II	24 inches
MOA Type A Geotextile	
Total Section Thickness	48 inches

The calculated frost penetration with this section is 52 inches, is consistent with the allowable frost penetration described in the DCM.

Organic soils were observed in Boreholes BH-07 and BH-13 below the fill material and also observed in historical boreholes advanced in the area. Based on these findings and the prevalence of organic soils observed in the historic boreholes, we conclude that organic soils may exist at other locations along the road. All organic material encountered in road excavations should be removed and replaced with material meeting MOA Type II specifications.

7.1.2 Subdrainage

It is recommended that the road sections are constructed with subdrains. In general, water level readings suggest the groundwater table is within or just below the anticipated structural section thickness, with water measured as shallow as 2.9 feet bgs in Borehole BH-09. It is possible that seasonal or annual fluctuations in this water table can occur with the groundwater level rising into the pavement structural section in the areas where it was not encountered during the exploration. Infiltrating water and subsurface water will tend to collect in the more permeable pavement structural section fill soils. Installing subdrains will improve overall road performance where groundwater has the potential to infiltrate into the structural section.

The best overall drainage in areas of relatively shallow groundwater like at this site is typically provided by subdrains located on both sides of the road and at depths sufficient to maintain groundwater levels below the insulation and to prevent seasonal freezing of the subdrain, like those shown in Figure 3. However, the resulting subdrains are frequently relatively deep and may not be economical, especially if they do not flow by gravity and require use of lift stations, as we understand may be required at this site. A less costly drainage option that is often used in Anchorage because of limits on project funding or consideration of subdrain hydraulics is a perforated storm drain like that shown in Figure 4. This section may result in poorer structural section performance over time when compared to the use of dual subdrains. Additionally, the option shown in Figure 4 does not mitigate adverse subdrain hydraulics. Hence, the option without



subdrains shown in Figure 5 may also need to be considered at this site. The optional section shown in Figure 5 may be subject to periodic flooding of the section with an accompanied reduction in strength, as well as being more subject to frost differential movement of the road in areas where the groundwater rises above the insulation layer. Additional maintenance costs should be anticipated where subdrains or perforated storm drains cannot be used. However, we expect that road performance will be at least as good as the current uninsulated section because the frost susceptible soils in the existing road will be replaced by NFS sand and gravel.

7.2 Board Insulation

Board insulation used to insulate the road structural section should have a minimum compressive strength of 60 psi and maximum water absorption of 0.3 percent by volume in accordance with the current version of MASS. This insulation should have a minimum R-value of 9. A minimum of 18 inches of gravel fill should be placed over the insulation to protect it from being crushed by heavy wheel loads during construction. This fill layer also reduces the potential for differential icing between insulated and uninsulated pavements.

To reduce potential rolling of the curb caused by frost heave, board insulation should extend a minimum of 3 feet beyond the back of the curb or 1 foot beyond the back of the sidewalk. Past experience has shown this works well in most applications. However, in the past, MOA has reduced the width of board insulation to extend no more than 1 foot behind the back of curb when budget or right-of-way constraints exist. This approach increases the risk of the curb heaving up and rotating "curb rolling". In general, the potential for curb rolling decreases as the distance the insulation is extended behind the back of the curb is increased.

Special consideration should be given to transitions between insulated and uninsulated road structural sections. These areas include transitions at the beginning and ending of the project, intersections with cross streets, and residential driveway entrances. The insulation should extend out from the roadway section 8 to 12 feet and the thickness reduced in these areas in order to minimize potential for differential heave. The insulation can be tapered from an R-value of 9 to an R-value of 4.5 in the transition zone. Grades and cross-slopes should be maintained within the excavations and fill embankments such that the base and subbase can drain.

7.3 Geotextiles

The road design should include a geotextile at the base of the structural fill section, as shown in Figures 3 through 5. The use of a geotextile fabric should prevent migration of fines and promote lateral drainage at the base of the structural section.

To preserve the integrity of the structural sections over the frost susceptible subgrade, we recommend that a non-woven geotextile (MASS Class 2, Type A) is be placed on top of the excavated subgrade soils prior



to placement of classified fill and insulation, if used. The geotextile should also be extended up the sides of excavations.

General practice is to install the geotextile transverse to the road centerline. Placing the fabric longitudinally may result in large overlaps because fabric widths may not coincide well with the width of subgrade to be covered. Joints should be overlapped in accordance to the manufacturer's recommendation for compact subgrades. If soft or loose subgrades are encountered along the alignment, sewing of the joints may be preferred.

Additionally, consideration could be given to the use of a water-wicking geotextile, such as TenCate Mirafi H2Ri. Through special provisions, a water-wicking geotextile can be used in place of the geotextile recommended above, and under the right conditions, may help move water from the road section to subdrains. However, in areas where the groundwater is within the structural section, the water-wicking geotextile may not perform as intended.

7.4 Subdrains

If utilized, the subdrains should be designed per MASS Detail # 55-3. The surface of the excavated subgrade should be sloped a minimum of 2 percent toward the subdrain to promote drainage to the edge drainage system. The subdrains may be terminated into the drainage system manholes or other suitable outfall. Flows from the subdrains should be considered in design of the drainage system to accommodate for the added volume of water and potential icing issues.

7.5 Site Preparation

All subgrade exposed at the bottoms of excavations should be scarified, moisture conditioned, and compacted to 95 percent of the modified Proctor density (AASHTO T180).


7.6 Reuse of Material

The majority of material encountered in the upper 5 feet along the roads are considered frost susceptible. This material does not meet the specification for MOA Type II or Type II-A fill. It is recommended these soils are not reused in the new pavement section.

7.7 Excavation Dewatering

It is our understanding that storm drain utility upgrades are planned as part of the project. During drilling, groundwater was observed in all boreholes except one, Borehole BH-01. In general, groundwater was observed at depths ranging from 3.7 feet to 7.5 feet bgs while drilling. However, approximately two weeks after the completion of drilling, groundwater levels had increased in the boreholes with PVC standpipes to depths ranging from approximately 2.9 feet to 5.9 feet bgs.





Additionally, it is unknown what influence the creek has on the groundwater table within the road section. When excavating near the creek, the contractor should have provisions to manage any excess groundwater encountered in the excavations.

7.8 Utility Excavations

The near surface soils at this site are granular and classified as Type C soils in relation to the Occupational Safety and Health Administration (OSHA) 29 CFR Part 1926 Occupational Safety and Health Standards – Excavations (Subpart P). The OSHA standard limits open trenches in the anticipated type of soils to a maximum allowable slope inclination of 1.5 horizontal to 1 vertical (1.5H:1V) if a shoring system or trench box is not used. The contractor should be responsible for all slope maintenance and monitoring during excavations.

7.9 Utility Bedding and Backfill

The satisfactory performance of the flexible pipe is highly dependent upon the quality of soil under and along the sides of the pipe. Bedding and backfill material, placement, and compaction should generally conform to the requirements of the pipe manufacturer, governing utility, and the current MASS. The condition of the trench subgrade should be verified to assure all loose, frozen, or organic soil is removed from beneath the bedding materials. Granular soils were generally encountered during our investigation and are considered suitable for reuse as backfill for the utilities, provided that proper compaction and moisture conditioning can be achieved.

7.10 Potential for Contaminated Soils

Based on the measurement of volatile organics in the headspace of samples discussed in Section 6.2.1, there is a potential that petroleum hydrocarbons or other constituents may be encountered in excavations. The extent and magnitude of potentially contaminated soils is unknown at this time. If contaminated soil or groundwater is encountered in excavations or during dewatering, there could be project delays and unexpected costs. However, these additional costs can be mitigated by including provisions for handling and disposal of contaminated soil and groundwater in the specifications.





8.0 USE OF REPORT

This report has been prepared exclusively for the use of CRW in their design of the proposed road improvements along Image Drive and Reflection Drive in Anchorage, Alaska. If there are significant changes in the nature, design, or location of the facilities, we should be notified so that we may review our conclusions and recommendations in light of the proposed changes and provide a written modification or verification of the changes.

Variations are likely in subsurface conditions between explorations and also with time. Therefore, inspection and testing by a qualified geotechnical engineer should be included during construction to provide corrective recommendations adapted to the conditions revealed during the work. A contingency for unanticipated conditions should be included in the construction budget and schedule in the event corrective measures are necessary based on conditions revealed in the excavations.

This work program followed the standard of care expected of professionals undertaking similar work in the State of Alaska under similar conditions. No warranty expressed or implied is made.





9.0 CLOSING

Thank you for the opportunity to assist with this project. If you have comments or questions, please contact one of the undersigned at (907) 344-6001.

GOLDER ASSOCIATES INC.

DRAFT, NO SIGNATURES

Brenton B. Savikko, PE Senior Project Engineer John D. Thornley, PE Senior Geotechnical Engineer

Mark R. Musial, PE Principal and Geotechnical-Permafrost Practice/Program Leader

BBS/MRM/JDT/cjc/mlp






10.0 REFERENCES

- Braley, W.A., Connor, B., 1989, BERG2 Micro-Computer Estimation of Freeze and Thaw Depths and Thaw Consolidation, Prepared for State of Alaska, Department of Transportation and Public Facilities, Statewide Research.
- Combellick, R.A., 1999, Simplified geologic map and cross sections of central and east Anchorage, Alaska: Alaska Division of Geological & Geophysical Surveys Preliminary Interpretive Report 1999-1, 13 p.
- Municipality of Anchorage (MOA) Project Management & Engineering (PM&E) Department. 2007. *Design Criteria Manual (DCM), Chapter 1, Streets*.
- Municipality of Anchorage (MOA) Project Management & Engineering Department. 2015. *Municipality of Anchorage Standard Specifications (MASS)*.

Various Construction As-Built Sheets, 1984 to 1986.







CRW ENGINEERING GROUP, LLC

CONSULTANT



YYYY-MM-DD	2016-06-17
DESIGNED	-
PREPARED	APG
REVIEWED	BBS
APPROVED	

IMAGE-REFLECTION DR ROAD UPGRADES

ANCHORAGE, ALASKA

TITLE

CICINITY MAP

PROJECT NO. CONTROL REV. FIGURE 1523636 •• A
--

NOTE(S)

NOTE(S)

APPENDIX A BOREHOLE LOGS

		UNIFIED SOIL C	CLASSIFICATION (adapted t	from AST	M D2487)	
MATERIAL TYPES		ERIA FOR ASSIGNING SO COUP SYMBOLS USING LA		GROUP SOIL GROUP NAMES & LEGEN		LEGEND
	GRAVELS	CLEAN GRAVELS	C _U ≥ 4 AND 1 ≤ C _C ≤ 3	GW	WELL-GRADED GRAVEL	
o _i	>50% OF COARSE	<5% FINES	C _U < 4 AND/OR [C _C < 1 OR C _C > 3]	GP	POORLY GRADED GRAVEL	soil contains 5% sand, ac
SOILS O ON 'E	FRACTION RETAINED ON NO 4. SIEVE	GRAVELS WITH	FINES CLASSIFY AS ML OR MH	GM	SILTY GRAVEL	If soil contains 215% sand, add
AINEC AINEC		>12% FINES	FINES CLASSIFY AS CL OR CH	GC	CLAYEY GRAVEL	- vi
COARSE-GRAINED S >50% RETAINED ON NO. 200 SIEVE	SANDS	CLEAN SANDS	$C_U \ge 6$ AND $1 \le C_C \le 3$	SW	WELL-GRADED SAND	
	≥50% OF COARSE	<5% FINES	C _U < 6 AND/OR [C _C < 1 OR C _C > 3]	SP	POORLY GRADED SAND	If soil contains ≥15% gravel, add
Ö	FRACTION PASSES ON NO 4. SIEVE	SANDS AND FINES	FINES CLASSIFY AS ML OR MH	SM	SILTY SAND	f soil o 15% gr
		>12% FINES	FINES CLASSIFY AS CL OR CH	SC	CLAYEY SAND	_ N
_	SILTS AND CLAYS	ORGANIC CLA	AY OR SILT	CL	LEAN CLAY	I from 'with
SOILS SOILS	LIQUID LIMIT <50	OH, OL) if: LL (oven dried) LL (not dried)	1 < 0.75 S CH	ML	SILT	grained soil from h sand" or "with ripe is prominent,
NED 8 ASSE		7	E E	OL	ORGANIC CLAY OR SILT	se-grail
FINE-GRAINED SOILS >50% PASSES NO. 200 SIEVE	SILTS AND CLAYS	A Solution (C.) (C.) (C.) (C.) (C.) (C.) (C.) (C.)	CL MH	СН	FAT CLAY	s coar 6, add "
	LIQUID LIMIT ≥50	PLASTICITY (No. 2)	ML	МН	ELASTIC SILT	15 % to 29%, add "with sand" or "with gravel" for whichever type is prominent
			30 40 50 60 70 80 90 100 LIQUID LIMIT (LL)	ОН	ORGANIC CLAY OR SILT	If soil 15% grave
HIGHLY (ORGANIC SOILS	PRIMARILY ORGANIC MATTER, DARK IN COLOR, AND ORGANIC ODOR		PT	PEAT	23

 $\begin{array}{c} C_{\text{U}} = \frac{D_{\text{60}}}{D_{\text{10}}} \quad C_{\text{c}} = \frac{\left(D_{\text{30}}\right)^2}{D_{\text{10}} \times D_{\text{60}}} \\ \text{Gravels or sands with 5% to 12% fines require dual symbols (GW-GM, GW-GC, GP-GM, GP-GC, SW-SM, SW-SC, SP-SM, SP-SC) and add "with clay" or "with sill" to group name. If fines classify as CL-ML for GM or SM, use dual symbol GC-GM or SC-SM. <math>D_{\text{CM}}$, is soil particle diameter where X% is % finer. Optional Abbeviations: Lower case "s" after USCS group symbol denotes either "sandy" or "with sand" while "g" denotes either "gravelly" or "with gravel" \\ \end{array}

CRITERIA FOR DESCRIBING MOISTURE CONDITION (adapted from ASTM D2488)

DRY	ABSENCE OF MOISTURE, DUSTY, DRY TO THE TOUCH
MOIST	DAMP BUT NO VISIBLE WATER
WET	VISIBLE FREE WATER, USUALLY SOIL IS BELOW
	MATER TARIE

COMPONENT DEFINITIONS BY GRADATION

COMPONENT	SIZE RANGE
BOULDERS	GREATER THAN 12 in.
COBBLES	12 in. to 3 in.
GRAVEL	3 in. to #4 Sieve (4.76 mm)
COARSE GRAVEL	3 in. to 3/4 in.
FINE GRAVEL	3/4 in. to #4 (4.76 mm)
SAND	#4 (4.76 mm) to #200 (0.074 mm)
COARSE SAND	#4 (4.76 mm) to #10 (2.0 mm)
MEDIUM SAND	#10 (2.0 mm) to #40 (0.42 mm)
FINE SAND	#40 (0.42 mm) to #200 (0.074 mm)
SILT & CLAY (FINES)	SMALLER THAN #200 (0.074 mm)

RELATIVE DENSITY / CONSISTENCY ESTIMATE USING STANDARD PENETRATION TEST (SPT) VALUES

(adapted from Terzaghi and Peck 1967 and NAVFAC DM 7.1)

COHESIONLESS	COHESIVE SOILS ^(b) UNCONFINED							
RELATIVE DENSITY	(N ₁) ₆₀ (blows/ft) ^(c)	CONSISTENCY	$(N_1)_{60}$ $(blows/ft)^{(c)}$	COMPRESSIVE STRENGTH (TSF) ^(d)				
VERY LOOSE	0 - 4	VERY SOFT	0 - 2	0 - 0.25				
LOOSE	4 - 10	SOFT	2 - 4	0.25 - 0.50				
COMPACT	10 - 30	FIRM	4 - 8	0.50 - 1.0				
(MEDIUM DENSE)		STIFF	8 - 15	1.0 - 2.0				
DENSE	30 - 50	VERY STIFF	15 - 30	2.0 - 4.0				
VERY DENSE	OVER 50	HARD	OVER 30	OVER 4.0				
(a) Caila appaiation of avairal	(a) Calle appointing of gravel and and all aither apparetally as in combination page agains as abstract right of							

- (a) Soils consisting of gravel, sand, and silt, either separately or in combination possessing no characteristics of plasticity, and exhibiting drained behavior.
- (b) Soils possessing the characteristics of plasticity, and exhibiting undrained behavior.
- (c) Refer to ASTM D1586 for a definition of N value. (N₁)_{e0} is the N value corrected for hammer energy and overburden pressure, and is detailed in ASTM D6066. N values may be affected by a number of factors including; material size, sampler size, hammer weight and type, depth, drilling method, and borehole disturbance. N values are only an approximate guide for cohesive soil and do not apply to frozen soil.
- (d) Undrained shear strength, s_u= 1/2 unconfined compression strength, U_c. Note that Torvane (TV) measures s_u and pocket penetrometer (PP) measures U_c

SAMPLER ABBREVIATIONS

SS	SPT Sampler (2 in. OD, 140 lb hammer)	С	Core (Diamond Bit)
HD	Heavy Duty Split Spoon (3 in. OD, 340 lb hammer)		Thin Wall (Shelby Tube)
-BL	Brass Liners used in Split Spoon	TP	Thin Wall Piston Sampler
R	R Refual when driving Split Spoon		Modified Shelby
CA	Continous Core (Soil in Hollow-Stem Auger)		Geoprobe Macro-Core
GS	Grab Sample from Surface / Testpit		Air Rotary Cuttings
AC	Auger Charge AW Auger Wash	AG	Auger Cuttings

DESCRIPTIVE TERMINOLOGY FOR PERCENTAGES (ASTM D2488)

	`
DESCRIPTIVE	RANGE OF
TERMS	PROPORTION
TRACE	0 - 5%
FEW	5 - 10%
LITTLE	10 - 25%
SOME	30 - 45%
MOSTLY	50 - 100%

LABORATORY TEST AND NOTES ABBREVIATIONS / SYMBOLS

Con	Consolidation	PID	Photoionization Detector	TXCD	Triaxial, Consolidated Drained
Dd	Dry Density	PM	Modified Proctor (D1557)	TXCU	Triaxial, Consolidated Undrained
K	Thermal Conductivity	PP	Pocket Penetrometer (Field)	TXUU	Triaxial, Unconsolidated Undrained
MA	Sieve and Hydrometer F	PTLD	Point Load	W_L	Liquid Limit (LL)
NP	Non-plastic	SA	Sieve Analysis	W_P	Plastic Limit (PL)
OLI	Organic Loss	SpG	Specific Gravity	Ω	Soil Resistivity (Res.)
P200	Passing #200 Sieve (D1140)	TC	Thaw Consolidation/Strain	▼	Water Level
pН	Soil pH	TV	Torvane (Field)	∇	Water Level While Drilling
PI	Plasticity Index (D4318)				



9/1/15

BRARY-ANC(8-7-15).GLB [ANC SOIL LEGEND]

FROZEN SOIL CLASSIFICATION (ASTM D4083)								
1. DESCRIBE SOIL INDEPENDENT OF FROZEN STATE	CLASSIFY SOIL BY THE UNIFIED SOIL CLASSIFICATION SYSTEM							
	MAJOR (GROUP	SUBGROUP					
	DESCRIPTION DESIGNATION		DESCRIPTION		DESIGNATION			
				y bonded friable	Nf			
	Segregated ice not visible by eye	N	Well	No excess ice	Nbn			
2. MODIFY SOIL DESCRIPTION BY DESCRIPTION OF			bonded	Excess ice	Nbe			
FROZEN SOIL	Segregated ice visible by eye (ice less than 25 mm thick)		Individual ice crystals or inclusions		Vx			
		V	Ice coatings on particles		Vc			
			Random or irregularly oriented ice formations		Vr			
			Stratified or distinctly oriented ice formations		Vs			
			Uniformly distributed ice		Vu			
3. MODIFY SOIL DESCRIPTION BY DESCRIPTION OF	Ice greater than 25 mm	ICE	Ice with soil inclusions		ICE+soil type			
SUBSTANTIAL ICE STRATA	thick	ICE	Ice without soil inclusions		ICE			

FROST DESIGN SOIL CLASSIFICATION (1)

FROST GROUP ⁽²⁾	GENERAL SOIL TYPE	% FINER THAN 0.02 mm BY WEIGHT	TYPICAL USCS SOIL CLASS
NFS ⁽³⁾ [MOA NFS]	(a) Gravels Crushed stone Crushed rock	0 to 1.5	GW, GP
	(b) Sands	0 to 3	SW, SP
PFS ⁽⁴⁾ [MOA NFS]	(a) Gravels Crushed stone Crushed rock	1.5 to 3	GW, GP
[MOA F2]	(b) Sands	3 to 10	SW, SP
S1 [MOA F1]	Gravelly soils	3 to 6	GW, GP GW-GM, GP-GM, GW-GC, GP-GC
S2 [MOA F2]	Sandy soils	3 to 6	SW, SP SW-SM, SP-SM, SW-SC, SP-SC
F1 [MOA F1]	Gravelly soils	6 to 10	GM, GC, GM-GC, GW-GM, GP-GM, GW-GC, GP-GC
F2	(a) Gravelly soils	10 to 20	GW, GP GW-GM, GP-GM, GW-GC, GP-GC
[MOA F2]	(b) Sands	6 to 15	SM, SW-SM, SP-SM, SC, SW-SC, SP-SC, SM-SC
F0	(a) Gravelly soils	Over 20	GM, GC, GM-GC
F3 [MOA F3]	(b) Sands, except very fine silty sands	Over 15	SM, SC, SM-SC
[.v.o, (1 0]	(c) Clays, PI>12		CL, CH
	(a) Silts		ML, MH, ML-CL
F4	(b) Very fine silty sands	Over 15	SM, SC, SM-SC
[MOA F4]	(c) Clays, PI<12		CL, ML-CL
	(d) Varved clays or other fine- grained banded sediments		CL or CH layered with ML, MH, ML-CL, SM, SC, or SM-SC

(1) From U.S. Army Corps of Engineers (USACE), EM 1110-3-138, "Pavement Criteria for Seasonal Frost Conditions," April 1984 (2) USACE frost groups directly correspond to frost groups listed in Municipality of Anchorage (MOA) design criteria manual (DCM), 2007; except as noted.

(3) Non-frost susceptible
(4) Possibly frost susceptible, requires lab test for void ratio to determine frost design soil classification. Gravel with void ratio > 0.25 would be NFS; Gravel with void ratio < 0.25 would be S1; Sands with void ratio > 0.30 would be NFS; Sands with void ratio < 0.30



No ice-bonded soil observed

Poorly bonded or friable

Well bonded

DEFINITIONS

<u>Candled Ice</u> is ice which has rotted or otherwise formed into long columnar crystals, very loosely bonded together.

<u>Clear Ice</u> is transparent and contains only a moderate number of air bubbles.

<u>Cloudy Ice</u> is translucent, but essentially sound and non-pervious

<u>Friable</u> denotes a condition in which material is easily broken up under light to moderate pressure.

<u>Granular Ice</u> is composed of coarse, more or less equidimensional, ice crystals weakly bonded together.

<u>Ice Coatings</u> on particles are discernible layers of ice found on or below the larger soil particles in a frozen soil mass. They are sometimes associated with hoarfrost crystals, which have grown into voids produced by the freezing action.

<u>Ice Crystal</u> is a very small individual ice particle visible in the face of a soil mass. Crystals may be present alone or in a combination with other ice formations.

<u>Ice Inclusions</u> are individual ice masses visible in the face of a soil mass. Inclusions may be present alone or in a combination with other ice formations.

<u>Ice Lenses</u> are lenticular ice formations in soil occurring essentially parallel to each other, generally normal to the direction of heat loss and commonly in repeated layers.

<u>Ice Segregation</u> is the growth of ice as distinct lenses, layers, veins and masses in soils, commonly but not always oriented normal to direction of heat loss.

<u>Massive Ice</u> is a large mass of ice, typically nearly pure and relatively homogeneous.

<u>Poorly-bonded</u> signifies that the soil particles are weakly held together by the ice and that the frozen soil consequently has poor resistance to chipping or breaking.

<u>Porous Ice</u> contains numerous voids, usually interconnected and usually resulting from melting at air bubbles or along crystal interfaces from presence of salt or other materials in the water, or from the freezing of saturated snow. Though porous, the mass retains its structural unity.

<u>Thaw-Stable</u> frozen soils do not, on thawing, show loss of strength below normal, long-time thawed values nor produce detrimental settlement.

<u>Thaw-Unstable</u> frozen soils show on thawing, significant loss of strength below normal, long-time thawed values and/or significant settlement, as a direct result of the melting of the excess ice in the soil.

<u>Well-Bonded</u> signifies that the soil particles are strongly held together by the ice and that the frozen soil possesses relatively high resistance to chipping or breaking.



				R	ECC	ORD	OF I	30	RE	HOLE	ВН-	-01					SHEET 1 of 2
F	PRO	JEC	CT: Image Drive / Reflection Drive Road Upg CT NUMBER: 1523636	rade	es (CLIENT	: CRW I	Engir	neerir 22/20	ng Group, LLC 16				WGS 8			
		ATI	ON: Anchorage, AK SOIL PROFILE							ruck Mount SAMPLES				61.18			77652° W
		BORING METHOD		Τ.						BLOWS			1		VS / FT I		NOTES
EPTI	E	IG ME	DESCRIPTION	CE BOND	nscs	GRAPHIC LOG	ELEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT	WATE		TY (ppt)	△ ERCENT)	TESTS
"	,	SORIN	VEGETATION: Road	SE	Sn .	GRA	DEPTH (ft)	NON	}	340 lb Hammer (Automatic) 30 in. Drop	BE	(inch)	w. H	0 20		40 WL	
-) –	Ш	0.0 - 0.2				0.2			30 III. Drop					=	:	PID = 0.2 ppm
			Asphalt; well bonded 0.2 - 10.0				0.2								:		
-			Frozen to 5 feet, compact to dense below, dry, brown, well-graded SAND with silt and gravel; medium to coarse-grained sand, some gravel					1	GS				0		:		
			up to 1.5 inch diameter, few silt, well bonded (SW-SM, F2) [FILL]												:		
\vdash																	
																>>	PID = 0.3 ppm, Gravel = 44%,
H								2	HD	27-28-30	58	<u>18</u> 18	0			>>	Sand = 46%, Fines = 10%, MA
												18					
-																	
															:		
- 5	5				SW-SN	¹‱									:	_	PID = 0.7 ppm
								3	HD	47-20-16	36	<u>18</u> 18	0				
												10			:		
															:		
															:		,
																	PID = 0.2 ppm
								4	HD	47-12-12	24	<u>18</u> 18	0				
															:		
		nger															
1	10	Stem Auger			L												
	10	ow St	10.0 - 15.0 Compact, dry, yellowish brown, SILTY				10.0								:	-	PID = 0.2 ppm, Gravel = 39%,
		Hollow	GRAVEL with sand; gravel up to 2.5 inch diameter, some medium-grained sand, little silt			Pa 19		5	HD	27-20-22	42	<u>18</u> 18	0		:		Sand = 37%, Fines = 24%
			(GM)														
6/6/16						1979									:		
					GM										:		
BSavikko															:		
킦						100											
BOR						60									:		
ANC 1	15			-	<u> </u>	100	15.0								:		PID = 0.2 ppm -
3LB			Firm, moist, brown, SILT with sand; little medium to coarse-grained sand, trace to little				10.0					18		•			
-16).			gravel up to 1 inch diameter, Layers of increased sand and gravel content up to					6	HD	5-6-7	13	<u>18</u> 18) :		:	
C(6-3			approximately 0.5 inch to 1 inch thick (ML)														
-\ -\ -\																	
BRAF					ML												
<u>-</u>															:	:	
N.GP															:		
CTO L																	
523636 IMAGE_REFLECTION.GPJ_LIBRARY-ANC(6-3-16).GLB_[ANC_BOREHOLE]																	
	20	L	Log continued on next page			1147.											-
9 IMA		7					to 2.5 fe			10 1				J. Feens			Figure
2363			TE CIVILLE		G CON R: Erick		OR: Dis	cove	ry Dri	iiing inc.				B. Sav TE: 4/2			Figure A-3
15	-		1350CIAICS			- ' -											

SHEET 2 of 2 RECORD OF BOREHOLE BH-01 PROJECT: Image Drive / Reflection Drive Road Upgrades CLIENT: CRW Engineering Group, LLC DRILLING DATE: 3/22/2016 DATUM: WGS 84 PROJECT NUMBER: 1523636 ELEVATION: 127.5 ft 149.77652° W LOCATION: Anchorage, AK EQUIPMENT: CME-75, Truck Mount COORDS: 61.18770° N UNCORRECTED SOIL PROFILE SAMPLES **BORING METHOD** BLOWS / FT **■**20 30 40 BLOWS per 6 in DEPTH (ft) NOTES TESTS DESCRIPTION GRAPHIC LOG ELEV. ICE BOND NUMBER BLOWS PER FT REC ATT SALINITY (ppt) \triangle **USCS** WATER CONTENT (PERCENT) WATER LEVELS 340 lb Hammer (Automatic) 30 in. Drop W_P 10 VEGETATION: Road 40 W DEPTH (inch) -OW 20 30 (ft) 15.0 - 26.5 Firm, moist, brown, SILT with sand; little medium to coarse-grained sand, trace to little gravel up to 1 inch diameter, Layers of increased sand and gravel content up to approximately 0.5 inch to 1 inch thick (ML) (Continued) - 20 PID = 0.4 ppm <u>18</u> 7 HD 11 0 6-5-6 Hollow Stem Auger ML - 25 PID = 0.2 ppm8 HD 8-12-22 0 Borehole completed at 26.5 ft. 1) No groundwater observed while drilling. 2) Borehole backfilled with cuttings. 3) Asphalt cold patch installed at ground surface. - 30 6/6/1 BSavikko [ANC BOREHOLE] - 35 REFLECTION.GPJ LIBRARY-ANC(6-3-16).GLB 40 DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra Figure DRILLING CONTRACTOR: Discovery Drilling Inc. CHECKED: B. Savikko Ă-3 DRILLER: Erickson CHECK DATE: 4/29/2016

	0	SOIL PROFILE							SAMPLES				UNCORRECTED BLOWS / FT ■		
(#)	BORING METHOD	DESCRIPTION VEGETATION: Road	ICE BOND	nscs	GRAPHIC LOG	ELEV. DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)	WATE	SALINITY (ppt) 2 ER CONTENT (PE	40	NOTES TESTS WATER LEVEL
) +		0.0 - 0.3 Frozen, Asphalt; well bonded 0.3 - 2.5 Frozen, light brown, poorly graded SAND with silt and gravel; some gravel up to 1 inch diameter, few silt, well bonded (SP-SM) [FILL]	ſ	SP-SM		0.3	1	GS				0			PID = 1.1 ppm
		2.5 - 5.0 Frozen to 4 feet, loose below, wet, brown, well-graded GRAVEL with silt and sand; gravel up to 1.5 inch diameter, some medium to coarse-grained sand, few silt, well bonded visible ice as colorless inclusions (GW-GM, Vx)		GW- GM	×0000000000000000000000000000000000000	2.5	2	HD	10-16-9	25	<u>18</u> 18	0:			PID = 0.5 ppm, Gravel = 52%, Sand = 38%, Fines = 10 SA 3.4 ft 4/5/2016 4 ft 3/22/2016; WD
;		5.0 - 15.0 Loose, wet, brown, poorly graded SAND with silt and gravel; medium to coarse-grained sand, few to little gravel up to 1 inch diameter, few silt (SP-SM)				5.0	3	HD	4-4-2	6	<u>18</u> 18	0			PID = 0.7 ppm
	Hollow Stem Auger						4	HD	3-2-5	7	<u>6</u> 18		0		PID = 2.0 ppm
10				SP-SM			5	HD	5-6-5	11	<u>6</u> 18		•		PID = 0.3 ppm
5	_	15.0 - 16.5 Firm, wet, gray, sandy SILT; medium to coarse-grained sand, few gravel up to 0.5 inch diameter, little silt (SM)				15.0	6	HD	12-10-10	20	<u>12</u> 18		.		PID = 0.5 ppm
20		Notes: 1) Groundwater observed at 4 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.4 feet on 4/5/2016 4) Borehole backfilled with cuttings.													

							SAMPLES				UNCORRECTED BLOWS / FT ■	
DESCRIPTION SETATION: Road	ICE BOND	nscs	GRAPHIC LOG	ELEV. DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)	WATE	0 20 30 40 SALINITY (ppt) △ ER CONTENT (PERCENT)	NOTES TESTS WATER LEVELS
i - 0.3 izen, Asphalt; well bonded i - 7.0 izen, light brown, SILTY GRAVEL with nd; some medium to coarse-grained sand, nvel up to 1.5 inch diameter, little silt, bbles present below 5 feet, well bonded in no excess ice M, Nbn, F1) [FILL]				0.3	1	GS				0		PID = 0.5 ppm, Gravel = 44%, Sand = 43%, Fines = 13%
		GM			2	HD	25-20-13	33	<u>18</u> 18	0	•	PID = 2.0 ppm, MA
						9	0.40.7	1-	18			4/5/2016 5 ft 3/22/2016; WD PID = 1.3 ppm
1-15.5 — — — — — — — — — — — — — — — — — —	_			7.0	3	HD	9-10-7	17	18 18	0:		
impact, wer, grayisti brown, is Li 1 santb h gravel; fine to coarse-grained sand, little ivel up to 0.5 inch diameter, little silt l)					4	HD	10-12-14	26	<u>18</u> 18	0		PID = 0.3 ppm, Gravel = 28%, Sand = 40%, Fines = 32
		SM			5	HD	12-16-22	38	<u>18</u> 18	0		PID = 0.3 ppm
					6A	HD	8		<u>6</u>	0		PID = 0.5 ppm
5 - 16.5 m, moist, gray, sandy SILT with gravel; little nd, little gravel up to 1 inch diameter, low sticity L)		ML		15.5	6B	HD	5-6		<u>12</u> 12	C)	PID = 0.5 ppm
Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 5 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installer in borehole. 3) Groundwater measured at 4.4 feet on 4/5/2016 4) Borehole backfilled with cuttings.												
Notes: 1) Grou (WD). 2) Slotte in boreh 3) Grou 4) Borel	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installe lole. Individual the state of the stat	ndwater observed at 5 feet while drilling and 1-inch diameter PVC standpipe installed ole. Andwater measured at 4.4 feet on 4/5/2016. The backfilled with cuttings.	ndwater observed at 5 feet while drilling ed 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings.	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings.	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet while drilling and the service of the servi	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Indwater measured at 4.4 feet on 4/5/2016. nole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Indwater measured at 4.4 feet on 4/5/2016. Indeed backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Hole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGO	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Advanced at 4.4 feet on 4/5/2016. Inches backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED:	ndwater observed at 5 feet while drilling ad 1-inch diameter PVC standpipe installed ole. Indwater measured at 4.4 feet on 4/5/2016. Indeed backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra

age Drive / Reflection Drive Road Upgra MBER: 1523636 unchorage, AK SOIL PROFILE	ades						g Group, LLC 16 <u>ruck Mount</u> SAMPLES		ELI		64.293 ft		77475° W
DESCRIPTION ETATION: Road	ICE BOND	nscs	GRAPHIC LOG	ELEV. DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)	SALI WATER CO	20 30 INITY (ppt) △ INTENT (PE		NOTES TESTS WATER LEVELS
en, Asphalt; well bonded 2.5 en, dry, brown, poorly graded SAND with and gravel; fine to medium-grained sand, e gravel up to 0.5 inch diameter, few silt, bonded SM) [FILL]		SP-SM		0.2	1	GS				0			PID = 0.3 ppm
ten to 4 feet, compact below, gray, SILTY AVEL; gravel up to 1.5 inch diameter, e ten to coarse-grained sand, few silt, bonded with no excess ice , Nbn)				2.5	2	HD	25-27-23	50	<u>18</u> 18	0		1	PID = 0.3 ppm, Gravel = 32%, Sand = 40%, Fines = 28%, SA 3.9 ft 4/5/2016
		SM			3	HD	8-7-9	16	<u>18</u> 18	• • • • • • • • • • • • • • • • • • •			PID = 0.4 ppm 5.25 ft 3/22/2016; WD
npact, dry, gray, poorly graded GRAVEL silt and sand; gravel up to 2 inch neter, little fine to medium-grained sand, silt -GM)				7.5	4	HD	8-9-11	20	<u>18</u> 18	0			PID = 0.4 ppm
	•	GP-GM			5	HD	7-17-11	28	<u>18</u> 18	0			PID = 0.5 ppm
i - 16.5 se, dry, gray, SILTY GRAVEL with sand; e sand, little to some silt)		 GM		15.0	6	HD	19-18-14	32	<u>18</u> 18	0	•		PID = 2.8 ppm
Borehole completed at 16.5 ft. otes: () Groundwater observed at 5.3 feet while drilling VD), 1) Slotted 1-inch diameter PVC standpipe installed borehole. () Groundwater measured at 3.9 feet on 4/5/2016. () Borehole backfilled with cuttings.			<u>MITT</u>										
otes:) Groundwater ob VD).) Slotted 1-inch d borehole.) Groundwater m	oserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings.	oserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings.	oserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. leld with cuttings.	oserved at 5.3 feet while drilling iarmeter PVC standpipe installed easured at 3.9 feet on 4/5/2016. leld with cuttings.	pserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings.	pserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. leld with cuttings.	pserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings.	pserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings.	bserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. led with cuttings. DEPTH SCALE: 1 inch to 2.5 feet	pompleted at 16.5 ft. posserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. lled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGO	perpleted at 16.5 ft. Inserved at 5.3 feet while drilling iterative items of the second at 3.9 feet on 4/5/2016. Items with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feet	perpleted at 16.5 ft. Disserved at 5.3 feet while drilling iameter PVC standpipe installed easured at 3.9 feet on 4/5/2016. lled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra	perpleted at 16.5 ft. Disserved at 5.3 feet while drilling liameter PVC standpipe installed leasured at 3.9 feet on 4/5/2016. lled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra

		1	RI	ECC	ORD	OF E	30	RE	HOLE	BH-	05					SHEET 1 of 1
PRO PRO	DJE(CT: Image Drive / Reflection Drive Road Upgra	des	- 1	DRILLIN	IG DATE	: 3/2	22/20	ng Group, LLC 16		ELE	EVATIO	WGS 84 N: 65.97			
LOC	_	ON: Anchorage, AK SOIL PROFILE		l	EQUIPN	MENT: C	ME-	75, Tı	ruck Mount SAMPLES		CO	ORDS:	61.185 UNCORR			7440° W
ı	먎								BLOWS			10	BLOWS			NOTES
DEPTH (ft)	IG ME	DESCRIPTION	ICE BOND	nscs	GRAPHIC LOG	ELEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT	WATE	SALINITY R CONTE	NT (PE		TESTS WATER LEVELS
	BORING METHOD	VEGETATION: Road	ICE	ñ	GRA	DEPTH (ft)	NON	~	340 lb Hammer (Automatic) 30 in. Drop	BE	(inch)	W _P 10		30	40 W _L	
-0 -	T	0.0 - 0.2 Frozen, Asphalt; well bonded				0.2			30 III. B10p							PID = 0.4 ppm, Gravel = 41%,
		0.2 - 2.5 Frozen, moist, brown, SILTY SAND with											:			Sand = 43%, Fines = 16%, MA
_		gravel; some gravel up to 1.5 inch diameter, little silt, well bonded		SM			1	GS				0	:			
		(SM, F2) [FILL]														
_													:			
		2.5 - 7.5 Frozen to 4 feet, compact below, wet, brown,			600	2.5						:				PID = 1.7 ppm
_		poorly graded GRAVEL with silt and sand; gravel up to 2.5 inch diameter, some sand,			20		2	HD	15-10-11	21	<u>18</u> 18	0	:			3 ft ▼ 4/5/2016
		few silt, well bonded (GP-GM)			000							:	:			
					20							:	:			4.5 ft ♀
 5				GP-GM									:			3/22/2016; WD
J				J. JIV	6									•		PID = 0.3 ppm
_					600		3	HD	6-13-15	28	<u>18</u> 18	0				
					00							:	:			
_					609	-						:	:			
	Jer	7.5 - 16.5			191	7.5										PID = 0.9 ppm,
_	m Auç	Compact to dense, moist, gray, SILTY SAND with gravel; little gravel up to 1 inch diameter,				7.5					10	:				Gravel = 18%, Sand = 45%, Fines = 37%,
	Hollow Stem Auger	some silt, cobbles present (SM)			ЫΨ		4	HD	17-13-13	26	<u>18</u> 18	0	:			SA
_	음															
 10												:	:			PID = 0.4 ppm
							_		44.00.47		18		:		•	
_					101		5	HD	14-20-17	37	<u>18</u> 18	0				
													:			
_				SM												
													:			
_					Po							:	:			
												:				
_																
					Pol							:				
 15													:	_		PID = 0.7 ppm
					[[]		6	HD	20-12-15	27	<u>18</u> 18	0	:	-		
					70											
		Borehole completed at 16.5 ft.			1.4.7.								:			
_															:	
		Notes: 1) Groundwater observed at 4.5 feet while drilling (WD).										:	:	:		
		 Slotted 1-inch diameter PVC standpipe installed in borehole. 										:	:	:		
_		Groundwater measured at 3 feet on 4/5/2016. Borehole backfilled with cuttings.										:				
— 20																
	-	DEPTI	∟ IS	CALE.	1 inch	to 2.5 fe	u— et		I		LOGG	ED: .I	. Feenstr	а		
	7/	l -				OR: Disc		ry Dri	lling Inc.				B. Savikk			Figure A-7
V	Ē	Associates DRILLI	ER:	Erick	son						CHEC	K DAT	E: 4/29/2	2016		A-1

			R	ECC	DRE) C)F E	30	RE	HOLE	BH-	-06					SHEET 1 of 1
PRC PRC	JEC JEC	CT: Image Drive / Reflection Drive Road Upgr CT NUMBER: 1523636	ade	s	CLIEN DRILL	T: C	CRW E	ngin : 3/2	eerin 22/20	g Group, LLC 16			TUM: V EVATIO				
	ATI	ON: Anchorage, AK SOIL PROFILE								SAMPLES		CO		61.18 UNCOR			77357° W
I	МЕТНОБ		T			T				BLOWS			10	BLOW 20			NOTES
DEPTH (ft)	IG ME	DESCRIPTION	ICE BOND	nscs	GRAPHIC	E	LEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT		SALINIT		ERCENT)	TESTS
	BORING	SNOW DEPTH: 1" VEGETATION: Grass	SEE	Sn	GRA	DE	EPTH	NON	≱	340 lb Hammer (Automatic)	BLC	(inch)	W _P I	20	⊖W 30	W _L	WATERCEVELO
-0 -	ă	0.0 - 5.0					(ft)			30 in. Drop			10	20	50		PID = 0.6 ppm,
		Frozen, moist to wet, brown, SILTY SAND with gravel; some gravel up to 1 inch) r								:				Gravel = 35%, Sand = 49%, Fines = 16%
		diameter, medium to coarse-grained sand, trace silt, organic odor in samples, well						1	GS				0	:	:	:	
		bonded (SM)											:	:	:	:	
					0	kil Ni											
				SM	5)											PID = 0.3 ppm
												40		:			С. 15 С. 6 рр. 11
					0 6			2	HD	10-17-29	46	18 18	0	:	:		
-					5	D								:	:		
					b									:	:		
- 5				L	0								:				DID 05
Ü		5.0 - 15.0 Loose to dense, wet, brown, poorly graded			0		5.0									•	PID = 0.5 ppm
		GRAVEL with silt and sand; gravel up to 2.5 inch diameter, little to some medium to coarse-grained sand, few silt, trace organics			Poli			3	HD	16-19-15	34	<u>12</u> 18	0				5.75 ft 3/22/2016; WD
		coarse-grained sand, few silt, trace organics as rootlets (GP-GM)			0								:	:	:		3/22/2010, VVD
		(GF-GW)			2									:	:		
	L				60	9							:	:			
	Auge												i .				PID = 0.2 ppm
	Stem Auger				00	\$		4	HD	7-7-6	13	<u>18</u> 18	0	- :	:		
	Hollow 8				00									:	:		
	운				00	\$:			
					501									:	:	:	
- 10				GP-GN	1 ₀ Q	\$:	:		PID = 0.2 ppm
					50			5	HD	4-5-5	10	<u>18</u> 18	- -	:	:	:	
					00							10		:	:	:	
					201	k							:	:			
					Q _o								:	:	:	:	
					59	 								:	:		
					° Q	Ċ.											
					100									:			
-					0	ð								:	:		
					60									:	:		
- 15		15.0 - 16.5		<u></u>	[0]	1	15.0						:	:	:	:	PID = 0.2 ppm
		Compact, wet, dark gray, poorly graded SAND with silt; fine to medium-grained sand, few silt		SP-SM				6	HD	11 10 12	22	<u>18</u> 18	:	: •	l :		
		(SP-SM)		3P-3IV				6	חח	11-10-13	23	18		0			
		Borehole completed at 16.5 ft.	+			1							:	- :	- :	<u> </u>	-
													:		:		
		Notes:											:	:	:	:	
		1) Groundwater observed at 5.8 feet while drilling (WD). 2) Borehole backfilled with cuttings.											:	:	:		
		2) BOTOTOTE DACKTITIEU WILLT CULTINGS.													:		
													:	:	:		
															:		
- 20													:	:			
	7	DEPT	TH S	CALE:	1 inc	h to :	2.5 fee	et				LOGO	SED: J.	Feens	tra		
	7 <i>E</i>								y Dri	lling Inc.			KED: E				Figure A-8
V	الح	Golder DRILLI Associates	LER	: Erick	son							CHEC	K DAT	: 4/29	9/201 6		∆- 0

Forces, Asphalt well bended 22 - 25 Frozes, dry, brown, SETY SAND with gravel general control of the set of				R	ECC	ORD	OF I	30	RE	HOLE	BH-	-07					SHEET 1 of
COLTION Anthonous Anthonous Anthonous Coltion Coltio	PRO.	JEC JEC	CT: Image Drive / Reflection Drive Road Upgra	ade	es (CLIENT	: CRW I	Engir	neerir 22/20	ng Group, LLC 16							
VEGETATION Road September	LOC/	4TIC	ON: Anchorage, AK							ruck Mount			ORDS: 6	51.184	197° N		7138° W
VEGETATION Road September		볼	SOIL PROFILE	Т					_					LOWS	6 / FT		
Section Sect	€	3 ME	DESCRIPTION	QN C	ဟ္ပ	일을	ELEV.	3ER	Щ		NS F1		SA	LINIT	Y (ppt)	Δ	TESTS
Column	1	RIN	VEGETATION: Road	SE B(OSO	SRAF] M	¥	340 lb Hammer	BLO' PER		W _o		. W	w.	WATER LEVELS
Procears Apparts well bronded Doz. 25 feet Do	,	В	0.0.02	_			(ft)						10	20	30	40	PID = 0.2 ppm.
Firstern, day, brown, SET Y SAND with gravet, same graving by 1 sind, diameter, little sit (SM F2) [FILL] 25 - 36 Firstern, cash graphs brown, poorly graded SAND (GP-GM, Vol.) 50 - 30 - 30 - 30 - 30 - 30 - 30 - 30 -		,	Frozen, Asphalt; well bonded				0.2							:			Gravel = 32%, Sand = 51%, Fines = 17%,
Solid Department Solid			Frozen, dry, brown, SILTY SAND with gravel;					1	GS				0	:		:	
PD = 0.2 ppm PD = 0.4 ppm PD			well bonded		SM												
Figure date, graysh brown, poorly graded GRAVIV. Well and leading region to 15 graded shows a white instructions (GP-CML Vs) 3.6. Fit of the shows a surface instruction of the shows a surfac			(OW, 12) [FILL]														
Figure date, graysh brown, poorly graded GRAVIV. Well and leading region to 15 graded shows a white instructions (GP-CML Vs) 3.6. Fit of the shows a surface instruction of the shows a surfac																:	
thick diameter, some medium to coarse grands sock of the with borded visible ice grands and control of the property of the pro			Frozen, dark grayish brown, poorly graded			000	2.5							:		>>	PID = 0.2 ppm
granded send, down of kind with bonded visible ico granded SAND (AC) (AC) (AC) (AC) (AC) (AC) (AC) (AC)			inch diameter, some medium to coarse-			000		2	HD	22-30-28	58	<u>18</u> 18	10	:	:	:	_
S0 - 8.0 Silf, reddels brown, ORGANIC SLT with and and gravel, little gravel up to 0.25 inch organics as florous peat/tier matter (CO_3 Silf, reddels brown, ORGANIC SLT with cand and gravel, little gravel up to 0.25 inch organics as florous peat/tier matter (CO_3 Silf, reddels brown, organics as florous peat/tier matter (CO_3 Silf, reddels brown, organics peat/tier matter (CO_3 Silf, reddels brown, organics peat/tier matter (CO_3 Silf, reddels brown, organics peatified matter (GP-GM) (GP-GM)			as white inclusions		GP-GN	621										:	
Stiff, eddish brown, ORGANC SIT with said and gravel; little fire to medium-grained and, organics as throuse peaker and the said and gravel; little fire to medium-grained and, organics as throuse peaker and the said gravel up as and, even its organics present as peathree matter. 60 - 150 Compact, wet, dark gray to dark brown, poorly graded SAND matter. 60 - 150 GP-GM) 61 - 150 GP-GM) 62 - 165 Compact, wet, brown, poorly graded SAND with sitt, medium-grained sand, fev gravel up to 14 inch diameter, trace sit, trace organics (QP-GM) 63 - 165 Compact, wet, brown, poorly graded SAND with sitt, medium-grained sand, fev gravel up to 14 inch diameter, trace sit, trace organics (QP-GM) 64 - 10 - 10 - 10 - 10 - 10 - 10 - 10 - 1			(GP-GM, Vx)			200								:	:		3.7 ft
Stiff, eddish brown, ORGANC SIT with said and gravel; little fire to medium-grained and, organics as throuse peaker and the said and gravel; little fire to medium-grained and, organics as throuse peaker and the said gravel up as and, even its organics present as peathree matter. 60 - 150 Compact, wet, dark gray to dark brown, poorly graded SAND matter. 60 - 150 GP-GM) 61 - 150 GP-GM) 62 - 165 Compact, wet, brown, poorly graded SAND with sitt, medium-grained sand, fev gravel up to 14 inch diameter, trace sit, trace organics (QP-GM) 63 - 165 Compact, wet, brown, poorly graded SAND with sitt, medium-grained sand, fev gravel up to 14 inch diameter, trace sit, trace organics (QP-GM) 64 - 10 - 10 - 10 - 10 - 10 - 10 - 10 - 1						00							:	:	:	:	
Sand and gravel, little graved up to 0.2 Sind and distinct particles and distincting graved gravel g	5	ŀ				0.1149	5.0										PID = 0.2 ppm, OLI = 11%
Congrands as florous peat/tree matter (CA) - 3.0, well, defig gray to dark brown, poorly graded GRAVEL with all rand sand; grayed up to 2 inch diameter; some medium-grained sand; grayed up to 2 inch diameter; some medium-grained sand; grayed up to 2 inch diameter; some predium-grained sand; grayed up to 2 inch diameter; some predium-grained sand; grayed up to 2 inch diameter; some predium-grained sand; grayed up to 2 inch diameter; some predium-grained sand; grayed up to 14 inch diameter; trace sit, trace organics SP-SM Borehole completed at 16.5 ft. Notes: Notes			sand and gravel; little gravel up to 0.25 inch		OL	-		3A	HD	7-7	14	12 12			0		
So - 15.0 Compact, vet, dark gray to dark brown, poorly graded GRAVEL with all and sand; gravel up sand, few sell; organics present as peal/tree matter (GP-GM) OP-GM FD = 0.4 ppm FD		,	organics as fibrous peat/tree matter				6.0	3B	HD	6		6		:			PID = 0.2 ppm
graded GRAVEL with all and sand, gravel up to 2 and diameter, some endium grained said, few silt, organics present as pealtiree (GP-GM) GP-GM GP-GM			6.0 - 15.0			5 Y.		36		0		6		:	:	:	
sand, few silt, organics present as peat/tree (GP-GM) GP-GM)			graded GRAVEL with silt and sand; gravel up											:			
Sp-cm S		ger	sand, few silt, organics present as peat/tree			6 Qq								:			PID = 0.2 ppm
PID = 0.4 ppm FID =		m Au				000						10	•	:	:	:	
SP-SM Borehole completed at 16.5 ft. Sp-SM Borehole completed at 3.7 feet while drilling (V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(v Ste				609		4	HD	5-6-6	12	18				:	
SP-SM Borehole completed at 16.5 ft. Sp-SM Borehole completed at 3.7 feet while drilling (V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(V)(웨				10/19								:	:		
GP-GM 5 HD 5-7-9 16 18 18 PID=0.4 ppm TIS-0-16.5 Compact, web, brown, porty graded SAND with sitt; medium-grained sand, few gravel up to 1/4 inch diameter, trace sitt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (V) Shored 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings.		_				600								:			
GP-GM 5 HD 5-7-9 16 18 18 PID=0.4 ppm TIS-0-16.5 Compact, web, brown, porty graded SAND with sitt; medium-grained sand, few gravel up to 1/4 inch diameter, trace sitt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (V) Shored 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings.	10					0								:	:	:	DID 04
5 HD 5-7-9 16 18 O					CD CM	000								■ : :			PID = 0.4 ppm
FID = 0.4 ppm PID =					GF-GIV	 1) .1 kl· 		5	HD	5-7-9	16	<u>18</u> 18	Ō				
FID = 0.4 ppm PID =						000								:			
Tis.0 - 16.5 Compact, wet, brown, poorly graded SAND with slit; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						Po 0								:			
Tis.0 - 16.5 Compact, wet, brown, poorly graded SAND with slit; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						000								:		:	
T5.0 - 16.5 Compact, wet, brown, poorly graded SAND with silt; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						200							:	:	:	:	
T5.0 - 16.5 Compact, wet, brown, poorly graded SAND with silt; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						000											
T5.0 - 16.5 Compact, wet, brown, poorly graded SAND with silt; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						200								:	:		
T5.0 - 16.5 Compact, wet, brown, poorly graded SAND with silt; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						621											
T5.0 - 16.5 Compact, wet, brown, poorly graded SAND with silt; medium-grained sand, few gravel up to 1/4 inch diameter, trace silt, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra						541							:	:	:	:	
with sift; medium-grained sand, few gravel up to 1/4 inch diameter, trace sift, trace organics (SP-SM) Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra	15	ŀ			<u> </u>		15.0							:	<u>:</u>		PID = 0.4 ppm
Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra			with silt; medium-grained sand, few gravel up		SP-SM			6	HD	21-16-14	30	18			-		
Notes: 1) Groundwater observed at 3.7 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra					0					21.10.11		18		:	:		
1) Groundwater observed at 3.7 feet while drilling (WD). 2) Stotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra	-		Borehole completed at 16.5 ft.											:	- :	:	
1) Groundwater observed at 3.7 feet while drilling (WD). 2) Stotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra														:	:		
(WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra														:			
in borehole. 3) Groundwater measured at 3.6 feet on 4/5/2016. 4) Borehole backfilled with cuttings. DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra			(WD).											:			
DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra			in borehole.										:	:			
DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra														:	:	:	
DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra																	
DEPTH SCALE: 1 inch to 2.5 feet LOGGED: J. Feenstra	20													:			
Figure	ا غر	Z	DEDT	Ήс	SCALE:	1 inch	to 2.5 fo	et				1000	SED ! =	eenst	ra		
A-9 Accociates DRILLER: Erickson CHECK DATE: 4/29/2016		7 _A	<u> -</u>						ry Dri	lling Inc.							Figure
	V		Associates DRILL						•	-							A-9

			RI	ECC	DRE	OF I	30	RE	HOLE	BH-	-08			SHEET 1 of 1
PRC)JE(CT: Image Drive / Reflection Drive Road Upgra	ade		DRILLI	ING DATE	: 3/2	23/20			ELE	TUM: WGS EVATION: (61.65 ft	774570184
LOC	-	ON: Anchorage, AK SOIL PROFILE			<u>-QUIP</u>	WENT: C	/IVIE-	/5, I	ruck Mount SAMPLES		- 00	UNC	.18758° N 149.7 CORRECTED DWS / FT ■	7/45/* W
DEPTH (ft)	BORING METHOD	DESCRIPTION	9		ಲ	ELEV.	ii.		BLOWS per 6 in	s.⊢	REC	10	20 30 40 INITY (ppt) △	NOTES TESTS
DEF	SING.	SNOW DEPTH: 0.5"	ICE BOND	nscs	GRAPHIC	DEPTH	NUMBER	TYPE	340 lb Hammer	BLOWS PER FT	ATT (inch)	WATER CO	NTENT (PERCENT)	
_ o -	BOF	VEGETATION: Grass	ੁ		Ō	(ft)	z		(Automatic) 30 in. Drop	шп	()	10	20 30 40	PID = 0.2 ppm
		0.0 - 2.5 Frozen, dark brown, SILTY SAND with gravel; some gravel up to 0.75 inch diameter, medium			0 0	i.i.						:		F1D = 0.2 ppiii
-		to coarse-grained sand, little silt, well bonded visible ice as white coatings on particles) ::	1	GS				0		
		(SM, Vc)		SM										
-					• (2						:		
		2.5 - 5.0 Frozen, dark brown, poorly graded SAND with			0	2.5								PID = 8.7 ppm, Gravel = 43%,
_		silt and gravel; some gravel up to 1.5 inch diameter, medium to coarse-grained sand,			0	}	2	HD	43-22-13	35	<u>18</u> 18	0	•	Sand = 46%, Fines = 11%, SA
		few silt, well bonded (SP-SM)		SP-SN	0									
					0									5 ft
— 5					0)								3/23/2016; WD PID = 3.2 ppm
		5.0 - 7.5 Compact, dark brown, SILTY GRAVEL with sand; some sand, little to some silt			[0]	5.0					10			71D = 3.2 ppm
_		(GM)				<u>}</u>	3	HD	5-8-7	15	18 18			
				GM	90,	<u>}</u>								
-														
	Auger	7.5 - 15.0				7.5								PID = 3.3 ppm
-	Stem Auger	Compact, wet, dark gray, poorly graded GRAVEL with silt and sand; gravel up to 1 inch diameter, some medium to coarse-			00		4	HD	6-8-11	19	<u>18</u> 18	0		
	Hollow 8	grained sand, few silt (GP-GM)			9	Ţ.								
_	Ĭ													
— 10														PID = 33.8 ppm
					0						10	:		FID = 33.0 ppill
-					$\left[\cdot \right]$		5	HD	13-10-12	22	18 18			
				GP-GN		+								
-					60									
					00	<u></u>						:		
_					001									
						,								
					0							:		
— 15														DID = 0.6 mass
		15.0 - 16.5 Compact, wet, dark gray, SILTY GRAVEL with sand; gravel up to 1 inch diameter, some				15.0					10	:		PID = 0.6 ppm
L		medium-grained sand, little silt (GM)		GM	100		6	HD	19-19-18	37	18 18	0		
		Borehole completed at 16.5 ft.				b. T						:		-
-														
		Notes: 1) Groundwater observed at 5 feet while drilling												
<u> </u>		(WD). 2) Borehole backfilled with bentonite chips and hydrated in place.										:		
		nyarated in place.												
												:		
— 20														
		DEPT	⊥ H S	CALE:	1 inc	h to 2.5 fe	et	1	I		LOGO	ED: J. Fee	enstra	
		Golder	ING	CON	TRAC	TOR: Dis		ry Dri	lling Inc.		CHEC	CKED: B. S	avikko	Figure A-10
	ĹΞ	Accordates DRILL	ĿR	: Erick	son						CHEC	CK DATE: 4	129/2016	-

	5	SOIL PROFILE							SAMPLES			UNCORRECTED BLOWS / FT ■		
(#)	BORING ME IF	DESCRIPTION VEGETATION: Road	ICE BOND	SOSO	GRAPHIC LOG	ELEV. DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)	SALINITY (ppt) 2	40 \(\triangle \)	NOTES TESTS WATER LEVEL:
0 +	\	0.0 - 0.2 Frozen, Asphalt; well bonded 0.2 - 5.0 Frozen, brown, SILTY SAND with gravel; some gravel up to 1 inch diameter, medium to coarse-grained sand, little silt, well bonded visible ice as clear coatings on particles (SM, Vc) [FILL]				0.2	1	GS				0		PID = 0.1 ppm, Gravel = 40%, Sand = 46%, Fines = 14 SA
				SM			2	HD	19-20-12	32	<u>18</u> 18	•		PID = 0.2 ppm 2.9 ft 4/5/2016
5		5.0 - 10.0 Loose, wet, dark gray, poorly graded GRAVEL with silt and sand; gravel up to 1 inch diameter, some medium to coarse-grained sand, few silt (GP-GM)				5.0	3	HD	6-6-6	12	<u>18</u> 18	• •		5 ft 3/23/2016; WD PID = 0.3 ppm, Gravel = 46%, Sand = 43%, Fines = 11
Hollow Other Assess	Hollow Stem Auger			GP-GM			4	HD	5-6-7	13	<u>18</u> 18	0		PID = 0.5 ppm
10		10.0 - 15.0 Loose, wet, gray, SILTY SAND; fine-grained sand, little sand, trace gravel up to 0.5 inch diameter (SM)				10.0	5	HD	7-7-11	18	<u>18</u> 18	•		PID = 0.3 ppm
				SM										
15		15.0 - 16.5 Stiff, wet, dark gray, SILT; trace fine-grained sand (ML)		ML		15.0	6	HD	5-5-4	9	<u>18</u> 18	• 0		PID = 0.2 ppm
20		Notes: 1) Groundwater observed at 5 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 2.9 feet on 4/5/2016. 4) Borehole backfilled with cuttings.												

ROJ ROJ	EC.	T: Image Drive / Reflection Drive Road Upgra T NUMBER: 1523636	ade	s (CLIEN	IT: IN	CRW E G DATE	Engir : 3/2	eerin 23/20	g Group, LLC 16				WGS 84 DN: 67.			
<u>OCA</u>	TIC	ON: Anchorage, AK SOIL PROFILE								ruck Mount SAMPLES		CO	ORDS		RRECTED		7257° W
	METHOD									BLOWS			1	BLOW	'S / FT ■	40	NOTES
€	∑ S S	DESCRIPTION	ICE BOND	nscs	GRAPHIC)	ELEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT	WATE		TY (ppt) △ ENT (PEF		TESTS WATER LEVELS
	BORING	VEGETATION: Road	핑	Š	GR/	ı	DEPTH (ft)	N	<u> </u>	340 lb Hammer (Automatic) 30 in. Drop	BE	(inch)	W _P ⊢		→W `	40 W _L	
Ť		0.0 - 0.2 Frozen, Asphalt; well bonded			XXX	\otimes	0.2							:	:	:	PID = 0.2 ppm
		0.2 - 5.0 Frozen, brown, poorly graded SAND with			\bowtie	\otimes											
		gravel; some gravel, well bonded with no excess ice				$\stackrel{\times}{\otimes}$		1	GS				0		:	:	
		(SP, Nbn) [FILL]			\bowtie	$\stackrel{>}{\sim}$:	:	:	
						\otimes											DID 00
				SP		\otimes									•		PID = 0.3 ppm
						\otimes		2	HD	29-21-10	31	18 18	0	:	:	:	
						$\stackrel{\times}{\otimes}$:	:		3.8 ft 4/5/2016
					\bowtie	\otimes								:	:	i	5 ft
						\otimes	5.0							:	:	:	3/23/2016; WD PID = 0.3 ppm,
		Loose, wet, gray, SILTY GRAVEL with sand; gravel up to 1 inch diameter, some medium to					5.0					10			:		Gravel = 45%, Sand = 42%, Fines = 12
		coarse-grained sand, few to little silt (GM)).		3	HD	5-5-5	10	18 18	0				
				GM	90									:	:		
						<u>}.</u>								:	:	:	
	Auger	- 7.5 - 10.0				• ¯	7.5										PID = 0.5 ppm
	Stem Au	Compact, wet, dark gray, poorly graded SAND with silt and gravel; medium-grained sand,			0	$\left\langle \right $,		44.7.0	45	18					
	ow Ste	little gravel up to 1 inch diameter, few silt (SP-SM)		SP-SM				4	HD	11-7-8	15	18 18		0			
	Hollow			OF -OIVI	, C												
					0	$\Big\}$:	:	:	
		10.0 - 16.5			7		10.0							_ :			PID = 1.7 ppm
		Compact, wet, dark gray, poorly graded SAND with silt; fine-grained sand, trace to few silt, none to trace gravel up to 0.5 inch diameter						5	HD	6-6-8	14	<u>18</u> 18		• :			
		(SP-SM)										10		Ī			
														:	:		
														:	:	:	
				SP-SM													
														:	:		
														:		:	
5		0.5 inch thick layer of SILT (ML) at 15 feet															DID = 0.3
		0.5 Incit trick layer of SiL1 (ML) at 15 leet						6A	HD	5		6		0	:	:	PID = 0.3 ppm PID = 0.3 ppm
								6B	HD	10-16		<u>12</u> 12		0:	:	:	F1D = 0.3 ppiii
		Borehole completed at 16.5 ft.				1						12		:	- :	-	
		20.00.0 completed at 10.0 it.													:		
		Notes:												:	:		
		 Groundwater observed at 5 feet while drilling (WD). Slotted 1-inch diameter PVC standpipe installed 															
		in borehole. 3) Groundwater measured at 3.8 feet on 4/5/2016.													:		
		Borehole backfilled with cuttings.												:	:	:	
														:			
	_													:			
_=	2	DEPT.	H S	CALE:	1 inc	:h 1	to 2.5 fe	et				LOGO	SED:	l. Feens	tra		Figure A-12

[로	SOIL PROFILE				1			SAMPLES	1		UNCORRECTED BLOWS / FT ■	
(ft) BORING METHOD	DESCRIPTION OUNCE VEGETATION: Road	ICE BOND	SOSO	GRAPHIC LOG	DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)		·
	0.0 - 0.3 Frozen, Asphalt; well bonded 0.3 - 5.0 Frozen, brown, poorly graded SAND with silt and gravel; some gravel up to 1 inch diameter, few silt, well bonded with no excess ice (SP-SM, Nbn) [FILL]				0.3	1	GS	30 п. Бюр			0	PID = 0.2 ppm, Gravel = 27%, Sand = 65%, Fines = 8%
			SP-SM			2	HD	19-23-25	48	<u>18</u> 18	0	PID = 0.3 ppm
	5.0 - 15.0 Compact, wet, grayish brown, poorly graded SAND with silt and gravel; medium to coarsegrained sand, some gravel up to 2 inch diameter, few silt, cobbles present (SP-SM)				5.0	3	HD	8-11-8	19	<u>18</u> 18	0	PID = 0.4 ppm, Gravel = 44%, Sand = 48%, Fines = 99 SA
Hollow Stem Auger	Hollow Stem Auger					4	HD	7-4-4	8	18 18	0	7 ft 3/23/2016; WD PID = 0.4 ppm
			SP-SM			5	HD	4-8-8	16	<u>18</u> 18	0	PID = 1.2 ppm
	15.0 - 16.5 Dense, wet, gray, SILTY GRAVEL with sand; some sand, little to some silt (GM)				15.0	6A 6B	HD HD	17 20-37		6 6 12 12	0	PID = 2.6 ppm PID = 0.3 ppm
	Notes: 1) Groundwater observed at 7 feet while drilling (WD).			101/15								
	Slotted 1-inch diameter PVC standpipe installed in borehole. Groundwater measured at 3.5 feet on 4/5/2016. Borehole backfilled with cuttings.											

								HOLE					SHEET 1 of
PROJEC	CT: Image Drive / Reflection Drive Road Upgr CCT NUMBER: 1523636	ade	[DRILLII	NG DATE	: 3/2	23/20	g Group, LLC 16		ELE	TUM: WGS 84 EVATION: 67.177		- 4400.44
	TON: Anchorage, AK SOIL PROFILE			<u>=QUIPI</u>	MENI: C	ME-	/5, II	ruck Mount SAMPLES		<u> </u>	ORDS: 61.18680 UNCORRE	CTED	7118° W
ft) METHOD	DESCRIPTION				51.57			BLOWS			BLOWS / I	FT ■ 30 40	NOTES
(ft) NG MET	DESCRIPTION	CE BOND	nscs	GRAPHIC LOG	ELEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT	SALINITY () WATER CONTENT		TESTS WATER LEVELS
BORING	VEGETATION: Grass	CE	ő	GR/	DEPTH (ft)	ğ	-	340 lb Hammer (Automatic) 30 in. Drop	PE	(inch)	w _o W	30 40 W _L	
	0.0 - 5.0 Frozen to 2.5 feet, compact below, dark brown, SILTY SAND with gravel and organics; medium to coarse-grained sand, some gravel up to 0.5 inch diameter, few silt, organics present as rootlets, well bonded with no			0 ()		1	GS	30 III. 210p				54 ⁽	PID = 0.2 ppm, Gravel = 30%, Sand = 56%, Fines = 14%
	excess ice (SM, Nbn)		SM	0 0									
			SIVI	000		2	HD	3-2-5	7	<u>18</u> 18		0	PID = 0.2 ppm
5	5.0 - 10.0				5.0								5 ft 3/23/2016; WD PID = 0.3 ppm ♀
	Loose to compact, wet, brown, poorly graded GRAVEL with silt and sand; gravel up to 1.5 inch diameter, some medium to coarsegrained sand, few silt, organics present as rootlets, cobbles present (GP-GM)					3	HD	8-8-9	17	18 18	0		
Stem Auger			GP-GM										PID = 0.3 ppm
Hollow						4	HD	10-15-12	27	18 18	0		
10	10.0 - 15.0 Compact, wet, grayish brown, poorly graded SAND with silt and gravel; medium to coarse- grained sand, little gravel up to 1 inch diameter, few silt (SP-SM)				10.0	5	HD	14-15-17	32	<u>18</u> 18	0	•	PID = 0.3 ppm
			SP-SM	000	S								
15	15.0 - 16.5			0000	15.0								PID = 0.6 ppm
	Loose, wet, gray, poorly graded SAND with silt; medium to coarse-grained sand, few silt, few gravel up to 1 inch diameter (SP-SM)		SP-SM			6	HD	6-7-9	16	<u>12</u> 18	0		
	Borehole completed at 16.5 ft.												
	Notes: 1) Groundwater observed at 5 feet while drilling (WD). 2) Borehole backfilled with cuttings.												
20													
Â	Golder DRILL	LING		TRACT	to 2.5 fe		ry Dri	lling Inc.		CHEC	GED: J. Feenstra CKED: B. Savikko CK DATE: 4/29/20		Figure A-14

	CT: Image Drive / Reflection Drive Road Upgra							HOLE g Group, LLC			TUM: WGS 84		SHEET 1 of
PROJEC	CT NUMBER: 1523636 ION: Anchorage, AK	auc		DRILLIN	ig date	: 3/2	23/20	16		ELI	EVATION: 62.8 ORDS: 61.186	51 ft	7181° W
	•		EQUIPMENT: CME-75, Truck Mount C								UNCORE BLOWS		
(ft) BORING METHOD	DESCRIPTION VEGETATION: Road	ICE BOND	SOSO	GRAPHIC LOG	ELEV. DEPTH (ft)	NUMBER	TYPE	BLOWS per 6 in 340 lb Hammer (Automatic) 30 in. Drop	BLOWS PER FT	REC ATT (inch)	WATER CONTE	30 40 Y (ppt) △ ENT (PERCENT) W W W.	NOTES TESTS WATER LEVELS
	Frozen; Asphalt; well bonded 0.2 - 5.0 Frozen, brown, well-graded SAND with silt and gravel; some gravel up to 1.5 inch diameter, few silt, well bonded with no excess ice (SW-SM, Nbn, F2) [FILL]	/			0.2	1	GS	·			0		PID = 0.3 ppm
			SW-SM			2	HD	32-11-6	17	<u>18</u> 18	0		PID = 0.8 ppm, Gravel = 42%, Sand = 48%, Fines = 11% MA 4.8 ft 4/13/2016 5 ft
;	5.0 - 7.5 Very loose, wet, brown, SILTY SAND with gravel and organics; some gravel up to 1 inch diameter, medium to coarse-grained sand, little silt, organic material is tree matter (SM)		SM		5.0	3	HD	1-1-1	2	<u>18</u> 18	• 0	0	3/23/2016; WD PID = 0.3 ppm, Gravel = 36%, Sand = 50%, Fines = 14%
Stem Auger	7.5 - 8.5 Loose, wet, brown, SILTY SAND with gravel; medium to coarse-grained sand, some gravel up to 0.5 inch diameter, little silt		SP-SM	0 0	7.5	4A	HD	8-4		<u>12</u> 12	0		PID = 0.6 ppm
Hollow	(SP-SM) 8.5 - 10.0 Very soft, wet, dark gray, ORGANIC SILT with sand; some medium to coarse-grained sand, tree matter present (OL)		OL		8.5	4B	HD	1		6 6		.0	PID = 0.4 ppm, OLI = 5%
0	10.0 - 10.5 Very loose, wet, gray, poorly graded SAND		SM		10.0	5A	HD	3		<u>6</u> 6	0		PID = 0.5 ppm
	with silt; fine-grained sand, few silt (SM) 10.5 - 16.5 Compact, wet, grayish brown, poorly graded GRAVEL with silt and sand; gravel up to 2 inch diameter, some medium to coarse- grained sand, few silt (GP-GM)	<i>J</i>	GP-GM		10.5	5B	HD	12-17 12 0	0		PID = 0.4 ppm		
5	Porchalo completed at 16.5.ft					6	HD	16-22-20	42	<u>18</u> 18	0	•	PID = 0.4 ppm
20	Borehole completed at 16.5 ft. Notes: 1) Groundwater observed at 5 feet while drilling (WD). 2) Slotted 1-inch diameter PVC standpipe installed in borehole. 3) Groundwater measured at 4.8 feet on 4/13/2016. 4) Borehole backfilled with cuttings.	i.											
	Golder DRILL	INC		TRACT	to 2.5 fe		ry Dri	lling Inc.		CHEC	GED: J. Feensti CKED: B. Savik CK DATE: 4/29	ko	Figure A-15

								HOLE		14					SHEET 1 of
PROJE	ECT: Image Drive / Reflection Drive Road Upgra ECT NUMBER: 1523636	ade		PRILLIN	IG DATE	: 3/2	23/20			ELI	TUM: V EVATIO	N: 63.0	092 ft		
	TION: Anchorage, AK SOIL PROFILE			QUIPN	IENT: C	ME-	75, Tı	ruck Mount SAMPLES		CO		UNCOR	RECTE	D	77038° W
ft) METHOD								BLOWS			10	BLOW:	S / FT I 30	40	NOTES
(ft) NG MET	E DESCRIPTION	ICE BOND	nscs	GRAPHIC LOG	ELEV.	NUMBER	TYPE	per 6 in	BLOWS PER FT	REC ATT		SALINIT		△ ERCENT)	TESTS WATER LEVELS
BORING	VEGETATION: Road	CEE	Sn	GRA	DEPTH (ft)	N N	}	340 lb Hammer (Automatic)	BEG	(inch)	W _P I		₩ 30	—H W _L	WATERCEVEES
· + =	0.0 - 0.2							30 in. Drop							PID = 1.2 ppm,
	Frozen, Asphalt; well bonded 0.2 - 5.0				0.2										Gravel = 43%, Sand = 47%, Fines = 10%
	Frozen, brown, poorly graded SAND with silt and gravel; some gravel up to 1.5 inch			\bowtie		1	GS				0		:		SA
	diameter, few silt, well bonded with no excess ice													:	
	(SP-SM, Nbn) [FILL]			\bowtie							:				
			SP-SM	\bowtie										:	PID = 0.5 ppm
										10		:	:		
						2	HD	26-24-22	46	<u>18</u> 18	0			:	
				\bowtie							:				
	L														PID = 0.4 ppm,
	5.0 - 10.0 Loose to compact, brown, SILTY SAND with				5.0							•			Gravel = 27%, Sand = 59%, Fines = 14%
	gravel; medium to coarse-grained sand, little gravel up to 1.5 inch diameter, little silt, with no excess ice			[1]		3	HD	14-10-5	15	<u>18</u> 18	0		:		SA 5.9 ft
	(SM, Nbn)														4/5/2016
											:				7.5.4
_	-		014	[:	:	:	7.5 ft 3/23/2016; WD
Auge	Auge		SM												PID = 0.8 ppm →
Stem Auger				0		4	HD	4-5-6	11	<u>18</u> 18	0				
Hollow 8	WOOL			[0							:			:	
운												:	:	:	
												:	:		
0	10.0 - 16.5				10.0							_	:		PID = 0.6 ppm
	Loose, wet, grayish brown, poorly graded SAND; medium-grained sand, trace to few silt, thin layers of silt interbedded					5	HD	8-8-9	17	<u>18</u> 18		- C)	:	
	(SP)									18					
											:			:	
											:	:	:	:	
			SP								:	:	:	:	
			55												
														:	
5															PID = 0.9 ppm
										18	:		•		
						6	HD	7-8-19	27	18 18	:	0		:	
-	Borehole completed at 16.5 ft.										:	:	:	- :	
											:	:			
	Notes:										:		:		
	 Groundwater observed at 7.5 feet while drilling (WD). 										:			:	
	2) Slotted 1-inch diameter PVC standpipe installed in borehole.3) Groundwater measured at 5.9 feet on 4/5/2016.										:				
	Borehole backfilled with cuttings.										:	:			
											:				
0											:				
	DEDT	L 6	CAI E.	1 inch	to 2.5 fe			<u> </u>		LOGO	SED: J.	Feere	tra		
					10 2.5 Te OR: Disc		ry Dri	lling Inc.			KED: E				Figure A-16
J	Golder DRILLI Associates DRILLI						•	-			K DATE				A-16

		ON: Anchorage, AK SOIL PROFILE			_ <u>~UIFIV</u>	<u></u>	.V(L=	J, 11	SAMPLES			<u> </u>	UNCORRE BLOWS / I	CTED	7024° W
(111)	BORING METHOD	DESCRIPTION	ICE BOND	nscs	GRAPHIC LOG	ELEV.	NUMBER	TYPE	BLOWS per 6 in	BLOWS PER FT	REC ATT		SALINITY (NOTES TESTS WATER LEVELS
	BORIN	VEGETATION: Road	ICE	S	GRA	DEPTH (ft)	NON	Ţ	340 lb Hammer (Automatic) 30 in. Drop	BLC		W _P 10) 20	30 40 W.	
		0.0 - 0.2 Frozen, Asphalt; well bonded 0.2 - 7.5	/			0.2									PID = 0.6 ppm
		U.2 - 7.5 Frozen, moist, brown, well-graded SAND with silt and gravel; gravel up to 1.5 inch diameter, some medium to coarse-grained sand, few silt, well bonded (SW-SM, F2) [FILL]					1	GS				0			
							2	HD	34-28-27	55	<u>18</u> 18	0		>>I	PID = 0.4 ppm, Gravel = 41%, Sand = 49%, Fines = 10% MA
				SW-SM											PID = 0.5 ppm
							3	HD	27-12-10	22	<u>18</u> 18	0	•		
	ı														7.5 ft 3/22/2016; WD
	m Auge	7.5 - 10.0 Compact, wet, reddish brown, poorly graded SAND with gravel; some gravel up to 1.5 inch			° ()	7.5					10		•		PID = 0.6 ppm, Gravel = 48%, Sand = 49%, Fines = 3%
	Hollow Stem Auger	diameter, medium to coarse-grained sand, trace silt (SP)		SP) , ()		4	HD	8-9-10	19	<u>18</u> 18	0			SA
						10.0									PID = 0.5 ppm
		Compact, wet, yellowish brown, poorly graded GRAVEL with silt and sand; gravel up to 1 inch diameter, little medium to coarse-grained sand, few silt (GP-GM)					5	HD	9-14-12	26	<u>18</u> 18	C)		
				GP-GM											
		15.0 - 16.5 Compact, wet, brown, poorly graded SAND with gravel; medium to coarse-grained sand, some gravel up to 0.75 inch diameter, trace silt		 SP	000	15.0	6	HD	34-20-14	34	<u>18</u> 18	(Э		PID = 0.5 ppm
		(SP) Borehole completed at 16.5 ft.										:			
		Notes: 1) Groundwater observed at 7.5 feet while drilling (WD). 2) Borehole backfilled with cuttings.													
_	20		<u> </u>		4	to 2.5 fe							. Feenstra		

APPENDIX B LABORATORY DATA



6/6/1

BSavikko

SUMMARY

SAMPLE

ANC

GLB.

LIBRARY-ANC(6-3-16).

REFLECTION.GPJ

1523636 IMAGE

TABLE B-1: SAMPLE SUMMARY CRW Engineering Group, LLC Client: Project No.: 1523636 Project: Image Drive / Reflection Drive Road Upgrades Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016 SAMPLING DATA **CLASSIFICATION AND INDEX TEST RESULTS** MOISTURE (%) DEPTH (ft) **GRADATION (%)** SAMPLE LOCATION **BLOWS PER FOOT** PID HEADSPACE (ppm) SAMPLE NUMBER AMOUNT FINER THAN 0.02 mm (%) FROST CLASSIFICATION RECOVERY (%) ORGANIC CONTENT (%) DESCRIPTION (USCS) TESTS / OTHER TESTS SAMPLE TYPE FINES (SILT & CLAY) NATURAL N BOTTOM TOP BH-01 0.0 20 100 GS 5 02 1 BH-01 2 2.5 4.0 100 HD 58 4 44 46 10 6 F2 0.3 SW-SM BH-01 3 6.5 HD 36 5.0 100 3 0.7 BH-01 4 7.5 9.0 100 HD 24 3 0.2 BH-01 5 10.0 11.5 100 HD 42 6 39 37 24 0.2 GM BH-01 6 15.0 16.5 100 HD 13 10 02 BH-01 7 20.0 21.5 0.4 100 11 15 8 26.5 34 0.2 BH-01 25.0 100 HD 13 BH-02 1 0.0 2.0 100 1.1 2 52 BH-02 25 4.0 HD 25 8 38 10 0.5 GW-GM SA 100 BH-02 3 5.0 6.5 100 HD 6 0.7 BH-02 4 7.5 9.0 33 HD 7 16 2 BH-02 5 10.0 11.5 33 HD 11 14 0.3 BH-02 6 15.0 16.5 67 HD 20 0.5 11 BH-03 1 0.0 2.0 100 GS 3 44 43 13 9 0.5 2 BH-03 2.5 4.0 100 HD 33 4 F1 2 GM MA BH-03 3 5.0 6.5 100 HD 17 7 13 BH-03 4 7.5 9.0 100 HD 26 28 40 32 0.3 SM 7 BH-03 5 10.0 11.5 100 HD 38 0.3 8 6A 15.0 15.5 100 BH-03 6B HD 0.5 15.5 16.5 10 100 BH-04 0.0 2.0 100 GS 2 0.3 2 BH-04 2.5 4.0 HD 9 32 28 0.3 SM SA 100 50 40 BH-04 3 5.0 6.5 100 HD 16 10 0.4 BH-04 4 7.5 9.0 100 HD 20 7 0.4 BH-04 5 10.0 11.5 100 HD 28 6 0.5 BH-04 6 15.0 16.5 100 HD 32 7 2.8 BH-05 1 0.0 2.0 100 GS 5 41 43 16 11 F2 0.4 SM MA BH-05 2 4.0 4 2.5 100 HD 21 1.7 3 BH-05 5.0 6.5 100 HD 28 8 0.3 7.5 9.0 18 45 37 0.9 BH-05 5 HD 0.4 10.0 11.5 100 37 6



6/6/1

BSavikko

SUMMARY

SAMPLE

ANC

GLB.

LIBRARY-ANC(6-3-16)

REFLECTION.GPJ

523636 IMAGE

TABLE B-1: SAMPLE SUMMARY CRW Engineering Group, LLC Client: Project No.: 1523636 Project: Image Drive / Reflection Drive Road Upgrades Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016 SAMPLING DATA **CLASSIFICATION AND INDEX TEST RESULTS** MOISTURE (%) DEPTH (ft) **GRADATION (%)** SAMPLE LOCATION **BLOWS PER FOOT** PID HEADSPACE (ppm) SAMPLE NUMBER AMOUNT FINER THAN 0.02 mm (%) FROST CLASSIFICATION RECOVERY (%) ORGANIC CONTENT (%) DESCRIPTION (USCS) SAMPLE TYPE FINES (SILT & CLAY) TESTS / OTHER TESTS NATURAL N BOTTOM TOP BH-05 6 15.0 16.5 100 HD 27 5 0.7 BH-06 1 0.0 2.0 100 GS 7 35 49 16 0.6 SM BH-06 2 4.0 HD 46 0.3 2.5 100 8 BH-06 3 5.0 6.5 67 HD 9 0.5 BH-06 4 7.5 9.0 100 HD 13 8 0.2 BH-06 5 10.0 11.5 100 HD 10 10 02 BH-06 6 15.0 16.5 HD 0.2 100 19 2.0 4 32 17 12 F2 SM MA BH-07 1 0.0 100 GS 51 0.2 BH-07 2 2.5 4.0 100 58 12 За BH-07 5.0 6.0 HD 14 32 11 02 100 BH-07 3b 6.0 6.5 100 HD 11 0.2 BH-07 4 7.5 9.0 100 HD 12 11 0.2 BH-07 5 10.0 11.5 100 HD 10 BH-07 6 15.0 16.5 100 HD 30 0.4 14 BH-08 1 0.0 2.0 100 GS 8 0.2 2 BH-08 2.5 4.0 100 HD 35 13 43 46 11 8.7 SP-SM SA BH-08 3 5.0 6.5 100 HD 15 11 32 BH-08 4 7.5 9.0 100 HD 19 11 3.3 BH-08 5 10.0 11.5 100 HD 22 33.8 BH-08 6 15.0 16.5 100 37 0.6 BH-09 40 0.0 20 100 GS 6 46 14 0.1 SM SA 1 BH-09 2 2.5 4.0 100 HD 32 10 0.2 BH-09 3 HD 46 GP-GM 5.0 6.5 100 12 10 43 11 0.3 BH-09 4 7.5 9.0 100 HD 13 9 0.5 BH-09 5 10.0 11.5 100 HD 18 21 0.3 BH-09 6 15.0 16.5 100 HD 9 23 0.2 BH-10 1 0.0 2.0 100 GS 3 0.2 BH-10 2 2.5 4.0 100 HD 31 7 0.3 BH-10 3 6.5 0.3 5.0 100 HD 10 45 42 12 GM 4 BH-10 7.5 9.0 100 HD 15 13 0.5 5 10.0 11.5 20 1.7 BH-10 6A 15.0 HD 21 0.3 15.5 100



6/6/1

BSavikko

SUMMARY

SAMPLE

ANC

GLB

LIBRARY-ANC(6-3-16)

REFLECTION.GPJ


523636 IMAGE

TABLE B-1: SAMPLE SUMMARY CRW Engineering Group, LLC Client: Project No.: 1523636 Project: Image Drive / Reflection Drive Road Upgrades Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016 SAMPLING DATA **CLASSIFICATION AND INDEX TEST RESULTS** MOISTURE (%) DEPTH (ft) **GRADATION (%)** SAMPLE LOCATION **BLOWS PER FOOT** PID HEADSPACE (ppm) SAMPLE NUMBER AMOUNT FINER THAN 0.02 mm (%) FROST CLASSIFICATION RECOVERY (%) ORGANIC CONTENT (%) DESCRIPTION (USCS) TESTS / OTHER TESTS SAMPLE TYPE FINES (SILT & CLAY) NATURAL N BOTTOM TOP BH-10 6B 15.5 16.5 100 HD 18 0.3 BH-11 1 0.0 2.0 100 GS 7 27 65 8 0.2 SP-SM SA BH-11 2 4.0 HD 48 2.5 100 0.3 11 BH-11 3 5.0 6.5 100 HD 19 8 44 48 9 0.4 SP-SM SA BH-11 4 7.5 9.0 100 HD 8 7 0.4 BH-11 5 10.0 11.5 100 HD 16 13 1.2 BH-11 6A 15.5 HD 14 2.6 100 7 6B 15.5 HD 0.3 BH-11 16.5 100 BH-12 1 0.0 2.0 100 30 14 SM 2 BH-12 25 4.0 HD 7 38 02 100 BH-12 3 5.0 6.5 100 HD 17 0.3 BH-12 4 7.5 9.0 100 HD 27 11 0.3 BH-12 5 10.0 11.5 100 HD 32 13 0.3 BH-12 6 15.0 16.5 67 HD 16 15 0.6 BH-13 1 0.0 2.0 100 GS 6 0.3 BH-13 2 2.5 4.0 100 HD 17 10 42 48 11 5 F2 0.8 SW-SM MA BH-13 3 5.0 6.5 100 HD 2 16 36 50 14 0.3 SM BH-13 4A 7.5 8.5 100 HD 13 0.6 BH-13 4B 8.5 9.0 100 HD 32 0.4 20 5A 10.0 10.5 100 BH-13 5B 11.5 9 10.5 100 HD 04 BH-13 6 15.0 16.5 100 HD 42 0.4 SP-SM BH-14 2.0 4 43 47 10 1.2 SA 1 0.0 100 GS BH-14 2 2.5 4.0 100 HD 46 6 0.5 BH-14 3 5.0 6.5 100 HD 15 9 27 59 14 0.4 SM SA BH-14 4 7.5 9.0 100 HD 11 10 0.8 BH-14 5 10.0 11.5 100 HD 17 23 0.6 BH-14 6 15.0 16.5 100 HD 27 17 0.9 BH-15 1 0.0 2.0 100 GS 0.6 2 SW-SM BH-15 2.5 4.0 100 HD 55 41 49 10 5 F2 0.4 MA 3 5.0 6.5 BH-15 4 7.5 HD 48 3 0.6 SP 9.0 100 19 9 49 SA



		Т	ABI	LE E	3-1:	: S/	AMPLE SU	JMN	IAR	Υ					
Client:	CRW Engineering Group, LLC								ct No	.:	15236	36			
Project:	Image Drive / Reflection Drive Road Upgrades														
Location:	Anch	orage, AK						Revi	ewed l	Ву:	M. Fa	ulise		Dat	te: 4/20/2016
	SAMPLING DATA								CL	ASSIFI	CATIO	N AND IN	DEX TEST RES	SULTS	
NO.	Z DEPTH (ft)					TURE	GRADATION (%)		(%)	z	ш				

SAMPLE LOCATIC	SAMPLE NUMBER	TOP	ВОТТОМ	RECOVERY (%)	SAMPLE TYPE	BLOWS PER FOO	NATURAL MOISTL CONTENT (%)	GRAVEL	SAND	FINES (SILT & CLAY)	ORGANIC CONTENT (%)	AMOUNT FINER THAN 0.02 mm (%)	FROST CLASSIFICATION	PID HEADSPACE (ppm)	DESCRIPTION (USCS)	TESTS/ OTHER TESTS	
BH-15	5	10.0	11.5	100	HD	26	10							0.5			
BH-15	6	15.0	16.5	100	HD	34	12							0.5			






1523636 IMAGE_REFLECTION.GPJ

FIGURE B-2: SUMMARY OF PARTICLE SIZE DISTRIBUTION RESULTS

Reference(s) ASTM D422 ASTM D6913

Client: CRW Engineering Group, LLC Project No.: 1523636

Project: Image Drive / Reflection Drive Road Upgrades QA/QC By: Date: 4/15/2016 K. Sorensen Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016



GRAIN SIZE IN MILLIMETERS

CORRIEC	GRA	VEL		SAND)	SILT OD CLAV
COBBLES	coarse	fine	coarse	medium	fine	SILT OR CLAY

	Sample Location	Sample Number		USCS Classification	Сс	Cu	% Gravel	% Sand	% Fines	% < 0.02 mm
•	BH-01	2	2.5	well-graded sand with silt and gravel (SW-SM)	1.2	72.2	44	46	10	6
X	BH-02	2	2.5	well-graded gravel with silt and sand (GW-GM)	1.5	111.7	52	38	10	
•	BH-03	1	0.0	silty gravel with sand (GM)	3.0	190.1	44	43	13	9
*	BH-04	2	2.5	silty sand with gravel (SM)	-	-	3 2	40	28	
<u> </u>	BH-05	1	0.0	silty sand with gravel (SM)	2.3	374.5	41	43	16	11




FIGURE B-3: SUMMARY OF PARTICLE SIZE DISTRIBUTION RESULTS

Reference(s) ASTM D422 ASTM D6913

Client: CRW Engineering Group, LLC Project No.: 1523636

Project: Image Drive / Reflection Drive Road Upgrades QA/QC By: Date: 4/15/2016 K. Sorensen Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016



OI (/	WIN OIZE IN WI	ILLIWIL I LIKO	
	SAND)	SILT OR CLAY
		_	SILTURULAT

fine

	Sample Location	Sample Number	Depth (ft)	USCS Classification	Сс	Cu	% Gravel	% Sand	% Fines	% < 0.02 mm
•	BH-05	4	7.5	silty sand with gravel (SM)	-	-	18	45	37	
	BH-07	1	0.0	silty sand with gravel (SM)	5.0	417.0	32	51	17	12
_	BH-08	2	2.5	poorly graded sand with silt and gravel (SP-SM)	0.8	84.8	43	46	11	
*	BH-09	1	0.0	silty sand with gravel (SM)	-	-	4 0	46	14	
\odot	BH-11	1	0.0	poorly graded sand with silt and gravel (SP-SM)	1.0	14.6	27	65	8	

medium

GRAVEL

fine

coarse

coarse

COBBLES




COBBLES

FIGURE B-4: SUMMARY OF PARTICLE SIZE DISTRIBUTION RESULTS

Reference(s) ASTM D422 ASTM D6913

Client: CRW Engineering Group, LLC Project No.: 1523636

Project: Image Drive / Reflection Drive Road Upgrades QA/QC By: Date: 4/15/2016 K. Sorensen Location: Anchorage, AK Reviewed By: M. Faulise Date: 4/20/2016



GRA	VEL		SAND)	SH T OD CLAY
coarse	fine	coarse	medium	fine	SILT OR CLAT

	Sample Location	Sample Number	Depth (ft)	USCS Classification	Сс	Cu	% Gravel	% Sand	% Fines	% < 0.02 mm
•	BH-11	3	5.0	poorly graded sand with silt and gravel (SP-SM)	8.0	58.3	44	48	9	
	BH-13	2	2.5	well-graded sand with silt and gravel (SW-SM)	1.3	77.1	42	48	11	5
4	BH-14	1	0.0	poorly graded sand with silt and gravel (SP-SM)	0.8	67.8	43	47	10	
*	BH-14	3	5.0	silty sand with gravel (SM)	-	-	27	59	14	
િ	BH-15	2	2.5	well-graded sand with silt and gravel (SW-SM)	1.5	67.7	41	49	10	5




FIGURE B-5: SUMMARY OF PARTICLE SIZE DISTRIBUTION RESULTS

Reference(s) ASTM D422 ASTM D6913

Client:CRW Engineering Group, LLCProject No.:1523636

Project:Image Drive / Reflection Drive Road UpgradesQA/QC By:K. SorensenDate:4/15/2016Location:Anchorage, AKReviewed By:M. FauliseDate:4/20/2016



Sample Location	Sample Number	Depth (ft)	USCS Classification	Сс	Cu	% Gravel	% Sand	% Fines	% < 0.02 mm
BH-15	4	7.5	poorly graded sand with gravel (SP)	0.8	17.0	48	49	3	·

APPENDIX C HISTORIC PHOTOGRAPHY



APPROVED

APG BBS

REV.

PROJECT NO. 1523636

older ociate
P S S

)RAFT

L	
RA	
<u> </u>	

CONSULTANT DRAFT

1. ORTHOIMAGE DATED JULY 2002 AGDUIRED AND DISTRIBUTED BY U.S.G.S.

BOREHOLE LOCATION AND NAME

REFERENCE(S)

2016-06-1		APG	BBS	
AYYY-MM-DD	DESIGNED	PREPARED	REVIEWED	

ANCHORAGE, ALASKA

	ш
	⋖
	≧.
	₹
	₹
	Ş
	₹
	ē
Ц	<u>:S</u>
=	I

PROJECT NO. CONTROL 1523636

C-5

REV.

APPENDIX D SITE PHOTOGRAPHS

Project Title: Image/Reflection Drive Road Upgrades

PHOTO 1

Typical pavement conditions along the project area, Photo taken at Borehole BH-03.



1

PHOTO 2

Typical pavement and sidewalk conditions along project area. Photo taken near Borehole BH-02.







PHOTO 3

Cracking along road center line near Borehole BH-11.



2

PHOTO 4

Typical pavement and sidewalk conditions along project area. Photo taken near Borehole BH-10.



APPENDIX E SGS LABORATORY TEST RESULTS



Laboratory Report of Analysis

To: Golder Associates Inc.

2121 Abbott Road, #100 Anchorage, AK 99507 (907)865-2524

Report Number: 1161603

Client Project: Image/Reflection Drive

Dear Brenton Savikko,

Enclosed are the results of the analytical services performed under the referenced project for the received samples and associated QC as applicable. The samples are certified to meet the requirements of the National Environmental Laboratory Accreditation Conference Standards. Copies of this report and supporting data will be retained in our files for a period of ten years in the event they are required for future reference. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. Any samples submitted to our laboratory will be retained for a maximum of fourteen (14) days from the date of this report unless other archiving requirements were included in the quote.

If there are any questions about the report or services performed during this project, please call Victoria at (907) 562-2343. We will be happy to answer any questions or concerns which you may have.

Thank you for using SGS North America Inc. for your analytical services. We look forward to working with you again on any additional analytical needs.

Sincerely,

SGS North America Inc.

Victoria.Pennick@sgs.com

Victoria Pennick

2016.04.21

nc. 11:37:04 -08'00'

Victoria Pennick

Project Manager

Print Date: 04/20/2016 1:13:54PM

Date



Case Narrative

SGS Client: Golder Associates Inc. SGS Project: 1161603 Project Name/Site: Image/Reflection Drive Project Contact: Brenton Savikko

Refer to sample receipt form for information on sample condition.

*QC comments may be associated with the field samples found in this report. When applicable, comments will be applied to associated field samples.

Print Date: 04/20/2016 1:13:55PM



Laboratory Qualifiers

Enclosed are the analytical results associated with the above work order. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx. Attention is drawn to the limitation of liability, indenmification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the context or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS maintains a formal Quality Assurance/Quality Control (QA/QC) program. A copy of our Quality Assurance Plan (QAP), which outlines this program, is available at your request. The laboratory certification numbers are AK00971 (DW Chemistry & Microbiology) & UST-005 (CS) for ADEC and 2944.01 for DOD ELAP/ISO17025 (RCRA methods: 1020B, 1311, 3010A, 3050B, 3520C, 3550C, 5030B, 5035A, 6020A, 7470A, 7471B, 8021B, 8082A, 8260B, 8270D, 8270D-SIM, 9040C, 9045D, 9056A, 9060A, AK101 and AK102/103). Except as specifically noted, all statements and data in this report are in conformance to the provisions set forth by the SGS QAP and, when applicable, other regulatory authorities.

The following descriptors or qualifiers may be found in your report:

* The analyte has exceeded allowable regulatory or control limits.

! Surrogate out of control limits.

B Indicates the analyte is found in a blank associated with the sample.

CCV/CVA/CVB Continuing Calibration Verification
CCCV/CVC/CVCA/CVCB Closing Continuing Calibration Verification

CL Control Limit

D The analyte concentration is the result of a dilution.

DF Dilution Factor

DL Detection Limit (i.e., maximum method detection limit)
E The analyte result is above the calibrated range.
F Indicates value that is greater than or equal to the DL

GT Greater Than
IB Instrument Blank

ICV Initial Calibration Verification

J The quantitation is an estimation.

JL The analyte was positively identified, but the quantitation is a low estimation.

LCS(D) Laboratory Control Spike (Duplicate)
LOD Limit of Detection (i.e., 1/2 of the LOQ)

LOQ Limit of Quantitation (i.e., reporting or practical quantitation limit)

LT Less Than

M A matrix effect was present.

MB Method Blank

MS(D) Matrix Spike (Duplicate)

ND Indicates the analyte is not detected.
Q QC parameter out of acceptance range.

R Rejected

RPD Relative Percent Difference

U Indicates the analyte was analyzed for but not detected.

Note: Sample summaries which include a result for "Total Solids" have already been adjusted for moisture content.

All DRO/RRO analyses are integrated per SOP.

Print Date: 04/20/2016 1:13:56PM

SGS North America Inc. | 200 West Potter Drive, Anchorage, AK 99518 | t 907.562.2343 f 907.561.5301 www.us.sgs.com



Sample Summary

<u>Client Sample ID</u> <u>Lab Sample ID</u> <u>Collected</u> <u>Received</u> <u>Matrix</u>

BH-8 #5 1161603001 04/06/2016 04/06/2016 Soil/Solid (dry weight)

 Method
 Method Description

 AK101
 AK101/8021 Combo. (S)

 SW8021B
 AK101/8021 Combo. (S)

AK102 Diesel/Residual Range Organics
AK103 Diesel/Residual Range Organics

SM21 2540G Percent Solids SM2540G

Print Date: 04/20/2016 1:13:57PM



Detectable Results Summary

<u>Parameter</u>	Result	<u>Units</u>
Diesel Range Organics	37.5	mg/Kg
Residual Range Organics	38.6	mg/Kg
Gasoline Range Organics	1.44J	mg/Kg
o-Xylene	26.8J	ug/Kg
	Diesel Range Organics Residual Range Organics Gasoline Range Organics	Diesel Range Organics37.5Residual Range Organics38.6Gasoline Range Organics1.44J

Print Date: 04/20/2016 1:13:58PM



Results of BH-8 #5

Client Sample ID: BH-8 #5

Client Project ID: Image/Reflection Drive

Lab Sample ID: 1161603001 Lab Project ID: 1161603 Collection Date: 04/06/16 12:00 Received Date: 04/06/16 15:35 Matrix: Soil/Solid (dry weight)

Solids (%):89.0 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	DF	<u>Limits</u>	Date Analyzed
Diesel Range Organics	37.5	22.1	6.86	mg/Kg	1		04/12/16 13:56
Surrogates							
5a Androstane (surr)	101	50-150		%	1		04/12/16 13:56

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK102

Analyst: CJSW
Analytical Date/Time:

Analytical Date/Time: 04/12/16 13:56 Container ID: 1161603001-A Prep Batch: XXX35139
Prep Method: SW3550C
Prep Date/Time: 04/11/16 09:03
Prep Initial Wt./Vol.: 30.466 g
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	DF	<u>Limits</u>	Date Analyzed
Residual Range Organics	38.6	22.1	6.86	mg/Kg	1		04/12/16 13:56
Surrogates							
n-Triacontane-d62 (surr)	97.2	50-150		%	1		04/12/16 13:56

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK103 Analyst: CJSW

Analytical Date/Time: 04/12/16 13:56 Container ID: 1161603001-A Prep Batch: XXX35139
Prep Method: SW3550C
Prep Date/Time: 04/11/16 09:03
Prep Initial Wt./Vol.: 30.466 g
Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:13:59PM

J flagging is activated



Results of BH-8 #5

Client Sample ID: BH-8 #5

Client Project ID: Image/Reflection Drive

Lab Sample ID: 1161603001 Lab Project ID: 1161603

Collection Date: 04/06/16 12:00 Received Date: 04/06/16 15:35 Matrix: Soil/Solid (dry weight)

Solids (%):89.0 Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL 3.35	<u>DL</u> 1.01	<u>Units</u> mg/Kg	<u>DF</u> 1	Allowable Limits	Date Analyzed 04/15/16 04:51
Surrogates 4-Bromofluorobenzene (surr)	96	50-150		%	1		04/15/16 04:51

Batch Information

Analytical Batch: VFC12962 Analytical Method: AK101

Analyst: S.P

Analytical Date/Time: 04/15/16 04:51 Container ID: 1161603001-B

Prep Batch: VXX28685 Prep Method: SW5035A Prep Date/Time: 04/06/16 12:00 Prep Initial Wt./Vol.: 51.295 g Prep Extract Vol: 30.6335 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	8.40 ∪	16.8	5.37	ug/Kg	1		04/15/16 04:51
Ethylbenzene	16.8 U	33.5	10.5	ug/Kg	1		04/15/16 04:51
o-Xylene	26.8 J	33.5	10.5	ug/Kg	1		04/15/16 04:51
P & M -Xylene	33.5 ∪	67.1	20.1	ug/Kg	1		04/15/16 04:51
Toluene	16.8 ∪	33.5	10.5	ug/Kg	1		04/15/16 04:51
Surrogates							
1,4-Difluorobenzene (surr)	95.7	72-119		%	1		04/15/16 04:51

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B

Analyst: S.P

Analytical Date/Time: 04/15/16 04:51 Container ID: 1161603001-B

Prep Batch: VXX28685 Prep Method: SW5035A Prep Date/Time: 04/06/16 12:00 Prep Initial Wt./Vol.: 51.295 g Prep Extract Vol: 30.6335 mL

Print Date: 04/20/2016 1:13:59PM

J flagging is activated



Method Blank

Blank ID: MB for HBN 1731160 [SPT/9866]

Blank Lab ID: 1318918

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by SM21 2540G

 Parameter
 Results
 LOQ/CL
 DL
 Units

 Total Solids
 100
 %

Batch Information

Analytical Batch: SPT9866 Analytical Method: SM21 2540G

Instrument: Analyst: K.W

Analytical Date/Time: 4/7/2016 7:53:00PM

Print Date: 04/20/2016 1:14:00PM



Duplicate Sample Summary

Original Sample ID: 1161579002 Duplicate Sample ID: 1318919

QC for Samples: 1161603001

Analysis Date: 04/07/2016 19:53 Matrix: Soil/Solid (dry weight)

Results by SM21 2540G

NAME	<u>Original</u>	<u>Duplicate</u>	<u>Units</u>	RPD (%)	RPD CL
Total Solids	81.8	82.5	%	0.83	(< 15)

Batch Information

Analytical Batch: SPT9866 Analytical Method: SM21 2540G

Instrument: Analyst: K.W

Print Date: 04/20/2016 1:14:02PM



Method Blank

Blank ID: MB for HBN 1731617 [VXX/28685]

Blank Lab ID: 1319812

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK101

ParameterResultsLOQ/CLDLUnitsGasoline Range Organics1.25U2.500.750mg/Kg

Surrogates

4-Bromofluorobenzene (surr) 76.4 50-150 %

Batch Information

Analytical Batch: VFC12962 Prep Batch: VXX28685 Analytical Method: AK101 Prep Method: SW5035A

Instrument: Agilent 7890A PID/FID Prep Date/Time: 4/14/2016 8:00:00AM

Analyst: S.P Prep Initial Wt./Vol.: 50 g Analytical Date/Time: 4/14/2016 7:38:00PM Prep Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:03PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VXX28685]

Blank Spike Lab ID: 1319815 Date Analyzed: 04/14/2016 20:54

QC for Samples: 1161603001 Spike Duplicate ID: LCSD for HBN 1161603

[VXX28685]

Spike Duplicate Lab ID: 1319816 Matrix: Soil/Solid (dry weight)

Results by AK101

			_						
	В	lank Spike	(mg/Kg)	S	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	<u>CL</u>	RPD (%)	RPD CL
Gasoline Range Organics	12.5	13.5	108	12.5	14.3	114	(60-120)	5.30	(< 20)
Surrogates									
4-Bromofluorobenzene (surr)	1.25	85	85	1.25	88.4	88	(50-150)	3.90	

Batch Information

Analytical Batch: VFC12962 Analytical Method: AK101

Instrument: Agilent 7890A PID/FID

Analyst: S.P

Prep Batch: VXX28685 Prep Method: SW5035A

Prep Date/Time: 04/14/2016 08:00

Spike Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:05PM



Matrix Spike Summary

Original Sample ID: 1161564001 MS Sample ID: 1319817 MS MSD Sample ID: 1319818 MSD

QC for Samples: 1161603001

Analysis Date: 04/15/2016 1:21 Analysis Date: 04/15/2016 1:41 Analysis Date: 04/15/2016 2:00

Matrix: Soil/Solid (dry weight)

Results by **AK101**

		Matrix Spike (mg/Kg)		Spike Duplicate (mg/Kg)					
Parameter Gasoline Range Organics	Sample 2.09U	<u>Spike</u> 9.46	Result 9.31	Rec (%) 98	<u>Spike</u> 9.46	Result 9.54	Rec (%) 101	<u>CL</u> 60-120	RPD (%) RPD CL (< 20)
Surrogates 4-Bromofluorobenzene (surr)		0.946	0.780	82	0.946	0.799	85	50-150	2.50

Batch Information

Analytical Batch: VFC12962 Analytical Method: AK101 Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/15/2016 1:41:00AM

Prep Batch: VXX28685

Prep Method: AK101 Extraction (S)
Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 68.69g Prep Extract Vol: 25.00mL

Print Date: 04/20/2016 1:14:06PM



Method Blank

Blank ID: MB for HBN 1731617 [VXX/28685]

Blank Lab ID: 1319812

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by SW8021B

<u>Parameter</u>	Results	LOQ/CL	<u>DL</u>	<u>Units</u>
Benzene	6.25U	12.5	4.00	ug/Kg
Ethylbenzene	12.5U	25.0	7.80	ug/Kg
o-Xylene	12.5U	25.0	7.80	ug/Kg
P & M -Xylene	25.0U	50.0	15.0	ug/Kg
Toluene	12.5U	25.0	7.80	ug/Kg
Surrogates				
1.4-Difluorobenzene (surr)	96.1	72-119		%

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/14/2016 7:38:00PM

Prep Batch: VXX28685 Prep Method: SW5035A

Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 50 g Prep Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:07PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VXX28685]

Blank Spike Lab ID: 1319813 Date Analyzed: 04/14/2016 19:57

QC for Samples: 1161603001

Spike Duplicate ID: LCSD for HBN 1161603

[VXX28685]

Spike Duplicate Lab ID: 1319814 Matrix: Soil/Solid (dry weight)

Results by SW8021B

	E	Blank Spike	(ug/Kg)	S	pike Duplic	ate (ug/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	1250	1320	106	1250	1350	108	(75-125)	2.30	(< 20)
Ethylbenzene	1250	1330	107	1250	1370	109	(75-125)	2.40	(< 20)
o-Xylene	1250	1330	106	1250	1370	110	(75-125)	3.20	(< 20)
P & M -Xylene	2500	2700	108	2500	2760	111	(80-125)	2.30	(< 20)
Toluene	1250	1480	118	1250	1510	121	(70-125)	2.00	(< 20)
Surrogates									
1,4-Difluorobenzene (surr)	1250	97.6	98	1250	97.8	98	(72-119)	0.14	

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Prep Batch: VXX28685
Prep Method: SW5035A

Prep Date/Time: 04/14/2016 08:00

Spike Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:09PM



Matrix Spike Summary

Original Sample ID: 1161564001 MS Sample ID: 1319817 MS MSD Sample ID: 1319818 MSD

QC for Samples: 1161603001

Analysis Date: 04/15/2016 1:21 Analysis Date: 04/15/2016 1:41 Analysis Date: 04/15/2016 2:00 Matrix: Soil/Solid (dry weight)

Results by SW8021B

		Mat	rix Spike (ι	ıg/Kg)	Spike	Duplicate	(ug/Kg)			
<u>Parameter</u>	Sample	Spike	Result	Rec (%)	Spike	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	10.4U	946	1003	106	946	1016	107	75-125	1.20	(< 20)
Ethylbenzene	20.9U	946	982	104	946	1002	106	75-125	1.90	(< 20)
o-Xylene	20.9U	946	967	102	946	988	104	75-125	2.10	(< 20)
P & M -Xylene	41.7U	1892	1944	103	1892	1985	105	80-125	2.30	(< 20)
Toluene	20.9U	946	990	105	946	1006	106	70-125	1.60	(< 20)
Surrogates										
1,4-Difluorobenzene (surr)		946	941	100	946	923	98	72-119	1.90	

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/15/2016 1:41:00AM

Prep Batch: VXX28685

Prep Method: AK101 Extraction (S)
Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 68.69g Prep Extract Vol: 25.00mL

Print Date: 04/20/2016 1:14:10PM



Method Blank

Blank ID: MB for HBN 1731261 [XXX/35139]

Blank Lab ID: 1319120

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK102

LOQ/CL Results <u>Units</u> <u>Parameter</u> DL Diesel Range Organics 10.0U 20.0 6.20 mg/Kg

Surrogates

5a Androstane (surr) 97.9 60-120 %

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK102 Instrument: Agilent 7890B R

Analyst: CJSW

Analytical Date/Time: 4/12/2016 1:17:00PM

Prep Batch: XXX35139 Prep Method: SW3550C

Prep Date/Time: 4/11/2016 9:03:02AM

Prep Initial Wt./Vol.: 30 g Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:11PM

SGS North America Inc.



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VVV3X1328

Blank Spike La5 ID: 13121] 1 Date 9 nalt Aey: 0zdl] d 016 13:] 4

KC for SaP pleR 1161603001

Spike D/ pliuabe ID: LCSD for HBN 1161603

[VVV3X1328

Spike D/ pliuabe La5 ID: 13121]] s abriM SoiloSoliy xyrt (eiwgbh

ceR/lbR5t AK102

	В	lank Spike >	Pwd/wh	Sp	oike D/ pliua	abe xPwd%wh			
<u>) araP eber</u>	<u>Spike</u>	c eR/ lb	<u>c eu xmh</u>	Spike	ceR/lb	<u>c eu xmh</u>	CL	<u>c) Dxmh</u>	c) DCL
DieRel canwe QrwaniuR	164	141	103	164	12-	112	x4XG]Xh	1z.60	xO] 0 h
Surrogates									
Xa 9 nyroRoane xR/rrh	3.33	10z	10z	3.33	116	116	x60G]0h	11.30	

Batch Information

9 nalt bual Babug: XFC12329 9 nalt bual s ebgoy: AK102 InRor/ Penb Agilent 7890B R

9 nalt Rb CJSW

) rep Babug: XXX35139) rep s ebgoy: SW3550C

) rep DabeckiPe: 04/11/2016 09:03

Spike InibT bd/\dol.: 164 P wd/\dol EMbraubV\dol: 1 P L D/ pe InibT bd/\dol.: 164 P wd/\dol EMbraubV\dol: 1 P L

) rinbDabe: 0zd 0d 016 1:1z:1]) s



Method Blank

Blank ID: MB for HBN 1731261 [XXX/35139]

Blank Lab ID: 1319120

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK103

ParameterResultsLOQ/CLDLUnitsResidual Range Organics10.0U20.06.20mg/Kg

Surrogates

nA riacontaneAd62 (surr) 100 60Al20 %

Batch Information

Fnalytical Batch: X8C12329 Fnalytical Method: FK103 Instrument: Fgilent 7J90B R

Fnalyst: CVST

Fnalytical Date/- ime: 4/12/2016 1:17:00PM

Prep Batch: XXX35139 Prep Method: ST 3550C

Prep Date/- ime: 4/11/2016 9:03:02FM

Prep Initial T t./Vol.: 30 g Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:13PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VVV3X1328

Blank Spike La5 ID: 13121] 1 Date 9 nalt Aey: 0zdl] d 016 13:] 4

KC for SaP pleR 1161603001

Spike D/ pliuabe ID: LCSD for HBN 1161603

[VVV3X1328

Spike D/ pliuabe La5 ID: 13121]] s abriM SoildSoliy xyrt (eiwgbh

ceR/lbR5t AK102

			_						
	В	lank Spike	xPwd%wh	SI	oike D/ pliua	abe xPwd/wh			
<u>) araP eber</u>	Spike	c eR/ lb	<u>c eu xmh</u>	<u>Spike</u>	ceR/lb	<u>c eu xmh</u>	<u>CL</u>	<u>c)Dxmh</u>	c) DCL
c eRy/ al c anwe QrwaniuR	164	1X6	2z	164	14X	10X	x60@]0h	11.60	xO] 0 h
Surrogates									
nGriauonbane(§6) xR/rrh	3.33	<<	<<	3.33	22.X	100	x60G]0h	1] .30	

Batch Information

9 nalt bual Babug: XFC13239 9 nalt bual s ebgoy: AK102 InRor/ Penb Agilent 7890B R

9 nalt Rb CJSW

) rep Babug: XXX25129) rep s ebgoy: SW2550C

) rep Dabed iPe: 04/11/3016 09:02

Spike InibT bd/\dol.: 164 P wd/\dol EMbraubV\dol: 1 P L D/ pe InibT bd/\dol.: 164 P wd/\dol EMbraubV\dol: 1 P L

) rinbDabe: 0zd 0d 016 1:1z:1z) s



SGS North America Inc. CHAIN OF CUSTODY RECORD

1161603

Maryland New York as Nationwide

Kentucky Indiana

ww.us.sqs.com

	- po- ofe-				REMARKS/			Data Deliverable Requirements:	chewatigram	ictions:		Chain of Custody Seal: (Circle)	INTACT BROKEN ABSENT (See attached Sample Receipt Form)
structions: Sections 1 - 5 must be filled out. Omissions may delay the onset of analysis.	Preservative							DOD Project? Yes No	7	umaround Time and/or Special In			Ambient (CK. Sample Receipt Form)
Instructions: Sections 1 Omissions may delay t			(gizo x (Eoi)	08/10 8/10 8/10	CAKIL GRO/ CAKIL DRO/	×		Section 4	Cooler ID:	Requested		Temp Blank °C;	(See atta
Instru	Section 3	* 0		Num Num	Incre- mental Solls								Received For Laboratory By:
	2524		der.com		MATRIX	Soil		Received By:		Received By:	Received By:		Received For
	-598-20		Koegol	13636	TIME	12:00		Time	15:35	Time	Time		Time /535
ATES	PHONE NO: 907-865-2524	PROJECTI PWSID/ PERMITIS:	E-MAIL: BSavikKo@golder.com	QUOTE#: 1523636	DATE mm/dd/yy	01/20/10		Date	91/00/10	Date	Date		Date 4/6/16
CLIENT: GOLDER ASSOCIATES	Brenton Swikko PH	ge/Reflection		S	SAMPLE IDENTIFICATION	BH-8 #5		1 By: (1)	Brenton SaviKKO	By: (2)	By: (3)	/	By: (4)
CLIENT:	Brento,	PROJECT NAME: I,WAG		COD I de (RESERVED for lab use	086	Section 2	Relinquished By: (1)	Brento	Relinquished By: (2)	Relinquished By: (3)		Relinquished By: (4)

http://www.sgs.com/terms-and-conditions

[] 200 W. Potter Drive Anchorage, AK 99518 Tel: (907) 562-2343 Fax: (907) 561-5301 [] 5500 Business Drive Wilmington, NC 28405 Tel: (910) 350-1903 Fax: (910) 350-1557



1161603



SAMPLE RECEIPT FORM

Review Criteria:	Yes	N/A	No	Comments/Action Taken:
Were custody seals intact? Note # & location, if applicable. COC accompanied samples?		✓	H	Exemption permitted if sampler hand carries/delivers.
	<u> </u>	+	- - 	E
Temperature blank compliant* (i.e., 0-6°C after CF)?		H	-	Exemption permitted if chilled & collected <8 hrs ago.
If >6 °C, were samples collected <8 hours ago?	✓	H	H	
If <0 °C, were all sample containers ice free?	ш	V	Ш	
Cooler ID: @ ambient w/ Therm.ID:				
Cooler ID: @ w/ Therm.ID:				
Cooler ID: w/ Therm.ID:				
Cooler ID: w/ Therm.ID:				
Cooler ID: @ w/ Therm.ID:				
If samples are received <u>without</u> a temperature blank, the "cooler				
temperature" will be documented in lieu of the temperature blank & "COOLER TEMP" will be noted to the right. In cases where neither a				Note: Identify containers received at non-compliant
temp blank <u>nor</u> cooler temp can be obtained, note "ambient" or "chilled."				temperature. Use form FS-0029 if more space is needed.
Delivery method (specify all that apply): Client (hand carried)				
USPS Lynden AK Air Alert Courier				
UPS DFedEx DRAVN DC&D Delivery				
□Carlile □Pen Air □Warp Speed□Other:				
To WO with sinkills was the WO & sinkill				
→ For WO# with airbills, was the WO# & airbill		\checkmark		
info recorded in the Front Counter eLog?	ш	V	Ш	
	Yes	N/A	No	
Were samples received within hold time?	\checkmark	П	П	Note: Refer to form F-083 "Sample Guide" for hold times.
Do samples match COC* (i.e., sample IDs, dates/times collected)?	<u></u>	Ħ	Ħ	Note: If times differ <1hr, record details and login per COC.
Were analyses requested unambiguous?	7	Ħ	Ħ	
Were samples in good condition (no leaks/cracks/breakage)?	7	Ħ	Ħ	
Packing material used (specify all that apply): Bubble Wrap		ш	ш	
Separate plastic bags Vermiculite Other:				
Were proper containers (type/mass/volume/preservative*) used?	П	П	√	Exemption permitted for metals (e.g., 200.8/6020A).
Were Trip Blanks (i.e., VOAs, LL-Hg) in cooler with samples?	Ħ	./		
Were all VOA vials free of headspace (i.e., bubbles <6 mm)?	Ħ	Ž	Ħ	Samples were sub-sampled and extracted by lab
Were all soil VOAs field extracted with MeOH+BFB?	Ħ			upon receipt
For preserved waters (other than VOA vials, LL-Mercury or			V	
microbiological analyses), was pH verified and compliant ?		7		
If pH was adjusted, were bottles flagged (i.e., stickers)?	H		H	
For special handling (e.g., "MI" soils, foreign soils, lab filter for	Ш	V	Ш	
dissolved, lab extract for volatiles, Ref Lab, limited volume),		\checkmark		
were bottles/paperwork flagged (e.g., sticker)?	<u> </u>	V		
For RUSH/SHORT Hold Time, were COC/Bottles flagged				
accordingly? Was Rush/Short HT email sent, if applicable?	Ш	√	Ш	
For SITE-SPECIFIC QC, e.g. BMS/BMSD/BDUP, were				
containers / paperwork flagged accordingly?	Ш	\checkmark	Ш	
For any question answered "No," has the PM been notified and				SRF Completed by: CRD
the problem resolved (or paperwork put in their bin)?	Ш	\checkmark	Ш	PM notified:
Was PEER REVIEW of sample numbering/labeling completed?		\checkmark		Peer Reviewed by:
Additional notes (if applicable):				
, ,				
Note to Client: Any "no" answer above indicates non-comple	'iance	with s	tanda	ard procedures and may impact data quality.



Sample Containers and Preservatives

Container Id	<u>Preservative</u>	<u>Container</u>	Container Id	<u>Preservative</u>	<u>Container</u>
		Condition			<u>Condition</u>
1161603001-A	No Preservative Required	ОК			
1161603001-B	Methanol field pres. 4 C	OK			

Container Condition Glossary

Containers for bacteriological, low level mercury and VOA vials are not opened prior to analysis and will be assigned condition code OK unless evidence indicates than an inappropriate container was submitted.

- OK The container was received at an acceptable pH for the analysis requested.
- BU The container was received with headspace greater than 6mm.
- DM- The container was received damaged.
- FR- The container was received frozen and not usable for Bacteria or BOD analyses.
- PA The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt and the container is now at the correct pH. See the Sample Receipt Form for details on the amount and lot # of the preservative added.
- PH The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt, but was insufficient to bring the container to the correct pH for the analysis requested. See the Sample Receipt Form for details on the amount and lot # of the preservative added.

4/6/2016 22 of 27

CHROMATOGRAMS

Data Path : $Z:\04\SF\DATA\041216\$

Data File: 12013.D Signal(s) : FID3B.ch

1:56 pm Acq On : 12 Apr 2016

Operator : CJSW Sample : (1161603001)

Misc


ALS Vial : 8 Sample Multiplier: 1

Integration File: autoint1.e Quant Time: Apr 13 11:59:20 2016

Quant Method: Z:\04\SF\METHOD\SFR2016-0407A.M Quant Title : DRO/RRO by Method AK 102/103 QLast Update: Fri Apr 08 09:05:55 2016 Response via: Initial Calibration

Integrator: ChemStation

Volume Inj. Signal Phase : Signal Info :



Data Path : $Z:\01\SD\DATA\020215A\$

Data File : SD020215A_007.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:01 pm

Operator : NLL Sample : NAS

Misc

: NAS Normal Alkane Standards

ALS Vial : 2 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:21:38 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M
Quant Title: DRO/RRO by Method AK 102/103
QLast Update: Mon Feb 02 09:35:16 2015

Response via: Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



Data Path : Z:\01\SD\DATA\020215A\

Data File : SD020215A_008.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:11 pm

Operator : NLL
Sample : CCVB Diesel Range Organics
Misc : Diesel standard

ALS Vial : 3 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:23:42 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M Quant Title: DRO/RRO by Method AK 102/103 QLast Update: Mon Feb 02 09:35:16 2015

Response via : Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



Data Path : $Z:\01\SD\DATA\020215A\$

Data File : SD020215A_009.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:21 pm

Operator : NLL Residual Range Organics
Sample : CCVR "Lube Oil" standard

Misc :

ALS Vial : 4 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:28:20 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M
Quant Title: DRO/RRO by Method AK 102/103
QLast Update: Mon Feb 02 09:35:16 2015

Response via: Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



Established in 1960, Golder Associates is a global, employee-owned organization that helps clients find sustainable solutions to the challenges of finite resources, energy and water supply and management, waste management, urbanization, and climate change. We provide a wide range of independent consulting, design, and construction services in our specialist areas of earth, environment, and energy. By building strong relationships and meeting the needs of clients, our people have created one of the most trusted professional services organizations in the world.

Africa + 27 11 254 4800
Asia + 852 2562 3658
Australasia + 61 3 8862 3500
Europe + 356 21 42 30 20
North America + 1 800 275 3281
South America + 56 2 2616 2000

solutions@golder.com www.golder.com

Golder Associates Inc. 2121 Abbott Road, Suite 100 Anchorage, AK 99507 USA

Tel: (907) 344-6001 Fax: (907) 344-6011



Table 1: Summary of Groundwater Measurements

Borehole Number	Borehole Depth (feet)	While Drilling ⁽¹⁾ Groundwater Depth (feet)	4/5/2016 Groundwater Depth (feet)	7/15/2016 Groundwater Depth (feet)	10/18/2016 Groundwater Depth (feet)
BH-01	26.5	Not Observed	No PVC installed	No PVC installed	No PVC installed
BH-02	16.5	4	3.4	4.0	3.9
BH-03	16.5	5	4.4	5.5	4.5
BH-04	16.5	5.3	3.9	4.3	4.2
BH-05	16.5	4.5	3.0	3.7	3.2
BH-06	16.5	5.8	No PVC installed	No PVC installed	No PVC installed
BH-07	16.5	3.7	3.6	3.7	3.9
BH-08	16.5	5	No PVC installed	No PVC installed	No PVC installed
BH-09	16.5	5	2.9	3.1	3.0
BH-10	16.5	5	3.8	3.5	3.3
BH-11	16.5	7	3.5	3.6	3.5
BH-12	16.5	5	No PVC installed	No PVC installed	No PVC installed
BH-13	16.5	5	4.8(2)	4.8	4.8
BH-14	16.5	7.5	5.9	6.0	6.2
BH-15	16.5	7.5	No PVC installed	No PVC installed	No PVC installed

Notes:

- Water level depth observations were collected while drilling.
 Measured on 4/13/2016 due to access constraints on 4/5/2016.

Chemical Data Report

Appendix M





CHEMICAL DATA REPORT IMAGE DRIVE / REFLECTION DRIVE AREA ROAD UPGRADE

Anchorage, Alaska

(MOA PM&E Project No. 14-50)

Submitted To: Mr. Bill Johnson, PE

CRW Engineering Group, LLC 3940 Arctic Blvd., Suite 300 Anchorage, AK 99503

Submitted By: Golder Associates Inc.

2121 Abbott Road, Suite 100 Anchorage, AK 99507 USA

Distribution:

3 Copies – CRW Engineering Group, LLC 2 Copies – Golder Associates Inc.

December 8, 2016

1523636.01





Table of Contents

1.0	INTRODUCTION	1
1.1	Project Description and Background	1
1.2	Purpose, Objective, and Scope	1
2.0	FIELD INVESTIGATION METHODS	3
2.1	Direct-Push Boreholes	3
2.2	Field Screening	3
2.3	Laboratory Sample Collection and Analyses	3
2.3	3.1 Soil Samples	4
2.3	3.2 Groundwater Samples	4
2.3	3.3 Quality Control Samples	4
	2.3.3.1 Field Duplicates	4
	2.3.3.2 MS/MSD	4
	2.3.3.3 Trip Blanks	4
3.0	RESULTS	5
3.1	General Subsurface Conditions	5
3.2	Field Screening Results	5
3.3	Analytical Results	5
3.3	3.1 Soil Analytical Results	5
3.3	3.2 Groundwater Analytical Results	5
3.3	3.3 Quality Assurance	6
4.0	CONCLUSIONS	7
5.0	LIMITATIONS AND USE OF REPORT	8
6.0	CLOSING	9
7 N	REFERENCES	10

i

List of Tables

Table 1 Soil Sample GRO, DRO, RRO, and BTEX Laboratory Results Summary

Table 2 Groundwater Sample GRO, DRO, RRO, and BTEX Laboratory Results Summary

Table 3 Relative Percent Difference

List of Figures

Figure 1 Vicinity Map

Figure 2 Borehole Location Map

List of Appendices

Appendix A Borehole Logs

Appendix B Site Photos taken on September 8, 2016
Appendix C Laboratory Data from May 2016 Investigation

Appendix D Laboratory Data from September 2016 Investigation





1.0 INTRODUCTION

Golder Associates Inc. (Golder) is pleased to present this chemical data report as part of an environmental assessment to support design of the planned reconstruction of the Image Drive/Reflection Drive area in Anchorage, Alaska (Figure 1).

This report was prepared per our proposal dated May 12, 2016 and the authorization as Amendment Number Three for Environmental Assessment (10133, Task 9050) to our Agreement for Professional Services (CRW Project No. 10133.00). This work is a continuation of Amendment Number Two, which included preparing a Sampling and Analysis Plan (SAP) for this work (Golder 2016a), which was reviewed and approved by CRW and the Municipality of Anchorage (MOA).

1.1 Project Description and Background

The planned reconstruction of the Image Drive/Reflection Drive area will include the reconstruction of approximately 4,500 feet of road, curb and gutter, and subdrains, and replacement of the existing failing storm drains. In support of this project, Golder completed the geotechnical investigation field work in March 2016 that included collecting soil samples at the geotechnical borehole locations shown in Figure 1. The soil samples were field screened for the presence of volatile organic compounds by measuring the concentration of volatile organic compounds in the headspace of the sample containers using a photoionization detector (PID) (Golder 2016b).

A soil sample collected from Borehole BH-08 at the depth interval of 10 to 11.5 feet below ground surface (bgs) had a PID reading above 20 ppm and a slight petroleum hydrocarbon odor. Borehole BH-08 is located on the south edge of Image Drive about 15 to 20 feet west of a small creek (Figure 2). Because of the field screening results, the soil sample (BH-08 #5) was submitted to the SGS North America, Inc. Environmental Services (SGS) laboratory in Anchorage, Alaska and analyzed for Gasoline Range Organics (GRO), Diesel Range Organics (DRO), Residual Range Organics and Benzene, Toluene, Ethylbenzene, and total Xylenes (BTEX).

The results of the analyses are summarized in Table 1, and the complete laboratory report is attached in Appendix C. The DRO and RRO detections in the sample are likely due to weathered diesel fuel, as can be seen by inspection of the sample chromatogram attached at the end of Appendix C. Reference chromatograms for diesel fuel (heating oil) and lubrication oil are also attached at the end of Appendix C for comparison.

1.2 Purpose, Objective, and Scope

Although the DRO and RRO concentrations in the sample from Borehole BH-8 were below potential Alaska Department of Environmental Conservation (ADEC) cleanup levels, there was the potential that the planned





excavations during construction could encounter soil above cleanup levels. Therefore, the investigation described in this report was conducted in the vicinity of Borehole BH-8 for the purpose of further investigating the potential presence of hydrocarbons in the subsurface.

The objective of the work described in this report was to determine the presence, if any, of constituents identified during the geotechnical investigation in Borehole BH-08, and potentially identifying the source or migration pathway of petroleum hydrocarbons in the vicinity of Borehole BH-08.

The scope of work for this project is detailed in in a Sampling and Analysis Plan (SAP) prepared by Golder that outlined reasoning for sample collection location and depth selection, sample handling procedures, and data quality assurance and quality control requirements for the chemical testing (Golder 2016a).





2.0 FIELD INVESTIGATION METHODS

The field investigation, soil and groundwater sampling, and analytical laboratory testing was performed as outlined in the SAP (Golder 2016a), and is summarized in the following sections. Photographs taken during the investigation are presented in Appendix B. There were no significant changes or deviations from the SAP for this project.

2.1 Direct-Push Boreholes

The subsurface exploration activity was performed on September 8, 2016, when 5 boreholes (DP-1 through DP-5) were advanced at locations shown in Figure 2 by direct push methods to a target depth of 15 feet bgs. Prior to commencing drilling activities, conflicts with underground utilities were cleared through the statewide utility clearance process. Drilling services were provided by GeoTek Alaska, Inc. of Anchorage, Alaska using a Geoprobe 6610DT drill rig equipped with Macro-Core MC5 soil sampling tooling. Mr. Christopher Valentine, a Golder professional engineer who is a "qualified environmental professional" as defined in Alaska regulations 18 AAC 75 and 18 AAC 78, maintained a log of samples and subsurface conditions and collected soil samples from the Macro-Core 1.25-inch diameter disposable liner. Soils were visually classified in the field according to the Unified Soils Classification System (ASTM D 2488), which is summarized in Figure A-1 of Appendix A. Work was performed according the SAP using the methods summarized in the following sections.

2.2 Field Screening

Soil samples were collected at varying intervals of each borehole and were field screened. The soil samples were inspected for evidence of petroleum hydrocarbons (i.e., sheen, odor, and staining) and a portion of the soil was collected from the geoprobe sampler liner and was placed in a sealed plastic bag to test the headspace for volatile organic vapors using a PID in accordance with the methods detailed in the SAP and the ADEC Field Sampling Guidance, dated May 2016.

The PID was equipped with a 10.6-electronvolt (eV) lamp, and was calibrated prior to use with 100 parts per million (ppm) isobutylene calibration gas. The sample portion collected for headspace testing with the PID was placed in a sealed plastic bags and the samples were allowed to equilibrate to a temperature above 40 degrees Fahrenheit (°F) for at least 15 minutes. The samples were then agitated prior to measuring the concentration of volatile organics in the headspace using the PID. The PID readings of headspace for the soil samples are presented in the borehole logs in Appendix A.

2.3 Laboratory Sample Collection and Analyses

Soil and groundwater samples were selected and collected according the scope detailed in the SAP, and were submitted to SGS, a State of Alaska certified laboratory, to be analyzed for GRO, DRO, RRO, and BTEX using AK101, AK102, AK103, and SW 8021B testing methods respectively.





2.3.1 Soil Samples

Two soil samples were selected from each borehole for analytical testing, as detailed in the SAP. The soil samples were selected from zones with the highest potential for contamination, one sample was collected from the zone above the groundwater table, and because field screening did not observe any high PID reading and/or interval with other evidence of contamination, the second sample was collected at the depth of the existing sanitary sewer or storm line nearest to the borehole. As-built drawings for the sanitary sewer line and storm water line were used to estimate the depth.

2.3.2 Groundwater Samples

Groundwater samples were collected using a temporary well screen point (i.e. Geoprobe SP16 Groundwater Sampler), a variable-speed peristaltic pump, and disposable tubing at each sampling location. Visible signs of contamination (i.e., oil sheen, free product, incidental odors) were not observed in the groundwater. After purging and developing the well point, the water was pumped directly into sampling jars provided by the laboratory using a low flow-rate to avoid agitation of the water.

2.3.3 Quality Control Samples

2.3.3.1 Field Duplicates

A total of 5 soil and groundwater samples were collected for this project, and to meet the field duplicate target rate of 10 percent (one field duplicate per 10 samples), one soil and one groundwater field duplicate sample was collected to measure the precision of the sampling and analytical processes. The field duplicate samples were collected simultaneously from the same sample interval using identical methods. Each duplicate was submitted as a blind sample to the laboratory, meaning it was labeled with a sample number different from that of the sample being duplicated. The sample number for the duplicate was recorded in the field borehole log, and DP-2C was a field duplicate of DP-2A.

2.3.3.2 MS/MSD

Matrix spike (MS) and matrix spike duplicate (MSD) samples were used for evaluating potential matrix effects in soil samples. Additional sample volume was collected for the sample designated for MS/MSD analysis, DP-5B, with a note on the chain of custody form indicating that it is a MS/MSD sample. MS/MSD analyses were performed at a minimum frequency of five percent, per analyte, and per extraction batch.

2.3.3.3 Trip Blanks

Trip blanks for soil and water accompanied the collected samples back to the laboratory, and were analyzed for volatile compounds. The trip blanks were prepared by and supplied by the laboratory, and were analyzed to evaluate potential cross-contamination during the sample shipping and analysis process.





3.0 RESULTS

3.1 General Subsurface Conditions

Subsurface conditions observed during the environmental field investigation on September 8, 2016 were primarily silty sands and gravels, and were generally consistent with conditions observed during the geotechnical field investigation performed in May 2016, with is detailed in the Geotechnical Investigation Report (Golder 2016a).

Groundwater was observed in the boreholes advanced at the site. The average depth to groundwater at time of drilling was approximately 5 feet bgs and ranged from 4 to 10 feet bgs.

3.2 Field Screening Results

No soil staining, petroleum odors, or sheen was observed during the field investigation on September 8, 2016. The PID readings of soil sample headspace were all non-detect (0.0 ppm), and are presented in the borehole logs in Appendix A.

3.3 Analytical Results

As summarized in Tables 1 and 2, the analytical results for the collected soil and groundwater samples were below ADEC Method 2 cleanup levels. The laboratory report with chromatographs are provided in Appendix D with the ADEC Laboratory Data Review Checklist, and results are summarized in Table 1.

3.3.1 Soil Analytical Results

The DRO and RRO detections in the soil sample DP-2A and field duplicate DP-2C (from Borehole DP-2) were below potential cleanup levels, and are likely due to unknown heavy organic compounds bleeding into the DRO and RRO range, as can be seen by inspection of the sample chromatograms that are attached at the end of Appendix D. Reference chromatograms for diesel fuel (heating oil) and lubrication oil are also attached at the end of Appendix C for comparison. No odor, sheen, or indication of petroleum contamination was observed during field screening of that sample, but results like those obtained may be due to lubrication oil contamination or naturally occurring organics (i.e. peat) intermixed with the soil. The detection chromatograms from Borehole DP-2 are different from the chromatogram of the sample collected from Borehole BH-08 (Appendix C), which is closer to a weathered diesel fuel signature, and suggests the detections are likely from unrelated sources.

3.3.2 Groundwater Analytical Results

All groundwater analytical results at the site were below the laboratory limit of quantitation (LOQ), and were also below groundwater cleanup levels. Groundwater analytical results are summarized in Table 2, and the analytical laboratory report is provided in Appendix D.





3.3.3 Quality Assurance

The relative percent difference (RPD) for the sample concentration and corresponding duplicate concentration is used as a measure of precision. The RPDs for soil and water sample analyses is recommended to be below 50 percent and 30 percent, respectively. RPD is defined as:

RPD (%) = Absolute value of:
$$\frac{(R_1-R_2)}{((R_1+R_2)/2)} \times 100$$

Where: $R_1 = Sample Concentration$

 R_2 = Field Duplicate Concentration

RPD results for Soil Samples DP-2A and DP-2C were greater than 50 percent (as shown in Table 3) and did not meet the recommended goals. This is likely because to the soil sample contained gravel, so there was insufficient mixing/homogenization of the sample before jarring; however, this should not affect data quality. RPD results for Groundwater Samples DP-1 and DP-6 were less than the recommended goal of 30 percent (Table 3).

7



4.0 CONCLUSIONS

The field screening observations did not indicate evidence of soil staining, petroleum odors, or groundwater sheen, and all PID readings of volatile organic vapors in sample headspace were non-detect.

All analytical laboratory results of GRO, DRO, RRO, and BTEX for the collected soil and groundwater samples, which includes the previously collected sample from the geotechnical Borehole BH-08, were either not detected above the LOQ, or were below potential cleanup levels as summarized in Tables 1 and 2.

As detailed in Section 3.3.1, the chromatograms from the DRO and RRO detections in Borehole DP-2 were different from the chromatogram of the sample collected from Borehole BH-08 (Appendix C), which suggests the detections are likely from unrelated sources.

In addition, the possible weathered diesel fuel contamination observed in Borehole BH-08 likely does not extend far past the BH-08 location, as Borehole DP-1 was located less than 10 feet away from BH-08.



5.0 LIMITATIONS AND USE OF REPORT

This report has been prepared exclusively for the use of CRW and MOA in their design of the proposed road improvements along Image Drive and Reflection Drive in Anchorage, Alaska. This report is not meant to represent a legal opinion regarding compliance with applicable laws. With respect to regulatory compliance issues, please note that regulatory statutes and the interpretation of regulatory statutes are subject to change over time and should be discussed with legal counsel.

8

The work program followed the standard of care expected of professionals undertaking similar work in the State of Alaska under similar conditions. No warranty is included, either express or implied, that the actual conditions will conform exactly to the assessments contained in this report. Where data supplied by the client or other external sources (including without limitation, other consultants, laboratories, public databases) have been used, it has been assumed that the information is correct unless otherwise stated. No responsibility is accepted by Golder for incomplete or inaccurate data supplied by others.

Any use which a third party makes of this report, any reliance on or decisions to be made based on it, are the responsibility of such third parties. Golder accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. The report is of a summary nature and is not intended to stand alone, and in order to properly understand the results, conclusions, and opinions expressed in this report, reference must be to the foregoing and to the entirety of the report. Golder cannot be responsible for use of portions of the report without reference to the entire report.



6.0 CLOSING

We appreciate the opportunity to provide this report. Please contact us at 907-344-6001 if you have questions or comments.

GOLDER ASSOCIATES INC.

Chin Viv

Christopher A. Valentine, PE

Qualified Environmental Professional

Mark R. Musial, PE

Principal and Geotechnical-Permafrost

Practice/Program Leader

CAV/MRM/mlp

7.0 REFERENCES

Golder Associates Inc. (Golder) 2016a, "Geotechnical Investigation – Image Drive / Reflection Drive Area Road Upgrade, Image Drive and Reflection Drive, Anchorage, Alaska, (MOA PM&E Project No. 14-50)," August 15, 2016, Golder Project Number 1523636

10

Golder Associates Inc. (Golder) 2016b, "Sampling and Analysis Plan for Environmental Assessment Services, Image Drive / Reflection Drive Area Road Reconstruction, Anchorage, Alaska" June 16, 2016, Golder Project Number 1523636.01






Table 1: Soil Sample GRO, DRO, RRO, and BTEX Laboratory Results Summary

December 2016

		2)	(2)	(+	(2)		2)	(2)	3)	(2)	(2)	2)	2)		<u>(c</u>
	P & M -Xylene (ug/Kg)	ND(33.5)	ND(24.05)	ND(22.4)	ND(28.65)	ND(28)	ND(19.5)	ND(21.35)	ND(15.8)	ND(15.35)	ND(26.35)	ND(21.15)	ND(21.6)	00008	ND(24.9)
	o-Xylene (ng/Kg)	26.8 J	ND(12)	ND(11.2)	ND(14.3)	ND(14)	ND(9.75)	ND(10.7)	ND(7.9)	ND(7.7)	ND(13.2)	ND(10.55)	ND(10.8)	63	ND(12.45)
	Ethylbenzene (ug/Kg)	ND(16.8)	ND(12)	ND(11.2)	ND(14.3)	ND(14)	ND(9.75)	ND(10.7)	ND(7.9)	ND(7.7)	ND(13.2)	ND(10.55)	ND(10.8)	0069	ND(12.45)
Parameter and Units	ənəuloT (gX\gu)	ND(16.8)	ND(12)	ND(11.2)	ND(14.3)	ND(14)	ND(9.75)	ND(10.7)	ND(7.9)	ND(7.7)	ND(13.2)	ND(10.55)	ND(10.8)	6500	ND(12.45)
Parameter	Benzene (ug/Kg)	ND(8.40)	(9)QN	ND(5.6)	ND(7.15)	(Z) (ND(Z)	ND(4.875)	ND(5.35)	ND(3.955)	ND(3.84)	ND(6.6)	ND(5.3)	ND(5.4)	25	ND(6.25)
	Residual Range Organics (RRO) (mg/kg)	38.6	25.9	9.86 J	511	1810	12.1 J	85.3	6.89 J	37.7	17.3 J	42.1	42.6	11000	:
	Diesel Range Organics (DRO) (mg/kg)	37.5	ND(11.1)	ND(11.8)	56.0 J	130	7.45 J	15.2 J	ND(10.75)	16.1 J	10.7 J	13.2 J	9.55 J	250	:
	Gasoline Range Organics (GRO) (mg/kg)	1.44 J	ND(1.2)	0.741 J	ND(1.43)	ND(1.4)	ND(0.975)	0.678 J	0.598 J	0.538 J	0.904 J	0.680 J	ND(1.08)	300	0.787 J
	Analytical Lab Sample ID	1161603001	1165330001	1165330002	1165330003	1165330004	1165330005	1165330007	1165330006	1165330008	1165330009	1165330010	1165330011		1165330012
	Date Collected	4/6/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	9/8/2016	Level (1)	9/8/2016
	Sample Depth Interval (feet bgs)	10 - 12	4 - 4.5	7 - 7.5	3 - 3.5	3 - 3.5	6.5 - 7	9 - 9.5	11 - 11.5	3.5 - 4	10.5 - 11	4 - 4.5	9 - 9.5	Potential Soil Cleanup Level (1)	
	Sample Number	BH-8 #2	DP-1A	DP-1B	DP-2A	DP-2C (DP-2A Field Duplicate)	DP-2B	DP-3B	DP-3C	DP-4A	DP-4B	DP-5A	DP-5B	Potential	Trip Blank
	Borehole Number	BH-8	DP-1	DP-1	DP-2	DP-2	DP-2	DP-3	DP-3	DP-4	DP-4	DP-5	DP-5		

Bold concentration indicate significant detections, no concentrations exceed potential cleanup level

Analytical Laboratory Methods: GRO by AK101

DRO by AK102 RRO by AK103 BTEX by 8021B

mg/kg = concentration in milligrams per kilogram

ug/kg = concentration in micrograms per kilogram ND(10) - Not detected at concentrations above the Method Detection Limit (MDL) shown in parenthesis

J - Estimated value, detected at concentration greater than the MDL but below the limit of quantitation (LOQ)

(1) Table B1. Method Two, Under 40-inch Zone, Migration to Groundwater Cleanup Level "18AAC75, Oil and Other Hazardous Substances Pollution Control," Revised May 8, 2016.



December 2016

Table 2: Groundwater Sample GRO, DRO, RRO, and BTEX Laboratory Results Summary

						Parameter and Units	nd Units			
Sample Number	Date Collected	Analytical Lab Sample ID	Gasoline Range Organics (GRO) (mg/L)	Diesel Range Organics (DRO) (mg/L)	Residual Range Organics (RRO) (mg/L)	geuzeue Beuzeue	Toluene (ug/L)	Ethylbenzene Ethylbenzene	(η/βn) əuəμΧχ-o	ənəlyX- M & 역 (Ll/gu)
DP-1	9/8/2016	1165330013	ND(0.05)	0.229 J	ND(0.25)	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)
DP-6 (DP-1 Field Duplicate)	9/8/2016	1165330014	ND(0.05)	0.212 J	ND(0.2405)	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)
DP-2	9/8/2016	1165330015	ND(0.05)	0.187 J	ND(0.252)	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)
DP-3	9/8/2016	1165330016	ND(0.05)	0.240 J	ND(0.265)	ND(0.25)	0.510 J	ND(0.5)	ND(0.5)	ND(1)
DP-4	9/8/2016	1165330017	ND(0.05)	0.322 J	0.250 J	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)
DP-5	9/8/2016	1165330018	ND(0.05)	ND(0.3)	ND(0.25)	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)
Potential Groundwater Cleanup Level (1)	r Cleanup Lev	(1)	2.2	1.5	1.1	5	1000	002	100	10000
Trip Blank	9/8/2016	1165330012	ND(0.05)	:	:	ND(0.25)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)

Notes:

Analytical Laboratory Methods:

GRO by AK101 DRO by AK102 RRO by AK103 BTEX by 8021B

mg/L = concentration in milligrams per liter

ug/L = concentration in micrograms per liter

ND(10) - Not detected at concentrations above the Method Detection Limit (MDL) shown in parenthesis J - Estimated value, detected at concentration greater than the MDL but below the limit of quantitation (LOQ)

(1) Table C. Groundwater Cleanup Levels "18AAC75, Oil and Other Hazardous Substances Pollution Control," Revised May 8, 2016.



Table 3: Relative Percent Difference

December 2016

		Soil Sample		Grou	Groundwater Sample	
	Sample DP-2A [1165330003] Results (mg/kg)	Sample DP-2C (DP- 2A Field Duplicate) [1165330004] Results (mg/kg)	Relative Percent Difference	Sample DP-1 [1165330013] Results (ug/l)	Sample DP-6 (DP-1 Field Duplicate) [1165330014] Results (ug/l)	Relative Percent Difference
Petroleum Hydrocarbons						
Gasoline Range Organics (GRO)	ND(1.43)	ND(1.4)	1	ND(0.05)	ND(0.05)	:
Diesel Range Organics (DRO)	56.0 J	130	%08	0.229 J	0.212 J	8%
Residual Range Organics (RRO)	511	1810	112%	ND(0.25)	ND(0.2405)	ł
втех						
Benzene	ND(7.15)	ND(7)	ı	ND(0.25)	ND(0.25)	ŀ
Toluene	ND(14.3)	ND(14)	1	ND(0.5)	ND(0.5)	:
Ethylbenzene	ND(14.3)	ND(14)	:	ND(0.5)	ND(0.5)	:
o-Xylene	ND(14.3)	ND(14)	1	ND(0.5)	ND(0.5)	:
P & M -Xylene	ND(28.65)	ND(28)	ŀ	ND(1)	ND(1)	1

Notes:

mg/L = concentration in milligrams per liter


ug/L = concentration in micrograms per liter


ND(10) - Not detected at concentrations above the Method Detection Limit (MDL) shown in parenthesis

J - Estimated value, detected at concentration greater than the MDL but below the limit of quantitation (LOQ)

Relative percent difference is the difference between two values divided by the mean of the two values.







CLIENT CRW ENGINEERING GROUP, LLC

CONSULTANT

YYYY-MM-DD	2016-12-08
DESIGNED	-
PREPARED	APG
REVIEWED	CAV
APPROVED	MRM

ENVIRONMENTAL ASSESSMENT, IMAGE REFLECTION DRIVE

ANCHORAGE, ALASKA

VICINITY MAP

PROJECT NO.	CONTROL	REV.	FIGURE
1523636.01		Α	1

CRW ENGINEERING GROUP, LLC

2016-12-08 CAV MRM APG YYYY-MM-DD DESIGNED PREPARED REVIEWED APPROVED

PROJECT ENVIRONMENTAL ASSESSMENT, IMAGE REFLECTION DRIVE ANCHORAGE, ALASKA

TITLE OREHOLE LOCATION MAP

A A

PROJECT NO. 1523636.01

CONSULTANT

2016 GEOTECHNICAL BOREHOLE LOCATION AND NAME

REFERENCE(S)

10IMAGERY AC⊏UIRED IN JULY 2015 BY THE ANCHORAGE LIDA
IMAGERY PROJECT AND WAS DISTRIBUTED BY ALASKA DIVISIC
EOLOGICAL AND GEOPHYSICAL SURVEYS (DGGS) ONLINE MAP
NG LOCATIONS PROVIDED BY CRW ENGINEERING GROUP, LLC
CTOBER 3 2016.

IMAGERY AC□UIRED IN JULY 2015 BY THE ANCHORAGE LIDAR
AGERY PROJECT AND WAS DISTRIBUTED BY ALASKA DIVISION
DLOGICAL AND GEOPHYSICAL SURVEYS (DGGS) ONLINE MAP.
S LOCATIONS PROVIDED BY CRW ENGINEERING GROUP, LLC
TOBER 3 2016.

APPENDIX A BOREHOLE LOGS COHESIONLESS SOILS (a)

RELATIVE DENSITY

(MEDIUM DENSE)

VERY LOOSE

VERY DENSE

LOOSE

DENSE

COMPACT

 $C_{\text{U}} = \frac{D_{60}}{D_{10}} \qquad C_{\text{C}} = \frac{\left(D_{30}\right)^2}{D_{10} \times D_{60}}$ Gravels or sands with 50 12% fines require dual symbols (GW-GM, GW-GC, GP-GM, GF-GC, SW-SM, SW-SC, SP-SM, SP-SC) and add "with clay" or "with silt" to group name. If fines classify as CL-ML for GM or SM, use dual symbol GC-GM or SC-SM. The coefficient of uniformity, C $_{\text{U}}$, and coefficient of curvature, C $_{\text{C}}$ equations are given above where D $_{\text{CM}}$ is soil particle diameter where X% is % finer. Optional Abbeviations: Lower case "s" after USCS group symbol denotes either "sandy" or "with sand" while "g" denotes either "gravelly" or "with gravel"

CRITERIA FOR DESCRIBING MOISTURE CONDITION (adapted from ASTM D2488)

DRY	ABSENCE OF MOISTURE, DUSTY, DRY TO THE TOUCH
MOIST	DAMP BUT NO VISIBLE WATER
WET	VISIBLE FREE WATER, USUALLY SOIL IS BELOW
	WATER TABLE

COMPONENT DEFINITIONS BY GRADATION

COMPONENT	SIZE RANGE
BOULDERS	GREATER THAN 12 in.
COBBLES	12 in. to 3 in.
GRAVEL	3 in. to #4 Sieve (4.76 mm)
COARSE GRAVEL	3 in. to 3/4 in.
FINE GRAVEL	3/4 in. to #4 (4.76 mm)
SAND	#4 (4.76 mm) to #200 (0.074 mm)
COARSE SAND	#4 (4.76 mm) to #10 (2.0 mm)
MEDIUM SAND	#10 (2.0 mm) to #40 (0.42 mm)
FINE SAND	#40 (0.42 mm) to #200 (0.074 mm)
SILT & CLAY (FINES)	SMALLER THAN #200 (0.074 mm)

(a) Soils consisting of gravel, sand, and silt, either separately or in combination possessing no characteristics of plasticity, and exhibiting drained behavior.

 $(N_1)_{60}$ $(blows/ft)^{(c)}$

4 - 10

10 - 30

30 - 50

OVER 50

- (b) Soils possessing the characteristics of plasticity, and exhibiting undrained behavior.
- (c) Refer to ASTM D1586 for a definition of N value. (N₁)_∞ is the N value corrected for hammer energy and overburden pressure, and is detailed in ASTM D6066. N values may be affected by a number of factors including: material size, sampler size, hammer weight and type, depth, drilling method, and borehole disturbance. N values are only an approximate guide for cohesive soil and do not apply to frozen soil.

RELATIVE DENSITY / CONSISTENCY ESTIMATE
USING STANDARD PENETRATION TEST (SPT) VALUES
(adapted from Terzaghi and Peck 1967 and NAVFAC DM 7.1)

CONSISTENCY

VERY SOFT

VERY STIFF

SOFT

FIRM

STIFF

HARD

COHESIVE SOILS(b)

 $(N_1)_{60}$

(blows/ft)(c)

2 - 4

4 - 8

8 - 15

15 - 30

OVER 30

UNCONFINED

COMPRESSIVE

STRENGTH (TSF)(d)

0 - 0.25

0.25 - 0.50

0.50 - 1.0

1.0 - 2.0

2.0 - 4.0

OVER 4.0

(d) Undrained shear strength, s_u= 1/2 unconfined compression strength, U_c. Note that Torvane (TV) measures s_u and pocket penetrometer (PP) measures U_c.

SAMPLER ABBREVIATIONS

AR Air Rotary cuttings AS Auger Sample, cuttings	GB Grab sample (disturbed from surface/test pit)	SC Soil core (continuous sampler)
CS Chunk/block sample	MC Modified California	SS SPT sampler (2-in. OD,
(undisturbed from	sampler (3-in. OD split	140-lb hammer)
surface/test pit)	spoon, 340-lb hammer)	TO Thin-walled, open
DO Drive Open (split spoon	MS Modified Shelby tube	(Shelby tube)
other than SS or MC)	R Refusal when driving	TP Thin-walled, piston
DP Direct Push (Geoprobe)	RC Rock core	WS Wash Sample

DESCRIPTIVE TERMINOLOGY FOR PERCENTAGES (ASTM D2488)

	•
DESCRIPTIVE TERMS	RANGE OF PROPORTION
I ERIVIS	PROPORTION
TRACE	0 - 5%
FEW	5 - 10%
LITTLE	10 - 25%
SOME	30 - 45%
MOSTLY	50 - 100%

LABORATORY TEST AND NOTES ABBREVIATIONS / SYMBOLS

Con	Consolidation PII	ID	Photoionization Detector T	XCD	Triaxial, Consolidated Drained
Dd	Dry Density Pf	M	Modified Proctor (D1557) T	XCU	Triaxial, Consolidated Undrained
K	Thermal Conductivity P	P	Pocket Penetrometer (Field)	XUU	Triaxial, Unconsolidated Undrained
MA	Sieve and Hydrometer PTLI	D	Point Load	W_L	Liquid Limit (LL)
NP	Non-plastic Sa	A	Sieve Analysis	W_{P}	Plastic Limit (PL)
OLI	Organic Loss Spo	G	Specific Gravity	Ω	Soil Resistivity (Res.)
P200	Passing #200 Sieve (D1140) To	C	Thaw Consolidation/Strain	▼.	Water Level
pН	Soil pH T	V	Torvane (Field)	∇	Water Level at time of drilling
PI	Plasticity Index (D4318)				•



LEGENDI

SOIL

V2.0-ANC REVISED3.GLB [ANC

ЕВ

	PRO	JEC ₁	I.ON T	Image Drive / Reflection Drive Road Upgr 1523636.01 Anchorage, AK	REC ades	COR	DRILI	LING END:	September September N: 329,438	8. 201	16 00:00 T	SHEET: 1 of 1 GS ELEV.: OC ELEV.: na DATUM:	
				SOIL PROFILE					SAMPLES		PID CONCENTRATION		_ o
	O DEPTH (ft)	BORING METHOD	0.0	DESCRIPTION	ICE BOND	nscs	GRAPHIC LOG	SAMPLE TYPE & NUMBER	BLOWS per 6 in Hammer, 30 inch drop	REC ATT	© (SONCEINTRATION	NOTES WATER LEVELS	ADDITIONAL LAB TESTING
			3.5	POORLY GRADED GRAVEL, gray; moist to wet				-1A		40 60		- _▼ 5.0 ft, 09/08/2016 09:30	GRO, DRO, RRO, BTEX
IMAGE REFLECTION ENVRIO.GPJ	10	Geoprobe MC5 System	10.0	POORLY GRADED SAND; wet, fine sand	. — —			DP -18		3 <u>5</u> 60			GRO, DRO, RRO, BTEX
	 	-	12.5 <u> </u>	SILTY GRAVEL; compact, dry to moist				dO		60 60			
01 - GOLDER - BOREHOLE RECORD - DF STD US LAB E-M.GDT - 11/7/16 16:08 J/2015 JOBS/1523636.01 CRW ENVIRO ASSESSMENT IMAGE DRIVE/FIELD - GINT/152363601	20			Bottom of borehole at 15.0 ft. Backfilled with bentonite chips.									
01 - GOLDEF J:\2015 JOBS		DF	NG CC RILLEF LL RIC	· ·			СН	ECKED:	C. Valentine J. Karp M. Musial	e		Gold- Associ	er ates

PR	OJE	СТ	IECT: Image Drive / Reflection Drive Road L NO.: 1523636.01 FION: Anchorage, AK	RE(Jpgrades	D	RILLIN DRIL	NG START: LING END:	REHOLE September September N: 329,454	8, 201 8, 201	16 00:00 16 00:00 57,897	SHEET: 1 of 1 GS ELEV.: TOC ELEV.: na DATUM:	
O DEPTH			SOIL PROFILE DESCRIPTION 0.0	ICE BOND	nscs	GRAPHIC LOG		BLOWS per 6 in Hammer, 30 inch drop	REC ATT (in)	PID CONCENTRATION	NOTES WATER LEVELS	ADDITIONAL LAB TESTING
	_		0.3 (PT), PEAT, brown; moist (SM), SiLTY SAND WITH GRAVEL, grato wet	ay; moist	PT_		DP -2A&-2C		24 60 2			GRO, DRO, RRO, BTEX
ENVRIO.GPJ	Caparaha MC5 System		10.0 POORLY CRAPED SAND GROVE	wat fine			DP -28					GRO, DRO, RRO, BTEX
WEVELELD - GINTY152383601 IMAGE REFLECTION ENVRIO.GPJ			(SP), POORLY GRADED SAND, gray, sand 12.5 (GM), SILTY GRAVEL, light gray, wet	wet, fine	SP		DP		38 60			
J.2015 JOBS/1523636.01 CRW ENVIRO ASSESSMENT IMAGE DRIVEYIELD - GINT152363601			Bottom of borehole at 15.0 ft. Backfilled with bentonite chips.									
J:\2015 JOBS\15		DR	G CO.: Geotek Alaska, Inc. IILLER: Chris Bizaillon LL RIG: Geoprobe 6610DT			CH	HECKED:	C. Valentine J. Karp M. Musial	e 		Gold	er ates

RECORD OF BOREHOLE DP-3 SHEET: 1 of 1 DRILLING START: DRILLING END: September 8, 2016 00:00 September 8, 2016 00:00 Image Drive / Reflection Drive Road Upgrades GS ELEV. PROJECT NO.: 1523636.01 TOC ELEV.: LOCATION: N: 329,446 E: 367,811 Anchorage, AK COORDINATES: DATUM: PID SOIL PROFILE SAMPLES ADDITIONAL LAB TESTING CONCENTRATION DEPTH (ft) BORING METHOD SAMPLE TYPE & NUMBER **BLOWS №** (ppm) CE BOND GRAPHIC LOG **NOTES** uscs Depth per 6 in <u>REC</u> WATER LEVELS DESCRIPTION ATT Hammer, 30 inch X LEL (%) drop (in) 80 60 ASPHALT 0.3 (GW), WELL-GRADED GRAVEL; moist GW <u>41</u> 60 Ы (GM), SILTY GRAVEL WITH SAND; moist to 38 GRO, DRO, RRO, 5 BTEX Geoprobe MC5 System GM <u>12</u> 60 01 - GOLDER - BOREHOLE RECORD - DF STD US LAB E-M.GDT - 1*117*16 16:08 J.2015 JOBS\1523636.01 CRW ENVIRO ASSESSMENT IMAGE DRIVE\FIELD - GINT\152363601 IMAGE REFLECTION ENVRIO.GPJ 10 (ML), SILT WITH GRAVEL; dry to moist 30 GRO, DRO, RRO, BTEX <u>34</u> 60 РР ML15 Bottom of borehole at 15.0 ft. Backfilled with bentonite chips. 20 DRILLING CO.: Geotek Alaska, Inc. LOGGED: C. Valentine Golder Associates DRILLER: Chris Bizaillon CHECKED: J. Karp

REVIEWED: M. Musial

DRILL RIG:

Geoprobe 6610DT

RECORD OF BOREHOLE DP-4 SHEET: 1 of 1 DRILLING START: DRILLING END: Image Drive / Reflection Drive Road Upgrades 1523636.01 September 8, 2016 00:00 September 8, 2016 00:00 GS ELEV. PROJECT NO.: TOC ELEV.: LOCATION: N: 329,474 E: 367,871 Anchorage, AK COORDINATES: DATUM: PID SOIL PROFILE SAMPLES ADDITIONAL LAB TESTING CONCENTRATION DEPTH (ft) BORING METHOD SAMPLE TYPE & NUMBER **BLOWS №** (ppm) CE BOND GRAPHIC LOG **NOTES** uscs Depth per 6 in <u>REC</u> WATER LEVELS **DESCRIPTION** ATT Hammer, 30 inch X LEL (%) drop (in) 60 ASPHALT 0.3 (GP), POORLY GRADED GRAVEL; moist GP <u>41</u> 60 РР (GM), SILTY GRAVEL, dark gray; wet GRO, DRO, RRO, BTEX 5 ∑ 5.0 ft, 09/08/2016 12:30 Geoprobe MC5 System GM <u>24</u> 60 01 - GOLDER - BOREHOLE RECORD - DF STD US LAB E-M.GDT - 1*117*16 16:08 J.2015 JOBS\1523636.01 CRW ENVIRO ASSESSMENT IMAGE DRIVE\FIELD - GINT\152363601 IMAGE REFLECTION ENVRIO.GPJ 10 (SP), POORLY GRADED SAND, gray, wet 4_B SP GRO, DRO, RRO, BTEX <u>36</u> 60 РР (GM), SILTY GRAVEL, gray; moist GM 15 Bottom of borehole at 15.0 ft. Backfilled with bentonite chips. DRILLING CO.: Geotek Alaska, Inc. LOGGED: C. Valentine Golder Associates DRILLER: Chris Bizaillon CHECKED: J. Karp DRILL RIG: Geoprobe 6610DT REVIEWED: M. Musial

RECORD OF BOREHOLE DP-5 SHEET: 1 of 1 DRILLING START: DRILLING END: Image Drive / Reflection Drive Road Upgrades 1523636.01 September 8, 2016 00:00 September 8, 2016 00:00 GS ELEV. PROJECT NO.: TOC ELEV.: LOCATION: N: 329,493 E: 367,948 Anchorage, AK COORDINATES: DATUM: PID SOIL PROFILE SAMPLES ADDITIONAL LAB TESTING CONCENTRATION DEPTH (ft) BORING METHOD SAMPLE TYPE & NUMBER **BLOWS №** (ppm) CE BOND GRAPHIC LOG **NOTES** uscs per 6 in Depth <u>REC</u> WATER LEVELS **DESCRIPTION** ATT Hammer, 30 inch X LEL (%) drop (in) 60 ASPHALT 0.3 (GW), WELL-GRADED GRAVEL; moist GW <u>42</u> 60 Ы (GM), SILTY GRAVEL, dark gray; wet -5A GRO, DRO, RRO, 5 ∑ 5.0 ft, 09/08/2016 13:30 BTEX Geoprobe MC5 System GM <u>28</u> 60 GRO, DRO, RRO, BTEX 01 - GOLDER - BOREHOLE RECORD - DF STD US LAB E-M.GDT - 1*117*16 16:08 J.2015 JOBS\1523636.01 CRW ENVIRO ASSESSMENT IMAGE DRIVE\FIELD - GINT\152363601 IMAGE REFLECTION ENVRIO.GPJ -5B 10 (SP), POORLY GRADED SAND, gray, wet SP <u>36</u> 60 Ы (GM), SILTY GRAVEL, gray; moist GM 15 Bottom of borehole at 15.0 ft. Backfilled with bentonite chips. DRILLING CO.: Geotek Alaska, Inc. LOGGED: C. Valentine Golder Associates DRILLER: Chris Bizaillon CHECKED: J. Karp DRILL RIG: Geoprobe 6610DT REVIEWED: M. Musial

APPENDIX B SITE PHOTOS TAKEN ON SEPTEMBER 8, 2016

Site Photos taken on September 8, 2016



Photo 1: Typical geoprobe sampler liner.



Photo 2: Purging temporary .groundwater well poin t at DR-1



Photo 3: Backfilling DP-2 with bentonite chips



Photo 4: Drilling DP-5.

APPENDIX C
LABORATORY DATA FROM MAY 2016 INVESTIGATION



Laboratory Report of Analysis

To: Golder Associates Inc.

2121 Abbott Road, #100 Anchorage, AK 99507 (907)865-2524

Report Number: 1161603

Client Project: Image/Reflection Drive

Dear Brenton Savikko,

Enclosed are the results of the analytical services performed under the referenced project for the received samples and associated QC as applicable. The samples are certified to meet the requirements of the National Environmental Laboratory Accreditation Conference Standards. Copies of this report and supporting data will be retained in our files for a period of ten years in the event they are required for future reference. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. Any samples submitted to our laboratory will be retained for a maximum of fourteen (14) days from the date of this report unless other archiving requirements were included in the quote.

If there are any questions about the report or services performed during this project, please call Victoria at (907) 562-2343. We will be happy to answer any questions or concerns which you may have.

Thank you for using SGS North America Inc. for your analytical services. We look forward to working with you again on any additional analytical needs.

Sincerely, SGS North America Inc.

Victoria Pennick
Project Manager
Victoria.Pennick@sgs.com

Date

Print Date: 04/20/2016 1:13:54PM



Case Narrative

SGS Client: Golder Associates Inc. SGS Project: 1161603 Project Name/Site: Image/Reflection Drive Project Contact: Brenton Savikko

Refer to sample receipt form for information on sample condition.

*QC comments may be associated with the field samples found in this report. When applicable, comments will be applied to associated field samples.

Print Date: 04/20/2016 1:13:55PM



Laboratory Qualifiers

Enclosed are the analytical results associated with the above work order. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx. Attention is drawn to the limitation of liability, indenmification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the context or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS maintains a formal Quality Assurance/Quality Control (QA/QC) program. A copy of our Quality Assurance Plan (QAP), which outlines this program, is available at your request. The laboratory certification numbers are AK00971 (DW Chemistry & Microbiology) & UST-005 (CS) for ADEC and 2944.01 for DOD ELAP/ISO17025 (RCRA methods: 1020B, 1311, 3010A, 3050B, 3520C, 3550C, 5030B, 5035A, 6020A, 7470A, 7471B, 8021B, 8082A, 8260B, 8270D, 8270D-SIM, 9040C, 9045D, 9056A, 9060A, AK101 and AK102/103). Except as specifically noted, all statements and data in this report are in conformance to the provisions set forth by the SGS QAP and, when applicable, other regulatory authorities.

The following descriptors or qualifiers may be found in your report:

* The analyte has exceeded allowable regulatory or control limits.

! Surrogate out of control limits.

B Indicates the analyte is found in a blank associated with the sample.

CCV/CVA/CVB Continuing Calibration Verification
CCCV/CVC/CVCA/CVCB Closing Continuing Calibration Verification

CL Control Limit

D The analyte concentration is the result of a dilution.

DF Dilution Factor

DL Detection Limit (i.e., maximum method detection limit)
E The analyte result is above the calibrated range.
F Indicates value that is greater than or equal to the DL

GT Greater Than
IB Instrument Blank

ICV Initial Calibration Verification
J The quantitation is an estimation.

JL The analyte was positively identified, but the quantitation is a low estimation.

LCS(D) Laboratory Control Spike (Duplicate)
LOD Limit of Detection (i.e., 1/2 of the LOQ)

LOQ Limit of Quantitation (i.e., reporting or practical quantitation limit)

LT Less Than

M A matrix effect was present.

MB Method Blank

MS(D) Matrix Spike (Duplicate)

ND Indicates the analyte is not detected.
Q QC parameter out of acceptance range.

R Rejected

RPD Relative Percent Difference

U Indicates the analyte was analyzed for but not detected.

Note: Sample summaries which include a result for "Total Solids" have already been adjusted for moisture content.

All DRO/RRO analyses are integrated per SOP.

Print Date: 04/20/2016 1:13:56PM

SGS North America Inc. 200 West Potter Drive, Anchorage, AK 99518



Sample Summary

<u>Client Sample ID</u> <u>Lab Sample ID</u> <u>Collected</u> <u>Received</u> <u>Matrix</u>

BH-8 #5 1161603001 04/06/2016 04/06/2016 Soil/Solid (dry weight)

 Method
 Method Description

 AK101
 AK101/8021 Combo. (S)

 SW8021B
 AK101/8021 Combo. (S)

AK102 Diesel/Residual Range Organics
AK103 Diesel/Residual Range Organics

SM21 2540G Percent Solids SM2540G

Print Date: 04/20/2016 1:13:57PM



Detectable Results Summary

<u>Parameter</u>	Result	<u>Units</u>
Diesel Range Organics	37.5	mg/Kg
Residual Range Organics	38.6	mg/Kg
Gasoline Range Organics	1.44J	mg/Kg
o-Xylene	26.8J	ug/Kg
	Diesel Range Organics Residual Range Organics Gasoline Range Organics	Diesel Range Organics 37.5 Residual Range Organics 38.6 Gasoline Range Organics 1.44J

Print Date: 04/20/2016 1:13:58PM

SGS North America Inc. 200 West Potter Drive, Anchorage, AK 99518 t 907.562.2343 f 907.561.5301 www.us.sgs.com



Results of BH-8 #5

Client Sample ID: BH-8 #5

Client Project ID: Image/Reflection Drive

Lab Sample ID: 1161603001 Lab Project ID: 1161603 Collection Date: 04/06/16 12:00 Received Date: 04/06/16 15:35 Matrix: Soil/Solid (dry weight)

Solids (%):89.0 Location:

Results by Semivolatile Organic Fuels

Parameter Diesel Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	37.5	22.1	6.86	mg/Kg	1	Limits	04/12/16 13:56
Surrogates 5a Androstane (surr)	101	50-150		%	1		04/12/16 13:56

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK102 Analyst: CJSW

Analytical Date/Time: 04/12/16 13:56 Container ID: 1161603001-A Prep Batch: XXX35139
Prep Method: SW3550C
Prep Date/Time: 04/11/16 09:03
Prep Initial Wt./Vol.: 30.466 g
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	38.6	22.1	6.86	mg/Kg	1		04/12/16 13:56
Surrogates							
n-Triacontane-d62 (surr)	97.2	50-150		%	1		04/12/16 13:56

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK103 Analyst: CJSW

Analytical Date/Time: 04/12/16 13:56 Container ID: 1161603001-A Prep Batch: XXX35139
Prep Method: SW3550C
Prep Date/Time: 04/11/16 09:03
Prep Initial Wt./Vol.: 30.466 g
Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:13:59PM

J flagging is activated



Results of BH-8 #5

Client Sample ID: BH-8 #5

Client Project ID: Image/Reflection Drive

Lab Sample ID: 1161603001 Lab Project ID: 1161603 Collection Date: 04/06/16 12:00 Received Date: 04/06/16 15:35 Matrix: Soil/Solid (dry weight)

Solids (%):89.0 Location:

Results by Volatile Fuels

<u>Parameter</u> Gasoline Range Organics	Result Qual 1.44 J	LOQ/CL 3.35	<u>DL</u> 1.01	<u>Units</u> mg/Kg	<u>DF</u> 1	Allowable Limits	<u>Date Analyzed</u> 04/15/16 04:51
Surrogates							
4-Bromofluorobenzene (surr)	96	50-150		%	1		04/15/16 04:51

Batch Information

Analytical Batch: VFC12962 Analytical Method: AK101

Analyst: S.P

Analytical Date/Time: 04/15/16 04:51 Container ID: 1161603001-B

Prep Batch: VXX28685 Prep Method: SW5035A Prep Date/Time: 04/06/16 12:00 Prep Initial Wt./Vol.: 51.295 g Prep Extract Vol: 30.6335 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	8.40 U	16.8	5.37	ug/Kg	1		04/15/16 04:51
Ethylbenzene	16.8 ∪	33.5	10.5	ug/Kg	1		04/15/16 04:51
o-Xylene	26.8 J	33.5	10.5	ug/Kg	1		04/15/16 04:51
P & M -Xylene	33.5 ∪	67.1	20.1	ug/Kg	1		04/15/16 04:51
Toluene	16.8 U	33.5	10.5	ug/Kg	1		04/15/16 04:51
Surrogates							
1,4-Difluorobenzene (surr)	95.7	72-119		%	1		04/15/16 04:51

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B

Analyst: S.P

Analytical Date/Time: 04/15/16 04:51 Container ID: 1161603001-B

Prep Batch: VXX28685 Prep Method: SW5035A Prep Date/Time: 04/06/16 12:00 Prep Initial Wt./Vol.: 51.295 g

Prep Extract Vol: 30.6335 mL

Print Date: 04/20/2016 1:13:59PM

J flagging is activated



Method Blank

Blank ID: MB for HBN 1731160 [SPT/9866]

Blank Lab ID: 1318918

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by SM21 2540G

 Parameter
 Results
 LOQ/CL
 DL
 Units

 Total Solids
 100
 %

Batch Information

Analytical Batch: SPT9866 Analytical Method: SM21 2540G

Instrument: Analyst: K.W

Analytical Date/Time: 4/7/2016 7:53:00PM

Print Date: 04/20/2016 1:14:00PM



Duplicate Sample Summary

Original Sample ID: 1161579002 Duplicate Sample ID: 1318919

QC for Samples: 1161603001

Analysis Date: 04/07/2016 19:53 Matrix: Soil/Solid (dry weight)

Results by SM21 2540G

<u>NAME</u>	<u>Original</u>	<u>Duplicate</u>	<u>Units</u>	<u>RPD (%)</u>	RPD CL
Total Solids	81.8	82.5	%	0.83	(< 15)

Batch Information

Analytical Batch: SPT9866 Analytical Method: SM21 2540G

Instrument: Analyst: K.W

Print Date: 04/20/2016 1:14:02PM



Method Blank

Blank ID: MB for HBN 1731617 [VXX/28685]

Blank Lab ID: 1319812

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK101

ParameterResultsLOQ/CLDLUnitsGasoline Range Organics1.25U2.500.750mg/Kg

Surrogates

4-Bromofluorobenzene (surr) 76.4 50-150 %

Batch Information

Analytical Batch: VFC12962 Prep Batch: VXX28685
Analytical Method: AK101 Prep Method: SW5035A

Instrument: Agilent 7890A PID/FID Prep Date/Time: 4/14/2016 8:00:00AM

Analyst: S.P Prep Initial Wt./Vol.: 50 g Analytical Date/Time: 4/14/2016 7:38:00PM Prep Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:03PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VXX28685]

Blank Spike Lab ID: 1319815 Date Analyzed: 04/14/2016 20:54

QC for Samples: 1161603001

Spike Duplicate ID: LCSD for HBN 1161603

[VXX28685]

Spike Duplicate Lab ID: 1319816 Matrix: Soil/Solid (dry weight)

Results by AK101

	Е	Blank Spike	(mg/Kg)	s	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	Spike	Result	Rec (%)	CL	RPD (%)	RPD CL
Gasoline Range Organics	12.5	13.5	108	12.5	14.3	114	(60-120)	5.30	(< 20)
Surrogates									
4-Bromofluorobenzene (surr)	1.25	85	85	1.25	88.4	88	(50-150)	3.90	

Batch Information

Analytical Batch: VFC12962
Analytical Method: AK101

Instrument: Agilent 7890A PID/FID

Analyst: S.P

Prep Batch: VXX28685
Prep Method: SW5035A

Prep Date/Time: 04/14/2016 08:00

Spike Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:05PM



Matrix Spike Summary

Original Sample ID: 1161564001 MS Sample ID: 1319817 MS MSD Sample ID: 1319818 MSD

QC for Samples: 1161603001

Analysis Date: 04/15/2016 1:21 Analysis Date: 04/15/2016 1:41 Analysis Date: 04/15/2016 2:00

Matrix: Soil/Solid (dry weight)

Results by AK101

		Matr	rix Spike (n	ng/Kg)	Spike	Duplicate	(mg/Kg)		
Parameter Gasoline Range Organics	Sample 2.09U	<u>Spike</u> 9.46	Result 9.31	Rec (%) 98	<u>Spike</u> 9.46	Result 9.54	Rec (%) 101	<u>CL</u> 60-120	RPD (%) RPD CL (< 20)
Surrogates 4-Bromofluorobenzene (surr)		0.946	0.780	82	0.946	0.799	85	50-150	2.50

Batch Information

Analytical Batch: VFC12962 Analytical Method: AK101 Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/15/2016 1:41:00AM

Prep Batch: VXX28685

Prep Method: AK101 Extraction (S)
Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 68.69g Prep Extract Vol: 25.00mL

Print Date: 04/20/2016 1:14:06PM



Method Blank

Blank ID: MB for HBN 1731617 [VXX/28685]

Blank Lab ID: 1319812

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by SW8021B

<u>Parameter</u>	Results	LOQ/CL	<u>DL</u>	<u>Units</u>
Benzene	6.25U	12.5	4.00	ug/Kg
Ethylbenzene	12.5U	25.0	7.80	ug/Kg
o-Xylene	12.5U	25.0	7.80	ug/Kg
P & M -Xylene	25.0U	50.0	15.0	ug/Kg
Toluene	12.5U	25.0	7.80	ug/Kg
Surrogates				
1,4-Difluorobenzene (surr)	96.1	72-119		%

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/14/2016 7:38:00PM

Prep Batch: VXX28685 Prep Method: SW5035A

Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 50 g Prep Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:07PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [VXX28685]

Blank Spike Lab ID: 1319813 Date Analyzed: 04/14/2016 19:57

QC for Samples: 1161603001

Spike Duplicate ID: LCSD for HBN 1161603

[VXX28685]

Spike Duplicate Lab ID: 1319814 Matrix: Soil/Solid (dry weight)

Results by SW8021B

	E	Blank Spike	(ug/Kg)	S	pike Duplic	ate (ug/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	1250	1320	106	1250	1350	108	(75-125)	2.30	(< 20)
Ethylbenzene	1250	1330	107	1250	1370	109	(75-125)	2.40	(< 20)
o-Xylene	1250	1330	106	1250	1370	110	(75-125)	3.20	(< 20)
P & M -Xylene	2500	2700	108	2500	2760	111	(80-125)	2.30	(< 20)
Toluene	1250	1480	118	1250	1510	121	(70-125)	2.00	(< 20)
Surrogates									
1,4-Difluorobenzene (surr)	1250	97.6	98	1250	97.8	98	(72-119)	0.14	

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Prep Batch: VXX28685
Prep Method: SW5035A

Prep Date/Time: 04/14/2016 08:00

Spike Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL

Print Date: 04/20/2016 1:14:09PM



Matrix Spike Summary

Original Sample ID: 1161564001 MS Sample ID: 1319817 MS MSD Sample ID: 1319818 MSD

QC for Samples: 1161603001

Analysis Date: 04/15/2016 1:21 Analysis Date: 04/15/2016 1:41 Analysis Date: 04/15/2016 2:00 Matrix: Soil/Solid (dry weight)

Results by SW8021B

Treedite by GTTGGZTB			_							
		Mat	rix Spike (ι	ug/Kg)	Spike	Duplicate	(ug/Kg)			
<u>Parameter</u>	<u>Sample</u>	Spike	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	10.4U	946	1003	106	946	1016	107	75-125	1.20	(< 20)
Ethylbenzene	20.9U	946	982	104	946	1002	106	75-125	1.90	(< 20)
o-Xylene	20.9U	946	967	102	946	988	104	75-125	2.10	(< 20)
P & M -Xylene	41.7U	1892	1944	103	1892	1985	105	80-125	2.30	(< 20)
Toluene	20.9U	946	990	105	946	1006	106	70-125	1.60	(< 20)
Surrogates										
1,4-Difluorobenzene (surr)		946	941	100	946	923	98	72-119	1.90	

Batch Information

Analytical Batch: VFC12962 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: S.P

Analytical Date/Time: 4/15/2016 1:41:00AM

Prep Batch: VXX28685

Prep Method: AK101 Extraction (S)
Prep Date/Time: 4/14/2016 8:00:00AM

Prep Initial Wt./Vol.: 68.69g Prep Extract Vol: 25.00mL

Print Date: 04/20/2016 1:14:10PM



Method Blank

Blank ID: MB for HBN 1731261 [XXX/35139]

Blank Lab ID: 1319120

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK102

ParameterResultsLOQ/CLDLUnitsDiesel Range Organics10.0U20.06.20mg/Kg

Surrogates

5a Androstane (surr) 97.9 60-120 %

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK102 Instrument: Agilent 7890B R

Analyst: CJSW

Analytical Date/Time: 4/12/2016 1:17:00PM

Prep Batch: XXX35139 Prep Method: SW3550C

Prep Date/Time: 4/11/2016 9:03:02AM

Prep Initial Wt./Vol.: 30 g Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:11PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [XXX35139]

Blank Spike Lab ID: 1319121 Date Analyzed: 04/12/2016 13:27

QC for Samples: 1161603001

Spike Duplicate ID: LCSD for HBN 1161603

[XXX35139]

Spike Duplicate Lab ID: 1319122 Matrix: Soil/Solid (dry weight)

Results by AK102

	В	lank Spike	(mg/Kg)	S	oike Duplica	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	<u>CL</u>	RPD (%)	RPD CL
Diesel Range Organics	167	171	103	167	198	119	(75-125)	14.60	(< 20)
Surrogates									
5a Androstane (surr)	3.33	104	104	3.33	116	116	(60-120)	11.30	

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK102 Instrument: Agilent 7890B R

Analyst: CJSW

Prep Batch: XXX35139
Prep Method: SW3550C

Prep Date/Time: 04/11/2016 09:03

Spike Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL Dupe Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:12PM



Method Blank

Blank ID: MB for HBN 1731261 [XXX/35139]

Blank Lab ID: 1319120

QC for Samples: 1161603001

Matrix: Soil/Solid (dry weight)

Results by AK103

ParameterResultsLOQ/CLDLUnitsResidual Range Organics10.0U20.06.20mg/Kg

Surrogates

n-Triacontane-d62 (surr) 100 60-120 %

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK103 Instrument: Agilent 7890B R

Instrument: Agilent 7890 Analyst: CJSW

Analytical Date/Time: 4/12/2016 1:17:00PM

Prep Batch: XXX35139 Prep Method: SW3550C

Prep Date/Time: 4/11/2016 9:03:02AM

Prep Initial Wt./Vol.: 30 g Prep Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:13PM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1161603 [XXX35139]

Blank Spike Lab ID: 1319121 Date Analyzed: 04/12/2016 13:27

QC for Samples: 1161603001

Spike Duplicate ID: LCSD for HBN 1161603

[XXX35139]

Spike Duplicate Lab ID: 1319122 Matrix: Soil/Solid (dry weight)

Results by AK103

	Е	lank Spike	(mg/Kg)	s	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Residual Range Organics	167	156	94	167	175	105	(60-120)	11.60	(< 20)
Surrogates									
n-Triacontane-d62 (surr)	3.33	88	88	3.33	99.5	100	(60-120)	12.30	

Batch Information

Analytical Batch: XFC12329 Analytical Method: AK103 Instrument: Agilent 7890B R

Analyst: CJSW

Prep Batch: XXX35139
Prep Method: SW3550C

Prep Date/Time: 04/11/2016 09:03

Spike Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL Dupe Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL

Print Date: 04/20/2016 1:14:14PM



SGS North America Inc. CHAIN OF CUSTODY RECORD

Manyand New York

Indiana

Kentucity œ

Walls Sgs.com

18 Nationwide

	CLIENT: 🧲	CLIENT: GOLDER ASSOCIATES	xiATES			Ë	Instructions: Omissions	ns: Sy	istructions: Sections 1 - 5 must be filled or Omissions may delay the onset of analysis	1 - 5	must b	5 must be filled out.	d out.			
ı	Brento.	Brenton Swikko Sontact:	PHONE NO: 907-865-25	03-865	2524	Section 3				Press	Preservative				Page 10 10 10 10 10 10 10 10 10 10 10 10 10	
uoijoas	PROJECT NAME: ∑₩X	Je /Reflection	PROJECTI PWSJOV PERIMTA:			a 0									}	
5	кероктя то: Всемфи		E-MAIL: E-SavikKo@goldef.com	Kolego	deficom	0 z +		(ब्रा <u>स्</u> ट								
	INVOICE TO:		QUÖTE#: 1523636	3636		₹ - z		ष्ट्र/१ठ (<i>३.19</i> ,								
	RESERVED for lab use	SAMPLE IDENTIFICATION	OATE mm/dd/yy	TIME	MATRIX MATRIX CODE			DRO/ GRO/ GRO/			···				REMARKS/	
	S/40	BH-8 #5	OHIVETE	12:00	Soil		×	×		L				-		
S no						-		†	<u> </u>	+		+	+			
itə ə 2												H	_			
3															i	
			1									+	+	+	İ	
									$\frac{1}{1}$			$\dagger \dagger$	+			
						-	-			4		-	1	-		_
	Relinquished By: (1)	d By: (1)	Clate		Received By:				Section 4	_	D Project	DOD Project? Yes No		ata Deliv	rable R	
	Brento:	Brenton SaviKKO	cyfortio	15.35	$\frac{\left(\cdot \right)}{\cdot}$	~			Cooler ID:					ره ۱۹۵۸ ره ۱۹۵۸ کې ۲۸	A + EDD +	
<u> </u>	Refinguished By: (2)	l By: (2)	Date	Time	Rocolved By:			<u> </u>	Requested Turnaround Time and/or Special Instructions:	Turnaro	und Thm	andvor	pecial	nstruction		
ection	E Retinquished By: (3)	By: (3)	Date	<u>T</u> m0	Received By:											
S		1	\					<u> </u>	Temp Blank °C:	ن ا	}		Ě	Chain of (Chain of Custody Seal: (Clrele)	
	Relinquished By: (4)	By: (4)	Date 4/6/16	Time /535	Received For Jaboratory By:	aboratory E	in \		or Ambient () (See attached Sample Receipt Form)	or Arr ched Sai	or Ambient TA	A sipt Form	ı	INTACT 9e altacho	INTACT BROKEN ABSENT (See attached Sample Receipt Form)	
	:											ļ	1			_

200 W. Potter Drive Anchorage, AK 99618 Tol; (907) 562-2343 Fax; (907) 561-5301
 3 5500 Business Drive Wilmington, NC 28405 Tel; (910) 350-1903 Fax; (910) 350-1557

<u>ឬពីp./www sqs com/terms-and-conditions</u>



1161603



SAMPLE RECEIPT FORM

Review Criteria:	Yes	N/A	No	Comments/Action Taken:
Were custody seals intact? Note # & location, if applicable.	П	/	П	Exemption permitted if sampler hand carries/delivers.
COC accompanied samples?			Ħ	,
Temperature blank compliant* (i.e., 0-6°C after CF)?			7	Exemption permitted if chilled & collected <8 hrs ago.
If $>$ 6°C, were samples collected $<$ 8 hours ago?		Ħ	Ħ	
If < 0 °C, were all sample containers ice free?		7	Ħ	
Cooler ID: 1 @ ambient w/ Therm ID:	_		_	
Cooler ID: @_ ambient w/ Therm.ID: Cooler ID: @ w/ Therm.ID:				
Cooler ID: @ w/ Therm.ID:				
Cooler ID: @ w/ Therm.ID:				
Cooler ID: @ w/ Therm.ID:				
If samples are received without a temperature blank, the "cooler				
temperature" will be documented in lieu of the temperature blank &				
"COOLER TEMP" will be noted to the right. In cases where neither a				Note: Identify containers received at non-compliant
temp blank <u>nor</u> cooler temp can be obtained, note "ambient" or "chilled."				temperature. Use form FS-0029 if more space is needed.
Delivery method (specify all that apply):				
□USPS □Lynden □AK Air □Alert Courier				
\square UPS \square FedEx \square RAVN \square C&D Delivery				
☐Carlile ☐Pen Air ☐Warp Speed☐Other:				
\rightarrow For WO# with airbills, was the WO# & airbill	_	_	_	
info recorded in the Front Counter eLog?	Ш	\checkmark		
	Yes	N/A	No	
Were samples received within hold time?	165	IN/A	INO	Note: Refer to form F-083 "Sample Guide" for hold times.
Do samples match COC* (i.e., sample IDs, dates/times collected)?	<u></u>	H	H	Note: If times differ <1hr, record details and login per COC.
Were analyses requested unambiguous?	7	H	H	
Were samples in good condition (no leaks/cracks/breakage)?	<u></u>	\dashv	H	
Packing material used (specify all that apply): Bubble Wrap	V	Ш	ш	
Separate plastic bags Vermiculite Other:				
Were proper containers (type/mass/volume/preservative*) used?				Exemption permitted for metals (e.g., 200.8/6020A).
Were Trip Blanks (i.e., VOAs, LL-Hg) in cooler with samples?	H	\vdash	<u> </u>	
Were all VOA vials free of headspace (i.e., bubbles <6 mm)?		Y	H	Samples were sub-sampled and extracted by lab
Were all soil VOAs field extracted with MeOH+BFB?		V	\vdash	upon receipt
For preserved waters (other than VOA vials, LL-Mercury or	Ш		V	
microbiological analyses), was pH verified and compliant ?		.7		
If pH was adjusted, were bottles flagged (i.e., stickers)?	H		H	
For special handling (e.g., "MI" soils, foreign soils, lab filter for	ш	V		
dissolved, lab extract for volatiles, Ref Lab, limited volume),				
were bottles/paperwork flagged (e.g., sticker)?		\checkmark		
For RUSH/SHORT Hold Time, were COC/Bottles flagged	ш	W_		
		\checkmark		
accordingly? Was Rush/Short HT email sent, if applicable? For SITE-SPECIFIC QC, e.g. BMS/BMSD/BDUP, were	ш	¥		
containers / paperwork flagged accordingly?		V		
For any question answered "No," has the PM been notified and	ш	V		SRF Completed by: CRD
the problem resolved (or paperwork put in their bin)?		\checkmark		PM notified:
Was PEER REVIEW of sample numbering/labeling completed?	H		+	Peer Reviewed by:
	Ш	√		reel Reviewed by.
Additional notes (if applicable):				
Note to Client: Any "no" answer above indicates non-comp	liance	with	tanda	ard procedures and may impact data quality
1.00 to Chem. 11hy no unsiver above materies non-compl	unice	· rrilli D	unu	a procedures and may impact data quatity.



Sample Containers and Preservatives

Container Id	<u>Preservative</u>	<u>Container</u>	Container Id	<u>Preservative</u>	<u>Container</u>
		<u>Condition</u>			<u>Condition</u>
1161603001-A	No Preservative Required	OK			
1161603001-B	Methanol field pres. 4 C	ОК			

Container Condition Glossary

Containers for bacteriological, low level mercury and VOA vials are not opened prior to analysis and will be assigned condition code OK unless evidence indicates than an inappropriate container was submitted.

- OK The container was received at an acceptable pH for the analysis requested.
- BU The container was received with headspace greater than 6mm.
- DM- The container was received damaged.
- FR- The container was received frozen and not usable for Bacteria or BOD analyses.
- PA The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt and the container is now at the correct pH. See the Sample Receipt Form for details on the amount and lot # of the preservative added.
- PH The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt, but was insufficient to bring the container to the correct pH for the analysis requested. See the Sample Receipt Form for details on the amount and lot # of the preservative added.

4/6/2016 22 of 27

CHROMATOGRAMS

(QT Reviewed) Quantitation Report

Data Path : Z:\04\SF\DATA\041216\

Data File : 12013.D Signal(s) : FID3B.ch

Acq On : 12 Apr 2016 1:56 pm

Operator : CJSW Sample

Misc


ALS Vial Sample Multiplier: 1 : 8

Integration File: autoint1.e Quant Time: Apr 13 11:59:20 2016

Quant Method : Z:\04\SF\METHOD\SFR2016-0407A.M Quant Title : DRO/RRO by Method AK 102/103 QLast Update : Fri Apr 08 09:05:55 2016 Response via : Initial Calibration

Integrator: ChemStation

Volume Inj. : Signal Phase : Signal Info :



Data Path : $Z:\01\SD\DATA\020215A\$

Data File : SD020215A_007.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:01 pm

Operator : NLL Sample : NAS

Sample : NAS Normal Alkane Standards
Misc :

ALS Vial : 2 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:21:38 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M
Quant Title: DRO/RRO by Method AK 102/103
QLast Update: Mon Feb 02 09:35:16 2015

Response via: Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



Data Path : $Z:\01\SD\DATA\020215A\$

Data File : SD020215A_008.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:11 pm

Operator : NLL

Sample : CCVB Diesel Range Organics

Misc :
ALS Vial : 3 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:23:42 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M
Quant Title: DRO/RRO by Method AK 102/103
QLast Update: Mon Feb 02 09:35:16 2015

Response via : Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



Data Path : Z:\01\SD\DATA\020215A\

Data File : SD020215A_009.D

Signal(s) : FID2B.CH

Acq On : 02 Feb 2015 1:21 pm

Operator : NLL Residual Range Organics
Sample : CCVR "Lube Oil" standard

Misc :

ALS Vial : 4 Sample Multiplier: 1


Integration File: autoint1.e
Quant Time: Feb 02 13:28:20 2015

Quant Method: Z:\01\SD\METHOD\SDR2015-0130C.M
Quant Title: DRO/RRO by Method AK 102/103
QLast Update: Mon Feb 02 09:35:16 2015

Response via : Initial Calibration

Integrator: ChemStation 6890 Scale Mode: Small noise peaks clipped

Volume Inj. : Signal Phase : Signal Info :



APPENDIX D
LABORATORY DATA FROM SEPTEMBER 2016 INVESTIGATION

Laboratory Data Review Checklist

Completed by:	mpleted by: Christopher Valentine					
Title:	Project Enginee	er	Date:	Nov 23, 2016		
CS Report Name:	Report Name: Image / Reflection Drive			Report Date:	Sep 23, 2016	
Consultant Firm:	Consultant Firm: Golder Associates Inc.					
Laboratory Name:	SGS		Laboratory Report N	Number: 1165330		
ADEC File Number:	ADEC File Number: n/a			nber: n/a		
Laboratory a. Did an ADEC CS approved laboratory receive and perform all of the submitted sample are submitted samples.				sample analyses?		
• Yes	S O No	O NA (Plea	ise explain.)	Comments:		
b. If the samples were transferred to another "network" laboratory or sub-contracted to an alternate laboratory, was the laboratory performing the analyses ADEC CS approved? O Yes No ONA (Please explain) Comments:						
•	2. Chain of Custody (COC) a. COC information completed, signed, and dated (including released/received by)? • Yes • No • NA (Please explain) Comments:					
b. Correct analyses requested? • Yes • No • NA (Please explain) Comments:						
3. <u>Laboratory Sample Receipt Documentation</u> a. Sample/cooler temperature documented and within range at receipt (4° ± 2° C)? • Yes • No • NA (Please explain) Comments:						
The cooler was	measured with to	emperature blan	k at 5.9° C			

		servation accer lorinated Solv	ptable - acidified waters, Methanol ents, etc.)?	preserved VOC soil (GRO, BTEX,
•	Yes	○ No	○ NA (Please explain)	Comments:
c. Sam	nple con	dition docume	nted - broken, leaking (Methanol),	zero headspace (VOC vials)?
•	Yes	○ No	○ NA (Please explain)	Comments:
Sample c	ondition	documented,	all samples in good condition	
		• •	•	r example, incorrect sample containers/nsufficient or missing samples, etc.?
•	Yes	○ No	ONA (Please explain)	Comments:
Sample D	P-3C ac	cidentally liste	d as DP-3A on COC	
e. Data	a quality	or usability a	ffected? (Please explain)	
				Comments:
		ere usable for nd receipt cond	project purposes without qualificati litions.	on with respect to sample
Case Narrat	<u>tive</u>			
a. Pres	ent and	understandabl	e?	
•	Yes	○ No	ONA (Please explain)	Comments:
b. Disc	crepanci	es, errors or C	C failures identified by the lab?	
	Yes	• No	○ NA (Please explain)	Comments:
	re all con Yes	rrective action	s documented? NA (Please explain)	Comments:
none				
d. Wh	at is the	effect on data	quality/usability according to the ca	ase narrative? Comments:
Sample re	esults w	ere usable for	project purposes with some qualific	

4.

Tes Tes	• Yes O No ONA (Please explain)		Comments:
b. All applical	ole holding tin	nes met?	
• Yes	○ No	○ NA (Please explain)	Comments:
c. All soils rep	oorted on a dry	weight basis?	
• Yes	○ No	○NA (Please explain)	Comments:
d. Are the reperproject?	orted PQLs les	ss than the Cleanup Level or the mir	nimum required detection level for
• Yes	○ No	○ NA (Please explain)	Comments:
e. Data quality	or usability a	ffected? (Please explain)	
		iffected? (Please explain) project purposes with respect to hol	Comments:
ample results w C Samples a. Method Blar	ere usable for	project purposes with respect to hol	ding times and reporting limits.
ample results w C Samples a. Method Blar	ere usable for nk ethod blank rep	project purposes with respect to hole	ding times and reporting limits.
ample results w C Samples a. Method Blar i. One me	ere usable for nk ethod blank rep s	project purposes with respect to hole	amples?
ample results w C Samples a. Method Blar i. One me	ere usable for nk ethod blank rep s	project purposes with respect to hole ported per matrix, analysis and 20 sa	amples?

5. <u>Samples Results</u>

	• Yes	○ No	ONA (Please explain)	Comments:			
	v. Data qua	ality or usabil	lity affected? (Please explain)	Comments:			
All r	esults were	usable for pro	oject purposes.				
b. 1	Laboratory	Control Samp	ple/Duplicate (LCS/LCSD)				
	-		CCSD reported per matrix, analysis equired per SW846)	and 20 samples? (LCS/LCSD required			
	• Yes	○ No	○ NA (Please explain)	Comments:			
	ii. Metals/l samples?	Inorganics - C	One LCS and one sample duplicate r	eported per matrix, analysis and 20			
	○ Yes	\bigcirc No	• NA (Please explain)	Comments:			
no m	etals sample	taken					
	project spe	cified DQOs	ent recoveries (%R) reported and wi , if applicable. (AK Petroleum meth %-120%; all other analyses see the la				
	• Yes	○ No	ONA (Please explain)	Comments:			
	iv. Precision - All relative percent differences (RPD) reported and less than method or laboratory limits? And project specified DQOs, if applicable. RPD reported from LCS/LCSD, MS/DMSD, and or sample/sample duplicate. (AK Petroleum methods 20%; all other analyses see the laboratory QC pages)						
	○ Yes	No	○NA (Please explain)	Comments:			
See 7	Γable 3 for s	summary, and	see section 3.3.3 of report for expla	nation			
	v. If %R o	r RPD is outs	ide of acceptable limits, what sampl	es are affected? Comments:			
none							

	O Yes	No	ONA (Please explain)	Comments:
no fl	lags needed			
	vii. Data q	uality or usab	ility affected? (Please explain)	Comments:
no				
c	Surrogates -	Organics On	lv	
C.	Č	C	es reported for organic analyses - fi	eld. OC and laboratory samples?
	• Yes	○ No	CNA (Please explain)	Comments:
	project spe	•	if applicable. (AK Petroleum meth-	hin method or laboratory limits? And ods 50-150 %R; all other analyses see
	• Yes	○ No	○ NA (Please explain)	Comments:
	clearly def	-	○ NA (Please explain)	ave data flags? If so, are the data flags Comments:
Sami			lity affected? (Use the comment box	Comments:
d.	Trip Blank			Chlorinated Solvents, etc.): Water and
<u>Sc</u>	i. One trip	blank reporte er explanation	d per matrix, analysis and for each on below.)	cooler containing volatile samples?
	• Yes	○ No	O NA (Please explain.)	Comments:
	:: Ta 4h a a a			
			ransport the trip blank and VOA san plaining why must be entered belov	± •

iii. All 1	esults less than I	PQL?	
• Yes	○ No	O NA (Please explain.)	Comments:
The water and	soil trip blank re	sults were all less than LOQ	
iv. If al	pove PQL, what	samples are affected?	
			Comments:
All associated	project sample i	results were less than LOQ.	
v. Data	quality or usabil	ity affected? (Please explain.)	
			Comments:
Sample result	s were usable for	r project purposes. Data quality or	r usability was not affected.
e. Field Dup	licate		
•		omitted per matrix, analysis and 1	0 project samples?
	_		
• Yes	○ No	○ NA (Please explain)	Comments:
		plicate submitted for this project. State was DP-6 from DP-1.	Soil field duplicate was DP-2C from
	nitted blind to la		
• Yes	○ No	○ NA (Please explain.)	Comments:
		· · · · · · · · · · · · · · · · · · ·	Comments.
		ve percent differences (RPD) less 6 water, 50% soil)	s than specified DQOs?
	I	RPD(%) = Absolute Value of: (R)	₁₋ R ₂) x 100
		$((R_{1+})^{-1})^{-1}$	$R_2)/2)$
Where	$R_1 = Sample Co$		
	$R_2 = Field Dupl$	licate Concentration	
• Yes	○ No	○ NA (Please explain)	Comments:
All anlaytes n	net field duplicat	e RPD criteria.	
iv. Data	a quality or usabi	ility affected? (Use the comment	box to explain why or why not.)
○ Ye	s O No	• NA (Please explain)	Comments:
Sample result	s were usable for	r project purposes.	

f. Deconta	mination or Equ	uipment Blank (if applicable)	
○ Ye	s O No	NA (Please explain)	Comments:
No equipmen	t blank taken		
i. All r	esults less than	PQL?	
• Ye	S O No	ONA (Please explain)	Comments:
ii. If at	oove PQL, what	samples are affected?	Comments:
iii. Dat	a quality or usa	bility affected? (Please explain.)	
Data quality o	or usability was	not affected	Comments:
	•	COE, AFCEE, Lab Specific, etc.)	
a. Defined	and appropriate	?	
• Ye	s O No	ONA (Please explain)	Comments:

Reset Form



Laboratory Report of Analysis

To: Golder Associates Inc.

2121 Abbott Road, #100 Anchorage, AK 99507 (907)344-6001

Report Number: 1165330

Client Project: Image Reflection Drive

Dear Chris Valentine,

Enclosed are the results of the analytical services performed under the referenced project for the received samples and associated QC as applicable. The samples are certified to meet the requirements of the National Environmental Laboratory Accreditation Conference Standards. Copies of this report and supporting data will be retained in our files for a period of ten years in the event they are required for future reference. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. Any samples submitted to our laboratory will be retained for a maximum of fourteen (14) days from the date of this report unless other archiving requirements were included in the quote.

If there are any questions about the report or services performed during this project, please call Victoria at (907) 562-2343. We will be happy to answer any questions or concerns which you may have.

Thank you for using SGS North America Inc. for your analytical services. We look forward to working with you again on any additional analytical needs.

Sincerely,

SGS North America Inc.

Victoria Pennick

2016.09.23

Date

n America Inc.
ntal Services - Alaska Division
14:27:08 -08'00'

Victoria Pennick

Project Manager Victoria.Pennick@sgs.com

Print Date: 09/23/2016 8:02:24AM



Case Narrative

SGS Client: Golder Associates Inc.
SGS Project: 1165330
Project Name/Site: Image Reflection Drive
Project Contact: Chris Valentine

Refer to sample receipt form for information on sample condition.

*QC comments may be associated with the field samples found in this report. When applicable, comments will be applied to associated field samples.

Print Date: 09/23/2016 8:02:26AM



Laboratory Qualifiers

Enclosed are the analytical results associated with the above work order. All results are intended to be used in their entirety and SGS is not responsible for use of less than the complete report. This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx. Attention is drawn to the limitation of liability, indenmification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the context or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS maintains a formal Quality Assurance/Quality Control (QA/QC) program. A copy of our Quality Assurance Plan (QAP), which outlines this program, is available at your request. The laboratory certification numbers are AK00971 (DW Chemistry & Microbiology) & UST-005 (CS) for ADEC and 2944.01 for DOD ELAP/ISO17025 (RCRA methods: 1020B, 1311, 3010A, 3050B, 3520C, 3550C, 5030B, 5035A, 6020A, 7470A, 7471B, 8021B, 8082A, 8260B, 8270D, 8270D-SIM, 9040C, 9045D, 9056A, 9060A, AK101 and AK102/103). Except as specifically noted, all statements and data in this report are in conformance to the provisions set forth by the SGS QAP and, when applicable, other regulatory authorities.

The following descriptors or qualifiers may be found in your report:

* The analyte has exceeded allowable regulatory or control limits.

! Surrogate out of control limits.

B Indicates the analyte is found in a blank associated with the sample.

CCV/CVA/CVB Continuing Calibration Verification

CCCV/CVC/CVCA/CVCB Closing Continuing Calibration Verification

CL Control Limit

D The analyte concentration is the result of a dilution.

DF Dilution Factor

DL Detection Limit (i.e., maximum method detection limit)
E The analyte result is above the calibrated range.
F Indicates value that is greater than or equal to the DL

GT Greater Than
IB Instrument Blank

ICV Initial Calibration Verification

J The quantitation is an estimation.

JL The analyte was positively identified, but the quantitation is a low estimation.

LCS(D) Laboratory Control Spike (Duplicate)
LOD Limit of Detection (i.e., 1/2 of the LOQ)

LOQ Limit of Quantitation (i.e., reporting or practical quantitation limit)

LT Less Than

M A matrix effect was present.

MB Method Blank

MS(D) Matrix Spike (Duplicate)

ND Indicates the analyte is not detected.
Q QC parameter out of acceptance range.

R Rejected

RPD Relative Percent Difference

U Indicates the analyte was analyzed for but not detected.

Note: Sample summaries which include a result for "Total Solids" have already been adjusted for moisture content.

All DRO/RRO analyses are integrated per SOP.

Print Date: 09/23/2016 8:02:30AM

SGS North America Inc. | 200 West Potter Drive, Anchorage, AK 99518 | t 907.562.2343 f 907.561.5301 www.us.sgs.com



Sample Summary

Client Sample ID	Lab Sample ID	Collected	Received	<u>Matrix</u>
DP-1A	1165330001	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-1B	1165330002	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-2A	1165330003	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-2C	1165330004	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-2B	1165330005	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-3C	1165330006	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-3B	1165330007	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-4A	1165330008	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-4B	1165330009	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-5A	1165330010	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-5B	1165330011	09/08/2016	09/08/2016	Soil/Solid (dry weight)
Trip Blank	1165330012	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-1	1165330013	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-6	1165330014	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-2	1165330015	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-3	1165330016	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-4	1165330017	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-5	1165330018	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
Trip Blank	1165330019	09/08/2016	09/08/2016	Water (Surface, Eff., Ground)
DP-5B MS	1165330020	09/08/2016	09/08/2016	Soil/Solid (dry weight)
DP-5B MSD	1165330021	09/08/2016	09/08/2016	Soil/Solid (dry weight)

 Method
 Method Description

 AK101
 AK101/8021 Combo.

 SW8021B
 AK101/8021 Combo.

 AK101
 AK101/8021 Combo. (S)

 SW8021B
 AK101/8021 Combo. (S)

AK102 Diesel/Residual Range Organics
AK103 Diesel/Residual Range Organics
AK102 DRO/RRO Low Volume Water
AK103 DRO/RRO Low Volume Water
SM21 2540G Percent Solids SM2540G

Print Date: 09/23/2016 8:02:32AM



Detectable Results Summary

Client Sample ID: DP-1A			
Lab Sample ID: 1165330001	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Residual Range Organics	25.9	mg/Kg
Client Sample ID: DP-1B			
Lab Sample ID: 1165330002	Parameter	Result	Units
Semivolatile Organic Fuels	Residual Range Organics	9.86J	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.741J	mg/Kg
	3		3 3
Client Sample ID: DP-2A			
Lab Sample ID: 1165330003	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	56.0J	mg/Kg
	Residual Range Organics	511	mg/Kg
Client Sample ID: DP-2C			
Lab Sample ID: 1165330004	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	130	mg/Kg
	Residual Range Organics	1810	mg/Kg
Client Sample ID: DP-2B			
Lab Sample ID: 1165330005	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	7.45J	mg/Kg
Comvolatile Organie i dels	Residual Range Organics	12.1J	mg/Kg
01: 10 1 10 00			99
Client Sample ID: DP-3C			
Lab Sample ID: 1165330006	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Residual Range Organics	6.89J	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.598J	mg/Kg
Client Sample ID: DP-3B			
Lab Sample ID: 1165330007	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	15.2J	mg/Kg
	Residual Range Organics	85.3	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.678J	mg/Kg
Client Sample ID: DP-4A			
Lab Sample ID: 1165330008	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	16.1J	mg/Kg
Commodumo Crigamo i dolo	Residual Range Organics	37.7	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.538J	mg/Kg
	3 3		3 3
Client Sample ID: DP-4B		- "	
Lab Sample ID: 1165330009	Parameter Discal Bango Organica	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	10.7J	mg/Kg
Waladia Foota	Residual Range Organics	17.3J	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.904J	mg/Kg

Print Date: 09/23/2016 8:02:34AM

200 West Potter Drive, Anchorage, AK 99518 t 907.562.2343 f 907.561.5301 www.us.sgs.com



Detectable Results Summary

Client Sample ID: DP-5A			
Lab Sample ID: 1165330010	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	13.2J	mg/Kg
	Residual Range Organics	42.1	mg/Kg
Volatile Fuels	Gasoline Range Organics	0.680J	mg/Kg
Client Sample ID: DP-5B			
Lab Sample ID: 1165330011	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	9.55J	mg/Kg
G	Residual Range Organics	42.6	mg/Kg
Client Sample ID: Trip Blank			
Lab Sample ID: 1165330012	<u>Parameter</u>	Result	<u>Units</u>
Volatile Fuels	Gasoline Range Organics	0.787J	mg/Kg
Client Sample ID: DP-1			
Lab Sample ID: 1165330013	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	0.229J	mg/L
Client Sample ID: DP-6			
Lab Sample ID: 1165330014	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	0.212J	mg/L
Client Sample ID: DP-2			
Lab Sample ID: 1165330015	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	0.187J	mg/L
Client Sample ID: DP-3			
Lab Sample ID: 1165330016	Parameter	Result	Units
Semivolatile Organic Fuels	Diesel Range Organics	0.240J	mg/L
Volatile Fuels	Toluene	0.510J	ug/L
	Tolderic	0.0100	ug/L
Client Sample ID: DP-4			
Lab Sample ID: 1165330017	<u>Parameter</u>	Result	<u>Units</u>
Semivolatile Organic Fuels	Diesel Range Organics	0.322J	mg/L
	Residual Range Organics	0.250J	mg/L

Print Date: 09/23/2016 8:02:34AM



Results of DP-1A

Client Sample ID: DP-1A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330001 Lab Project ID: 1165330 Collection Date: 09/08/16 09:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):89.1 Location:

Results by Semivolatile Organic Fuels

Parameter	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable Limits	Date Analyzed
Diesel Range Organics	11.1 U	22.2	6.89	mg/Kg	1	<u>Enrito</u>	09/18/16 03:20
Surrogates							
5a Androstane (surr)	88.2	50-150		%	1		09/18/16 03:20

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 03:20 Container ID: 1165330001-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.285 g Prep Extract Vol: 1 mL

<u>Parameter</u>	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
Residual Range Organics	25.9	22.2	6.89	mg/Kg	1	Limits	09/18/16 03:20
Surrogates n-Triacontane-d62 (surr)	107	50-150		%	1		09/18/16 03:20

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 03:20 Container ID: 1165330001-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.285 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-1A

Client Sample ID: DP-1A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330001 Lab Project ID: 1165330 Collection Date: 09/08/16 09:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):89.1 Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	1.20 U	2.40	0.721	mg/Kg	1	Limits	09/10/16 14:33
Surrogates 4-Bromofluorobenzene (surr)	108	50-150		%	1		09/10/16 14:33

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 14:33 Container ID: 1165330001-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 09:20 Prep Initial Wt./Vol.: 78.156 g Prep Extract Vol: 33.4934 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	6.00 U	12.0	3.85	ug/Kg	1		09/10/16 14:33
Ethylbenzene	12.0 U	24.0	7.50	ug/Kg	1		09/10/16 14:33
o-Xylene	12.0 U	24.0	7.50	ug/Kg	1		09/10/16 14:33
P & M -Xylene	24.1 U	48.1	14.4	ug/Kg	1		09/10/16 14:33
Toluene	12.0 U	24.0	7.50	ug/Kg	1		09/10/16 14:33
Surrogates							
1,4-Difluorobenzene (surr)	93.2	72-119		%	1		09/10/16 14:33

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 14:33 Container ID: 1165330001-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 09:20 Prep Initial Wt./Vol.: 78.156 g

Prep Extract Vol: 33.4934 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-1B

Client Sample ID: DP-1B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330002 Lab Project ID: 1165330 Collection Date: 09/08/16 09:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):84.5 Location:

Results by Semivolatile Organic Fuels

<u>Parameter</u> Diesel Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	Date Analyzed
	11.8 U	23.6	7.31	mg/Kg	1	Limits	09/18/16 03:31
Surrogates 5a Androstane (surr)	83.5	50-150		%	1		09/18/16 03:31

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 03:31 Container ID: 1165330002-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.115 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	9.86 J	23.6	7.31	mg/Kg	1		09/18/16 03:31
Surrogates							
	00.5	50.450		0/			00/40/40 00:04
n-Triacontane-d62 (surr)	86.5	50-150		%	1		09/18/16 03:31

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 03:31 Container ID: 1165330002-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.115 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-1B

Client Sample ID: DP-1B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330002 Lab Project ID: 1165330

Collection Date: 09/08/16 09:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):84.5 Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.741 J	2.24	0.671	mg/Kg	1	Limits	09/10/16 14:52
Surrogates 4-Bromofluorobenzene (surr)	136	50-150		%	1		09/10/16 14:52

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 14:52 Container ID: 1165330002-B

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 09:35 Prep Initial Wt./Vol.: 111.674 g Prep Extract Vol: 42.2604 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	5.60 U	11.2	3.58	ug/Kg	1		09/10/16 14:52
Ethylbenzene	11.2 U	22.4	6.98	ug/Kg	1		09/10/16 14:52
o-Xylene	11.2 U	22.4	6.98	ug/Kg	1		09/10/16 14:52
P & M -Xylene	22.4 U	44.8	13.4	ug/Kg	1		09/10/16 14:52
Toluene	11.2 U	22.4	6.98	ug/Kg	1		09/10/16 14:52
Surrogates							
1,4-Difluorobenzene (surr)	93.2	72-119		%	1		09/10/16 14:52

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 14:52 Container ID: 1165330002-B

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 09:35 Prep Initial Wt./Vol.: 111.674 g

Prep Extract Vol: 42.2604 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-2A

Client Sample ID: DP-2A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330003 Lab Project ID: 1165330 Collection Date: 09/08/16 10:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.5 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	56.0 J	114	35.3	mg/Kg	1		09/18/16 03:41
Surrogates							
5a Androstane (surr)	101	50-150		%	1		09/18/16 03:41

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 03:41 Container ID: 1165330003-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.493 g Prep Extract Vol: 5 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	511	114	35.3	mg/Kg	1		09/18/16 03:41
Surrogates							
n-Triacontane-d62 (surr)	108	50-150		%	1		09/18/16 03:41

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 03:41 Container ID: 1165330003-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.493 g Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-2A

Client Sample ID: DP-2A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330003 Lab Project ID: 1165330 Collection Date: 09/08/16 10:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.5 Location:

Results by Volatile Fuels

<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable Limits	Date Analyzed
Gasoline Range Organics	1.43 U	2.86	0.859	mg/Kg	1		09/10/16 15:10
Surrogates							
4-Bromofluorobenzene (surr)	111	50-150		%	1		09/10/16 15:10

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 15:10 Container ID: 1165330003-B

Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 10:20
Prep Initial Wt./Vol.: 69.303 g
Prep Extract Vol: 34.3456 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	7.15 U	14.3	4.58	ug/Kg	1		09/10/16 15:10
Ethylbenzene	14.3 U	28.6	8.94	ug/Kg	1		09/10/16 15:10
o-Xylene	14.3 U	28.6	8.94	ug/Kg	1		09/10/16 15:10
P & M -Xylene	28.6 U	57.3	17.2	ug/Kg	1		09/10/16 15:10
Toluene	14.3 U	28.6	8.94	ug/Kg	1		09/10/16 15:10
Surrogates							
1,4-Difluorobenzene (surr)	91.3	72-119		%	1		09/10/16 15:10

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 15:10 Container ID: 1165330003-B

Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 10:20
Prep Initial Wt./Vol.: 69.303 g
Prep Extract Vol: 34.3456 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-2C

Client Sample ID: DP-2C

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330004 Lab Project ID: 1165330 Collection Date: 09/08/16 10:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.9 Location:

Results by Semivolatile Organic Fuels

_						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	130	114	35.2	mg/Kg	1		09/18/16 03:51
Surrogates							
5a Androstane (surr)	101	50-150		%	1		09/18/16 03:51

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 03:51 Container ID: 1165330004-A

Prep Batch: XXX36322
Prep Method: SW3550C
Prep Date/Time: 09/16/16 21:12
Prep Initial Wt./Vol.: 30.372 g
Prep Extract Vol: 5 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	1810	114	35.2	mg/Kg	1		09/18/16 03:51
Surrogates							
n-Triacontane-d62 (surr)	63.4	50-150		%	1		09/18/16 03:51

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 03:51 Container ID: 1165330004-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.372 g Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-2C

Client Sample ID: DP-2C

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330004 Lab Project ID: 1165330 Collection Date: 09/08/16 10:20 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.9 Location:

Results by Volatile Fuels

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	1.40 U	2.80	0.840	mg/Kg	1		09/10/16 15:29
Surrogates							
4-Bromofluorobenzene (surr)	109	50-150		%	1		09/10/16 15:29

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 15:29 Container ID: 1165330004-B Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 10:20
Prep Initial Wt./Vol.: 70.206 g
Prep Extract Vol: 34.1721 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	7.00 U	14.0	4.48	ug/Kg	1		09/10/16 15:29
Ethylbenzene	14.0 U	28.0	8.73	ug/Kg	1		09/10/16 15:29
o-Xylene	14.0 U	28.0	8.73	ug/Kg	1		09/10/16 15:29
P & M -Xylene	28.0 U	56.0	16.8	ug/Kg	1		09/10/16 15:29
Toluene	14.0 U	28.0	8.73	ug/Kg	1		09/10/16 15:29
Surrogates							
1,4-Difluorobenzene (surr)	92.7	72-119		%	1		09/10/16 15:29

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 15:29 Container ID: 1165330004-B Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 10:20
Prep Initial Wt./Vol.: 70.206 g
Prep Extract Vol: 34.1721 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-2B

Client Sample ID: DP-2B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330005 Lab Project ID: 1165330 Collection Date: 09/08/16 10:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.7 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	7.45 J	22.9	7.10	mg/Kg	1		09/18/16 04:02
Surrogates							
5a Androstane (surr)	83.5	50-150		%	1		09/18/16 04:02

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:02 Container ID: 1165330005-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.212 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	12.1 J	22.9	7.10	mg/Kg	1		09/18/16 04:02
Surrogates							
n-Triacontane-d62 (surr)	84.8	50-150		%	1		09/18/16 04:02

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:02 Container ID: 1165330005-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.212 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM

200 West Potter Drive Anchorage, AK 95518 t 907.562.2343 f 907.561.5301 www.us.sgs.com



Results of DP-2B

Client Sample ID: DP-2B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330005 Lab Project ID: 1165330

Collection Date: 09/08/16 10:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):86.7 Location:

Results by Volatile Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.975 U	1.95	0.585	mg/Kg	1		09/10/16 15:47
Surrogates							
4-Bromofluorobenzene (surr)	138	50-150		%	1		09/10/16 15:47

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 15:47 Container ID: 1165330005-B

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 10:35 Prep Initial Wt./Vol.: 122.018 g Prep Extract Vol: 41.2472 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	4.88 U	9.75	3.12	ug/Kg	1		09/10/16 15:47
Ethylbenzene	9.75 U	19.5	6.08	ug/Kg	1		09/10/16 15:47
o-Xylene	9.75 U	19.5	6.08	ug/Kg	1		09/10/16 15:47
P & M -Xylene	19.5 U	39.0	11.7	ug/Kg	1		09/10/16 15:47
Toluene	9.75 U	19.5	6.08	ug/Kg	1		09/10/16 15:47
Surrogates							
1,4-Difluorobenzene (surr)	92.7	72-119		%	1		09/10/16 15:47

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 15:47 Container ID: 1165330005-B

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 10:35 Prep Initial Wt./Vol.: 122.018 g

Prep Extract Vol: 41.2472 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-3C

Client Sample ID: DP-3C

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330006 Lab Project ID: 1165330 Collection Date: 09/08/16 11:40 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):92.2 Location:

Results by Semivolatile Organic Fuels

<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable Limits	Date Analyzed
Diesel Range Organics	10.8 U	21.5	6.67	mg/Kg	1		09/18/16 04:12
Surrogates				0.4			
5a Androstane (surr)	83.8	50-150		%	1		09/18/16 04:12

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:12 Container ID: 1165330006-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.253 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	6.89 J	21.5	6.67	mg/Kg	1		09/18/16 04:12
Surrogates							
n-Triacontane-d62 (surr)	85.3	50-150		%	1		09/18/16 04:12

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:12 Container ID: 1165330006-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.253 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-3C

Client Sample ID: DP-3C

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330006 Lab Project ID: 1165330 Collection Date: 09/08/16 11:40 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):92.2 Location:

Results by Volatile Fuels

<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable <u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.598 J	1.58	0.475	mg/Kg	1		09/10/16 16:06
Surrogates							
4-Bromofluorobenzene (surr)	116	50-150		%	1		09/10/16 16:06

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 16:06 Container ID: 1165330006-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 11:40 Prep Initial Wt./Vol.: 116.777 g Prep Extract Vol: 34.0775 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	3.96 U	7.91	2.53	ug/Kg	1		09/10/16 16:06
Ethylbenzene	7.90 U	15.8	4.94	ug/Kg	1		09/10/16 16:06
o-Xylene	7.90 U	15.8	4.94	ug/Kg	1		09/10/16 16:06
P & M -Xylene	15.8 U	31.6	9.49	ug/Kg	1		09/10/16 16:06
Toluene	7.90 U	15.8	4.94	ug/Kg	1		09/10/16 16:06
Surrogates							
1,4-Difluorobenzene (surr)	94.5	72-119		%	1		09/10/16 16:06

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 16:06 Container ID: 1165330006-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 11:40 Prep Initial Wt./Vol.: 116.777 g Prep Extract Vol: 34.0775 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-3B

Client Sample ID: DP-3B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330007 Lab Project ID: 1165330 Collection Date: 09/08/16 11:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):89.1 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	15.2 J	22.4	6.95	mg/Kg	1		09/18/16 04:23
Surrogates							
5a Androstane (surr)	92.2	50-150		%	1		09/18/16 04:23

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:23 Container ID: 1165330007-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.018 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	85.3	22.4	6.95	mg/Kg	1		09/18/16 04:23
Surrogates							
n-Triacontane-d62 (surr)	105	50-150		%	1		09/18/16 04:23

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:23 Container ID: 1165330007-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.018 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-3B

Client Sample ID: DP-3B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330007 Lab Project ID: 1165330 Collection Date: 09/08/16 11:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):89.1 Location:

Results by Volatile Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.678 J	2.14	0.641	mg/Kg	1		09/10/16 16:24
Surrogates							
4-Bromofluorobenzene (surr)	117	50-150		%	1		09/10/16 16:24

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 16:24 Container ID: 1165330007-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 11:35 Prep Initial Wt./Vol.: 91.938 g Prep Extract Vol: 35.0063 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	5.35 U	10.7	3.42	ug/Kg	1		09/10/16 16:24
Ethylbenzene	10.7 U	21.4	6.67	ug/Kg	1		09/10/16 16:24
o-Xylene	10.7 U	21.4	6.67	ug/Kg	1		09/10/16 16:24
P & M -Xylene	21.4 U	42.7	12.8	ug/Kg	1		09/10/16 16:24
Toluene	10.7 U	21.4	6.67	ug/Kg	1		09/10/16 16:24
Surrogates							
1,4-Difluorobenzene (surr)	95.1	72-119		%	1		09/10/16 16:24

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 16:24 Container ID: 1165330007-B Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 11:35
Prep Initial Wt./Vol.: 91.938 g
Prep Extract Vol: 35.0063 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-4A

Client Sample ID: DP-4A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330008 Lab Project ID: 1165330 Collection Date: 09/08/16 12:30 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):93.4 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	16.1 J	21.3	6.59	mg/Kg	1		09/18/16 04:33
Surrogates							
5a Androstane (surr)	90.2	50-150		%	1		09/18/16 04:33

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:33 Container ID: 1165330008-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.222 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	37.7	21.3	6.59	mg/Kg	1		09/18/16 04:33
Surrogates							
n-Triacontane-d62 (surr)	98.4	50-150		%	1		09/18/16 04:33

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:33 Container ID: 1165330008-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.222 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-4A

Client Sample ID: DP-4A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330008 Lab Project ID: 1165330 Collection Date: 09/08/16 12:30 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):93.4 Location:

Results by Volatile Fuels

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.538 J	1.54	0.461	mg/Kg	1		09/10/16 16:43
Surrogates							
4-Bromofluorobenzene (surr)	122	50-150		%	1		09/10/16 16:43

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 16:43 Container ID: 1165330008-B Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 12:30
Prep Initial Wt./Vol.: 113.033 g
Prep Extract Vol: 32.4424 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	3.84 U	7.68	2.46	ug/Kg	1		09/10/16 16:43
Ethylbenzene	7.70 U	15.4	4.79	ug/Kg	1		09/10/16 16:43
o-Xylene	7.70 U	15.4	4.79	ug/Kg	1		09/10/16 16:43
P & M -Xylene	15.4 U	30.7	9.22	ug/Kg	1		09/10/16 16:43
Toluene	7.70 U	15.4	4.79	ug/Kg	1		09/10/16 16:43
Surrogates							
1,4-Difluorobenzene (surr)	96.9	72-119		%	1		09/10/16 16:43

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 16:43 Container ID: 1165330008-B Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 12:30
Prep Initial Wt./Vol.: 113.033 g
Prep Extract Vol: 32.4424 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-4B

Client Sample ID: DP-4B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330009 Lab Project ID: 1165330

Collection Date: 09/08/16 12:45 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):84.3 Location:

Results by Semivolatile Organic Fuels

<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable Limits	Date Analyzed
Diesel Range Organics	10.7 J	23.4	7.26	mg/Kg	1		09/18/16 04:43
Surrogates							
5a Androstane (surr)	87.7	50-150		%	1		09/18/16 04:43

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:43 Container ID: 1165330009-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.394 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	17.3 J	23.4	7.26	mg/Kg	1		09/18/16 04:43
Surrogates							
n-Triacontane-d62 (surr)	88.7	50-150		%	1		09/18/16 04:43

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:43 Container ID: 1165330009-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.394 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM

t 907.562.2343 f 907.561.5301 www.us.sgs.com



Results of DP-4B

Client Sample ID: DP-4B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330009 Lab Project ID: 1165330 Collection Date: 09/08/16 12:45 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):84.3 Location:

Results by Volatile Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.904 J	2.64	0.791	mg/Kg	1		09/10/16 17:02
Surrogates							
4-Bromofluorobenzene (surr)	137	50-150		%	1		09/10/16 17:02

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 17:02 Container ID: 1165330009-B

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 12:45 Prep Initial Wt./Vol.: 87.128 g Prep Extract Vol: 38.7132 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	6.60 U	13.2	4.22	ug/Kg	1		09/10/16 17:02
Ethylbenzene	13.2 U	26.4	8.23	ug/Kg	1		09/10/16 17:02
o-Xylene	13.2 U	26.4	8.23	ug/Kg	1		09/10/16 17:02
P & M -Xylene	26.4 U	52.7	15.8	ug/Kg	1		09/10/16 17:02
Toluene	13.2 U	26.4	8.23	ug/Kg	1		09/10/16 17:02
Surrogates							
1,4-Difluorobenzene (surr)	92.7	72-119		%	1		09/10/16 17:02

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 17:02 Container ID: 1165330009-B Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 12:45 Prep Initial Wt./Vol.: 87.128 g

Prep Extract Vol: 38.7132 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-5A

Client Sample ID: DP-5A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330010 Lab Project ID: 1165330 Collection Date: 09/08/16 13:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):90.3 Location:

Results by Semivolatile Organic Fuels

Parameter Diesel Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	13.2 J	21.9	6.78	mg/Kg	1	Limits	09/18/16 04:54
Surrogates 5a Androstane (surr)	90.4	50-150		%	1		09/18/16 04:54

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 04:54 Container ID: 1165330010-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.363 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	42.1	21.9	6.78	mg/Kg	1		09/18/16 04:54
Surrogates							
n-Triacontane-d62 (surr)	93.9	50-150		%	1		09/18/16 04:54

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 04:54 Container ID: 1165330010-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.363 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Results of DP-5A

Client Sample ID: DP-5A

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330010 Lab Project ID: 1165330 Collection Date: 09/08/16 13:35 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):90.3 Location:

Results by Volatile Fuels

<u>Parameter</u> Gasoline Range Organics	Result Qual 0.680 J	LOQ/CL 2.11	<u>DL</u> 0.634	<u>Units</u> mg/Kg	<u>DF</u> 1	Allowable Limits	<u>Date Analyzed</u> 09/10/16 17:20
Surrogates							
4-Bromofluorobenzene (surr)	127	50-150		%	1		09/10/16 17:20

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 17:20 Container ID: 1165330010-B

Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 13:35
Prep Initial Wt./Vol.: 87.662 g
Prep Extract Vol: 33.4647 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	5.30 U	10.6	3.38	ug/Kg	1		09/10/16 17:20
Ethylbenzene	10.6 U	21.1	6.59	ug/Kg	1		09/10/16 17:20
o-Xylene	10.6 U	21.1	6.59	ug/Kg	1		09/10/16 17:20
P & M -Xylene	21.1 U	42.3	12.7	ug/Kg	1		09/10/16 17:20
Toluene	10.6 U	21.1	6.59	ug/Kg	1		09/10/16 17:20
Surrogates							
1,4-Difluorobenzene (surr)	94.8	72-119		%	1		09/10/16 17:20

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 17:20 Container ID: 1165330010-B

Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 13:35
Prep Initial Wt./Vol.: 87.662 g
Prep Extract Vol: 33.4647 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of DP-5B

Client Sample ID: DP-5B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330011 Lab Project ID: 1165330 Collection Date: 09/08/16 13:40 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):87.7 Location:

Results by Semivolatile Organic Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	9.55 J	22.7	7.03	mg/Kg	1		09/18/16 05:24
Surrogates							
5a Androstane (surr)	90.9	50-150		%	1		09/18/16 05:24

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/18/16 05:24 Container ID: 1165330011-A

Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.149 g Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	42.6	22.7	7.03	mg/Kg	1		09/18/16 05:24
Surrogates							
n-Triacontane-d62 (surr)	110	50-150		%	1		09/18/16 05:24

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/18/16 05:24 Container ID: 1165330011-A Prep Batch: XXX36322 Prep Method: SW3550C Prep Date/Time: 09/16/16 21:12 Prep Initial Wt./Vol.: 30.149 g Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-5B

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330011 Lab Project ID: 1165330 Collection Date: 09/08/16 13:40 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%):87.7 Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	1.08 U	2.16	0.648	mg/Kg	1	Limits	09/10/16 17:39
Surrogates 4-Bromofluorobenzene (surr)	124	50-150		%	1		09/10/16 17:39

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 17:39 Container ID: 1165330011-C

Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 13:40 Prep Initial Wt./Vol.: 97.391 g Prep Extract Vol: 36.9392 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	5.40 U	10.8	3.46	ug/Kg	1		09/10/16 17:39
Ethylbenzene	10.8 U	21.6	6.74	ug/Kg	1		09/10/16 17:39
o-Xylene	10.8 U	21.6	6.74	ug/Kg	1		09/10/16 17:39
P & M -Xylene	21.6 U	43.2	13.0	ug/Kg	1		09/10/16 17:39
Toluene	10.8 U	21.6	6.74	ug/Kg	1		09/10/16 17:39
Surrogates							
1,4-Difluorobenzene (surr)	94	72-119		%	1		09/10/16 17:39

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 17:39 Container ID: 1165330011-C Prep Batch: VXX29534 Prep Method: SW5035A Prep Date/Time: 09/08/16 13:40 Prep Initial Wt./Vol.: 97.391 g

Prep Extract Vol: 36.9392 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Results of Trip Blank

Client Sample ID: Trip Blank

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330012 Lab Project ID: 1165330 Collection Date: 09/08/16 13:40 Received Date: 09/08/16 16:49 Matrix: Soil/Solid (dry weight)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.787 J	2.49	0.747	mg/Kg	1	Limits	09/10/16 14:15
Surrogates 4-Bromofluorobenzene (surr)	101	50-150	•	%	1		09/10/16 14:15

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 14:15 Container ID: 1165330012-A Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 13:40
Prep Initial Wt./Vol.: 50.183 g
Prep Extract Vol: 25 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	6.25 U	12.5	3.99	ug/Kg	1		09/10/16 14:15
Ethylbenzene	12.4 U	24.9	7.77	ug/Kg	1		09/10/16 14:15
o-Xylene	12.4 U	24.9	7.77	ug/Kg	1		09/10/16 14:15
P & M -Xylene	24.9 U	49.8	14.9	ug/Kg	1		09/10/16 14:15
Toluene	12.4 U	24.9	7.77	ug/Kg	1		09/10/16 14:15
Surrogates							
1,4-Difluorobenzene (surr)	96.5	72-119		%	1		09/10/16 14:15

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 14:15 Container ID: 1165330012-A Prep Batch: VXX29534
Prep Method: SW5035A
Prep Date/Time: 09/08/16 13:40
Prep Initial Wt./Vol.: 50.183 g
Prep Extract Vol: 25 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-1

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330013 Lab Project ID: 1165330 Collection Date: 09/08/16 10:10 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

Parameter Diesel Range Organics	Result Qual 0.229 J	LOQ/CL 0.600	<u>DL</u> 0.180	<u>Units</u> mg/L	<u>DF</u> 1	Allowable Limits	Date Analyzed 09/15/16 23:09
Surrogates							
5a Androstane (surr)	79.6	50-150		%	1		09/15/16 23:09

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/15/16 23:09 Container ID: 1165330013-A Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 250 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.250 U	0.500	0.150	mg/L	1		09/15/16 23:09
Surrogates							
n-Triacontane-d62 (surr)	81.7	50-150		%	1		09/15/16 23:09

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/15/16 23:09 Container ID: 1165330013-A Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 250 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-1

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330013 Lab Project ID: 1165330 Collection Date: 09/08/16 10:10 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.0500 U	0.100	0.0310	mg/L	1	Limits	09/11/16 00:27
Surrogates 4-Bromofluorobenzene (surr)	103	50-150		%	1		09/11/16 00:27

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 00:27 Container ID: 1165330013-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 00:27
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:27
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:27
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 00:27
Toluene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:27
Surrogates							
1,4-Difluorobenzene (surr)	92.1	77-115		%	1		09/11/16 00:27

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 00:27 Container ID: 1165330013-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-6

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330014 Lab Project ID: 1165330 Collection Date: 09/08/16 10:15 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

Parameter Diesel Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.212 J	0.577	0.173	mg/L	1	Limits	09/15/16 23:20
Surrogates 5a Androstane (surr)	94.4	50-150		%	1		09/15/16 23:20

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/15/16 23:20 Container ID: 1165330014-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 260 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.240 U	0.481	0.144	mg/L	1		09/15/16 23:20
Surrogates							
n-Triacontane-d62 (surr)	93.7	50-150		%	1		09/15/16 23:20

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/15/16 23:20 Container ID: 1165330014-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 260 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-6

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330014 Lab Project ID: 1165330 Collection Date: 09/08/16 10:15 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	<u>LOQ/CL</u>	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.0500 U	0.100	0.0310	mg/L	1	Limits	09/11/16 00:45
Surrogates 4-Bromofluorobenzene (surr)	105	50-150		%	1		09/11/16 00:45

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 00:45 Container ID: 1165330014-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 00:45
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:45
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:45
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 00:45
Toluene	0.500 U	1.00	0.310	ug/L	1		09/11/16 00:45
Surrogates							
1,4-Difluorobenzene (surr)	90.1	77-115		%	1		09/11/16 00:45

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 00:45 Container ID: 1165330014-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-2

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330015 Lab Project ID: 1165330 Collection Date: 09/08/16 10:55 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

Parameter Diesel Range Organics	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	<u>Date Analyzed</u>
	0.187 J	0.605	0.181	mg/L	1	Limits	09/15/16 23:30
Surrogates 5a Androstane (surr)	82.9	50-150		%	1		09/15/16 23:30

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/15/16 23:30 Container ID: 1165330015-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 248 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.252 U	0.504	0.151	mg/L	1		09/15/16 23:30
Surrogates							
n-Triacontane-d62 (surr)	80.5	50-150		%	1		09/15/16 23:30

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/15/16 23:30 Container ID: 1165330015-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 248 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM J flagging is activated



Client Sample ID: DP-2

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330015 Lab Project ID: 1165330 Collection Date: 09/08/16 10:55 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual 0.0500 U	<u>LOQ/CL</u> 0.100	<u>DL</u> 0.0310	<u>Units</u> mg/L	<u>DF</u> 1	Allowable Limits	<u>Date Analyzed</u> 09/11/16 01:04
Surrogates							
4-Bromofluorobenzene (surr)	108	50-150		%	1		09/11/16 01:04

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 01:04 Container ID: 1165330015-C

Prep Batch: VXX29535
Prep Method: SW5030B
Prep Date/Time: 09/10/16 06:00
Prep Initial Wt./Vol.: 5 mL
Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 01:04
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:04
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:04
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 01:04
Toluene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:04
Surrogates							
1,4-Difluorobenzene (surr)	92	77-115		%	1		09/11/16 01:04

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 01:04 Container ID: 1165330015-C

Prep Batch: VXX29535
Prep Method: SW5030B
Prep Date/Time: 09/10/16 06:00
Prep Initial Wt./Vol.: 5 mL
Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-3

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330016 Lab Project ID: 1165330 Collection Date: 09/08/16 12:10 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Limits	Date Analyzed
Diesel Range Organics	0.240 J	0.636	0.191	mg/L	1		09/15/16 23:40
Surrogates							
5a Androstane (surr)	77.6	50-150		%	1		09/15/16 23:40

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/15/16 23:40 Container ID: 1165330016-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 236 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.265 U	0.530	0.159	mg/L	1		09/15/16 23:40
Surrogates							
n-Triacontane-d62 (surr)	75.8	50-150		%	1		09/15/16 23:40

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/15/16 23:40 Container ID: 1165330016-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 236 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-3

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330016 Lab Project ID: 1165330 Collection Date: 09/08/16 12:10 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable	Date Analyzed
	0.0500 U	0.100	0.0310	mg/L	1	Limits	09/11/16 01:22
Surrogates 4-Bromofluorobenzene (surr)	105	50-150		%	1		09/11/16 01:22

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 01:22 Container ID: 1165330016-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 01:22
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:22
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:22
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 01:22
Toluene	0.510 J	1.00	0.310	ug/L	1		09/11/16 01:22
Surrogates							
1,4-Difluorobenzene (surr)	92.9	77-115		%	1		09/11/16 01:22

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 01:22 Container ID: 1165330016-C

Prep Batch: VXX29535
Prep Method: SW5030B
Prep Date/Time: 09/10/16 06:00
Prep Initial Wt./Vol.: 5 mL
Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-4

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330017 Lab Project ID: 1165330 Collection Date: 09/08/16 13:05 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

D					5-	Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Diesel Range Organics	0.322 J	0.620	0.186	mg/L	1		09/15/16 23:51
Surrogates							
5a Androstane (surr)	87	50-150		%	1		09/15/16 23:51

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/15/16 23:51 Container ID: 1165330017-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 242 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.250 J	0.517	0.155	mg/L	1		09/15/16 23:51
Surrogates							
n-Triacontane-d62 (surr)	87.9	50-150		%	1		09/15/16 23:51

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/15/16 23:51 Container ID: 1165330017-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 242 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-4

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330017 Lab Project ID: 1165330 Collection Date: 09/08/16 13:05 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Gasoline Range Organics	0.0500 U	0.100	0.0310	mg/L	1		09/11/16 01:41
Surrogates							
4-Bromofluorobenzene (surr)	105	50-150		%	1		09/11/16 01:41

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 01:41 Container ID: 1165330017-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 01:41
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:41
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:41
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 01:41
Toluene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:41
Surrogates							
1,4-Difluorobenzene (surr)	93.6	77-115		%	1		09/11/16 01:41

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 01:41 Container ID: 1165330017-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-5

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330018 Lab Project ID: 1165330 Collection Date: 09/08/16 14:00 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Semivolatile Organic Fuels

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Limits	Date Analyzed
Diesel Range Organics	0.300 U	0.600	0.180	mg/L	1		09/16/16 00:00
Surrogates							
5a Androstane (surr)	89.8	50-150		%	1		09/16/16 00:00

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102

Analyst: CRA

Analytical Date/Time: 09/16/16 00:00 Container ID: 1165330018-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 250 mL
Prep Extract Vol: 1 mL

						<u>Allowable</u>	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Residual Range Organics	0.250 U	0.500	0.150	mg/L	1		09/16/16 00:00
Surrogates							
n-Triacontane-d62 (surr)	85.4	50-150		%	1		09/16/16 00:00

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103

Analyst: CRA

Analytical Date/Time: 09/16/16 00:00 Container ID: 1165330018-A

Prep Batch: XXX36299
Prep Method: SW3520C
Prep Date/Time: 09/15/16 08:48
Prep Initial Wt./Vol.: 250 mL
Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:02:36AM



Client Sample ID: DP-5

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330018 Lab Project ID: 1165330 Collection Date: 09/08/16 14:00 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

Parameter Gasoline Range Organics	Result Qual	LOQ/CL 0.100	<u>DL</u> 0.0310	<u>Units</u> mg/L	<u>DF</u> 1	Allowable Limits	Date Analyzed 09/11/16 01:59
Surrogates 4-Bromofluorobenzene (surr)	111	50-150		%	1		09/11/16 01:59

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/11/16 01:59 Container ID: 1165330018-C

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/11/16 01:59
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:59
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:59
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/11/16 01:59
Toluene	0.500 U	1.00	0.310	ug/L	1		09/11/16 01:59
Surrogates							
1,4-Difluorobenzene (surr)	92.2	77-115		%	1		09/11/16 01:59

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/11/16 01:59 Container ID: 1165330018-C

Prep Batch: VXX29535
Prep Method: SW5030B
Prep Date/Time: 09/10/16 06:00
Prep Initial Wt./Vol.: 5 mL
Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Results of Trip Blank

Client Sample ID: Trip Blank

Client Project ID: Image Reflection Drive

Lab Sample ID: 1165330019 Lab Project ID: 1165330 Collection Date: 09/08/16 10:10 Received Date: 09/08/16 16:49 Matrix: Water (Surface, Eff., Ground)

Solids (%): Location:

Results by Volatile Fuels

<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	Allowable Limits	Date Analyzed
Gasoline Range Organics	0.0500 U	0.100	0.0310	mg/L	1		09/10/16 23:31
Surrogates							
4-Bromofluorobenzene (surr)	111	50-150		%	1		09/10/16 23:31

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Analyst: ST

Analytical Date/Time: 09/10/16 23:31 Container ID: 1165330019-A

Prep Batch: VXX29535 Prep Method: SW5030B Prep Date/Time: 09/10/16 06:00 Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

						Allowable	
<u>Parameter</u>	Result Qual	LOQ/CL	<u>DL</u>	<u>Units</u>	<u>DF</u>	<u>Limits</u>	Date Analyzed
Benzene	0.250 U	0.500	0.150	ug/L	1		09/10/16 23:31
Ethylbenzene	0.500 U	1.00	0.310	ug/L	1		09/10/16 23:31
o-Xylene	0.500 U	1.00	0.310	ug/L	1		09/10/16 23:31
P & M -Xylene	1.00 U	2.00	0.620	ug/L	1		09/10/16 23:31
Toluene	0.500 U	1.00	0.310	ug/L	1		09/10/16 23:31
Surrogates							
1,4-Difluorobenzene (surr)	90.4	77-115		%	1		09/10/16 23:31

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B

Analyst: ST

Analytical Date/Time: 09/10/16 23:31 Container ID: 1165330019-A

Prep Batch: VXX29535
Prep Method: SW5030B
Prep Date/Time: 09/10/16 06:00
Prep Initial Wt./Vol.: 5 mL
Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:02:36AM



Blank ID: MB for HBN 1743156 [SPT/9997]

Blank Lab ID: 1352098

QC for Samples:

Matrix: Soil/Solid (dry weight)

1165330010, 1165330011

Results by SM21 2540G

 Parameter
 Results
 LOQ/CL
 DL
 Units

 Total Solids
 100
 %

Batch Information

Analytical Batch: SPT9997 Analytical Method: SM21 2540G

Instrument: Analyst: RJA

Analytical Date/Time: 9/14/2016 5:34:00PM

Print Date: 09/23/2016 8:02:47AM



Duplicate Sample Summary

Original Sample ID: 1165214018 Duplicate Sample ID: 1352100

QC for Samples:

Analysis Date: 09/14/2016 17:34 Matrix: Soil/Solid (dry weight)

Results by SM21 2540G

 NAME
 Original
 Duplicate
 Units
 RPD (%)
 RPD CL

 Total Solids
 94.1
 94.2
 %
 0.17
 (< 15)</td>

Batch Information

Analytical Batch: SPT9997 Analytical Method: SM21 2540G

Instrument: Analyst: RJA

Print Date: 09/23/2016 8:02:48AM



Duplicate Sample Summary

Original Sample ID: 1165292005 Analysis Date: 09/14/2016 17:34

Duplicate Sample ID: 1352101 Matrix: Soil/Solid (dry weight)

QC for Samples:

1165330009, 1165330010, 1165330011

Results by SM21 2540G

NAME	<u>Original</u>	<u>Duplicate</u>	<u>Units</u>	RPD (%)	RPD CL
Total Solids	89.1	89.4	%	0.27	(< 15)

Batch Information

Analytical Batch: SPT9997 Analytical Method: SM21 2540G

Instrument: Analyst: RJA

Print Date: 09/23/2016 8:02:48AM



Duplicate Sample Summary

Original Sample ID: 1165348003 Analysis Date: 09/14/2016 17:34
Duplicate Sample ID: 1352102 Matrix: Soil/Solid (dry weight)

QC for Samples:

1165330009, 1165330010, 1165330011

Results by SM21 2540G

NAME	<u>Original</u>	<u>Duplicate</u>	<u>Units</u>	RPD (%)	RPD CL
Total Solids	92.4	93.2	%	0.85	(< 15)

Batch Information

Analytical Batch: SPT9997 Analytical Method: SM21 2540G

Instrument: Analyst: RJA

Print Date: 09/23/2016 8:02:48AM



Blank ID: MB for HBN 1742949 [VXX/29534]

Blank Lab ID: 1351262

QC for Samples:

1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007, 1165330008, 1165330009,

Matrix: Soil/Solid (dry weight)

1165330010, 1165330011, 1165330012

Results by AK101

ParameterResultsLOQ/CLDLUnitsGasoline Range Organics0.937J2.500.750mg/Kg

Surrogates

4-Bromofluorobenzene (surr) 106 50-150 %

Batch Information

Analytical Batch: VFC13298 Prep Batch: VXX29534
Analytical Method: AK101 Prep Method: SW5035A

Instrument: Agilent 7890A PID/FID Prep Date/Time: 9/10/2016 12:30:00AM

Analyst: ST Prep Initial Wt./Vol.: 50 g Analytical Date/Time: 9/10/2016 1:42:00PM Prep Extract Vol: 25 mL

Print Date: 09/23/2016 8:02:52AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [VXX29534]

Blank Spike Lab ID: 1351265

Date Analyzed: 09/10/2016 13:05

Spike Duplicate ID: LCSD for HBN 1165330

[VXX29534]

Spike Duplicate Lab ID: 1351266

Matrix: Soil/Solid (dry weight)

QC for Samples: 1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007,

1165330008, 1165330009, 1165330010, 1165330011, 1165330012

Results by AK101

	В	lank Spike	(mg/Kg)	S	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Gasoline Range Organics	12.5	12.5	100	12.5	12.7	102	(60-120)	2.10	(< 20)
Surrogates									
4-Bromofluorobenzene (surr)	1.25	107	107	1.25	109	109	(50-150)	1.40	

Batch Information

Analytical Batch: VFC13298
Analytical Method: AK101

Instrument: Agilent 7890A PID/FID

Analyst: ST

Prep Batch: VXX29534
Prep Method: SW5035A

Prep Date/Time: 09/10/2016 00:30

Spike Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 12.5 mg/Kg Extract Vol: 25 mL

Print Date: 09/23/2016 8:02:55AM



Billable Matrix Spike Summary

Original Sample ID: 1165330011 MS Sample ID: 1165330020 BMS MSD Sample ID: 1165330021 BMSD

QC for Samples:

Analysis Date: 09/10/2016 17:39 Analysis Date: 09/10/2016 21:40 Analysis Date: 09/10/2016 21:58 Matrix: Soil/Solid (dry weight)

Results by AK101

		Matr	rix Spike (n	ng/Kg)	Spike	Duplicate	(mg/Kg)		
Parameter Gasoline Range Organics	Sample 1.08U	<u>Spike</u> 10.8	Result 10.7	Rec (%) 100	<u>Spike</u> 10.8	Result 10.6	Rec (%) 98	<u>CL</u> 60-120	RPD (%) RPD CL (< 20)
Surrogates 4-Bromofluorobenzene (surr)		0.732	0.896	122	0.732	0.884	121	50-150	1.40

Batch Information

Analytical Batch: VFC13298 Analytical Method: AK101 Instrument: Agilent 7890A PID/FID

Analyst: ST

Analytical Date/Time: 9/10/2016 9:40:00PM

Prep Batch: VXX29534

Prep Method: AK101 Extraction (S)
Prep Date/Time: 9/8/2016 10:10:00AM

Prep Initial Wt./Vol.: 97.39g Prep Extract Vol: 36.94mL

Print Date: 09/23/2016 8:02:56AM



Blank ID: MB for HBN 1742949 [VXX/29534]

Blank Lab ID: 1351262

QC for Samples:

1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007, 1165330008, 1165330009,

1165330010, 1165330011, 1165330012

Results by SW8021B

Parameter	Results	LOQ/CL	<u>DL</u>	<u>Units</u>
Benzene	6.25U	12.5	4.00	ug/Kg
Ethylbenzene	12.5U	25.0	7.80	ug/Kg
o-Xylene	12.5U	25.0	7.80	ug/Kg
P & M -Xylene	25.0U	50.0	15.0	ug/Kg
Toluene	12.5U	25.0	7.80	ug/Kg
Surrogates				
1,4-Difluorobenzene (surr)	94.7	72-119		%

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B

Instrument: Agilent 7890A PID/FID

Analyst: ST

Analytical Date/Time: 9/10/2016 1:42:00PM

Prep Batch: VXX29534 Prep Method: SW5035A

Prep Date/Time: 9/10/2016 12:30:00AM

Matrix: Soil/Solid (dry weight)

Prep Initial Wt./Vol.: 50 g Prep Extract Vol: 25 mL

Print Date: 09/23/2016 8:02:57AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [VXX29534]

Blank Spike Lab ID: 1351263 Date Analyzed: 09/10/2016 12:28 Spike Duplicate ID: LCSD for HBN 1165330

[VXX29534]

Spike Duplicate Lab ID: 1351264 Matrix: Soil/Solid (dry weight)

QC for Samples: 1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007,

1165330008, 1165330009, 1165330010, 1165330011, 1165330012

Results by SW8021B

	E	Blank Spike	(ug/Kg)	S	pike Duplic	ate (ug/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	1250	1400	112	1250	1370	110	(75-125)	1.80	(< 20)
Ethylbenzene	1250	1310	105	1250	1300	104	(75-125)	0.33	(< 20)
o-Xylene	1250	1280	103	1250	1280	103	(75-125)	0.12	(< 20)
P & M -Xylene	2500	2650	106	2500	2650	106	(80-125)	0.17	(< 20)
Toluene	1250	1320	106	1250	1310	105	(70-125)	1.30	(< 20)
Surrogates									
1,4-Difluorobenzene (surr)	1250	94.7	95	1250	94.1	94	(72-119)	0.64	

Batch Information

Analytical Batch: VFC13298
Analytical Method: SW8021B
Instrument: Agilent 7890A PID/FID

Analyst: ST

Prep Batch: VXX29534
Prep Method: SW5035A

Prep Date/Time: 09/10/2016 00:30

Spike Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL Dupe Init Wt./Vol.: 1250 ug/Kg Extract Vol: 25 mL

Print Date: 09/23/2016 8:03:00AM



Billable Matrix Spike Summary

Original Sample ID: 1165330011 MS Sample ID: 1165330020 BMS MSD Sample ID: 1165330021 BMSD

QC for Samples:

Analysis Date: 09/10/2016 17:39 Analysis Date: 09/10/2016 21:03 Analysis Date: 09/10/2016 21:21 Matrix: Soil/Solid (dry weight)

Results by SW8021B

results by CVVOCID		Matrix Spike (ug/Kg)		Spike Duplicate (ug/Kg)						
<u>Parameter</u>	<u>Sample</u>	Spike	Result	Rec (%)	Spike	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	5.40U	1078	1163	108	1078	1152	107	75-125	1.50	(< 20)
Ethylbenzene	10.8U	1078	1115	104	1078	1099	102	75-125	1.50	(< 20)
o-Xylene	10.8U	1078	1124	104	1078	1109	103	75-125	1.40	(< 20)
P & M -Xylene	21.6U	2155	2269	106	2155	2235	104	80-125	1.50	(< 20)
Toluene	10.8U	1078	1090	101	1078	1074	100	70-125	1.40	(< 20)
Surrogates										
1,4-Difluorobenzene (surr)		1083	1006	93	1083	998	92	72-119	0.86	

Batch Information

Analytical Batch: VFC13298 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: ST

Analytical Date/Time: 9/10/2016 9:03:00PM

Prep Batch: VXX29534

Prep Method: AK101 Extraction (S) Prep Date/Time: 9/8/2016 10:10:00AM

Prep Initial Wt./Vol.: 97.39g Prep Extract Vol: 36.94mL

Print Date: 09/23/2016 8:03:01AM



Blank ID: MB for HBN 1742950 [VXX/29535]

Blank Lab ID: 1351267

QC for Samples:

1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018, 1165330019

Results by AK101

ParameterResultsLOQ/CLDLUnitsGasoline Range Organics0.0500U0.1000.0310mg/L

Matrix: Water (Surface, Eff., Ground)

Surrogates

4-Bromofluorobenzene (surr) 102 50-150 %

Batch Information

Analytical Batch: VFC13286 Prep Batch: VXX29535 Analytical Method: AK101 Prep Method: SW5030B

Instrument: Agilent 7890A PID/FID Prep Date/Time: 9/10/2016 6:00:00AM

Analyst: ST Prep Initial Wt./Vol.: 5 mL Analytical Date/Time: 9/10/2016 11:12:00PM Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:03:02AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [VXX29535]

Blank Spike Lab ID: 1351270

Date Analyzed: 09/10/2016 22:35

Spike Duplicate ID: LCSD for HBN 1165330

[VXX29535]

Spike Duplicate Lab ID: 1351271

Matrix: Water (Surface, Eff., Ground)

QC for Samples: 1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018, 1165330019

Results by AK101

	Blank Spike (mg/L)			S	pike Dupli	cate (mg/L)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	<u>CL</u>	RPD (%)	RPD CL
Gasoline Range Organics	1.00	0.944	94	1.00	0.949	95	(60-120)	0.54	(< 20)
Surrogates									
4-Bromofluorobenzene (surr)	0.0500	109	109	0.0500	110	110	(50-150)	1.30	

Batch Information

Analytical Batch: VFC13286 Analytical Method: AK101

Instrument: Agilent 7890A PID/FID

Analyst: ST

Prep Batch: VXX29535
Prep Method: SW5030B

Prep Date/Time: 09/10/2016 06:00

Spike Init Wt./Vol.: 1.00 mg/L Extract Vol: 5 mL Dupe Init Wt./Vol.: 1.00 mg/L Extract Vol: 5 mL

Print Date: 09/23/2016 8:03:05AM



Blank ID: MB for HBN 1742950 [VXX/29535]

Blank Lab ID: 1351267

QC for Samples:

 $1165330013,\, 1165330014,\, 1165330015,\, 1165330016,\, 1165330017,\, 1165330018,\, 1165330019$

Results by SW8021B

<u>Parameter</u>	Results	LOQ/CL	<u>DL</u>	<u>Units</u>
Benzene	0.250U	0.500	0.150	ug/L
Ethylbenzene	0.500U	1.00	0.310	ug/L
o-Xylene	0.500U	1.00	0.310	ug/L
P & M -Xylene	1.00U	2.00	0.620	ug/L
Toluene	0.500U	1.00	0.310	ug/L
Surrogates				
1,4-Difluorobenzene (surr)	93.5	77-115		%

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: ST

Analytical Date/Time: 9/10/2016 11:12:00PM

Prep Batch: VXX29535 Prep Method: SW5030B

Prep Date/Time: 9/10/2016 6:00:00AM

Matrix: Water (Surface, Eff., Ground)

Prep Initial Wt./Vol.: 5 mL Prep Extract Vol: 5 mL

Print Date: 09/23/2016 8:03:07AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [VXX29535]

Blank Spike Lab ID: 1351268 Date Analyzed: 09/10/2016 22:17 Spike Duplicate ID: LCSD for HBN 1165330

[VXX29535]

Spike Duplicate Lab ID: 1351269 Matrix: Water (Surface, Eff., Ground)

QC for Samples: 1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018, 1165330019

Results by SW8021B

		Blank Spike	e (ug/L)	;	Spike Dupli	cate (ug/L)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Benzene	100	103	103	100	105	105	(80-120)	2.00	(< 20)
Ethylbenzene	100	98.7	99	100	97.5	98	(75-125)	1.20	(< 20)
o-Xylene	100	100	100	100	92.0	92	(80-120)	8.40	(< 20)
P & M -Xylene	200	200	100	200	188	94	(75-130)	6.30	(< 20)
Toluene	100	96.3	96	100	99.8	100	(75-120)	3.60	(< 20)
Surrogates									
1,4-Difluorobenzene (surr)	50	94.2	94	50	95	95	(77-115)	0.78	

Batch Information

Analytical Batch: VFC13286 Analytical Method: SW8021B Instrument: Agilent 7890A PID/FID

Analyst: ST

Prep Batch: VXX29535
Prep Method: SW5030B

Prep Date/Time: 09/10/2016 06:00

Spike Init Wt./Vol.: 100 ug/L Extract Vol: 5 mL Dupe Init Wt./Vol.: 100 ug/L Extract Vol: 5 mL

Print Date: 09/23/2016 8:03:14AM



Blank ID: MB for HBN 1743153 [XXX/36299]

Blank Lab ID: 1352089

QC for Samples:

1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018

Results by AK102

 Parameter
 Results
 LOQ/CL
 DL
 Units

 Diesel Range Organics
 0.300U
 0.600
 0.180
 mg/L

Matrix: Water (Surface, Eff., Ground)

Surrogates

5a Androstane (surr) 94.8 60-120 %

Batch Information

Analytical Batch: XFC12847 Prep Batch: XXX36299
Analytical Method: AK102 Prep Method: SW3520C

Instrument: Agilent 7890B R Prep Date/Time: 9/15/2016 8:48:09AM

Analyst: CRA Prep Initial Wt./Vol.: 250 mL Analytical Date/Time: 9/15/2016 9:16:00PM Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:17AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [XXX36299]

Blank Spike Lab ID: 1352090 Date Analyzed: 09/15/2016 21:27 Spike Duplicate ID: LCSD for HBN 1165330

[XXX36299]

Spike Duplicate Lab ID: 1352091 Matrix: Water (Surface, Eff., Ground)

QC for Samples: 1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018

Results by AK102

	E	Blank Spike	e (mg/L)	9	Spike Dupli	cate (mg/L)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	<u>CL</u>	RPD (%)	RPD CL
Diesel Range Organics	20	18.9	95	20	19.0	95	(75-125)	0.30	(< 20)
Surrogates									
5a Androstane (surr)	0.4	95.5	96	0.4	95.3	95	(60-120)	0.19	

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK102 Instrument: Agilent 7890B R

Analyst: CRA

Prep Batch: XXX36299 Prep Method: SW3520C

Prep Date/Time: 09/15/2016 08:48

Spike Init Wt./Vol.: 20 mg/L Extract Vol: 1 mL Dupe Init Wt./Vol.: 20 mg/L Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:21AM



Blank ID: MB for HBN 1743153 [XXX/36299]

Blank Lab ID: 1352089

QC for Samples:

1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018

Results by AK103

ParameterResultsLOQ/CLDLUnitsResidual Range Organics0.250U0.5000.150mg/L

Matrix: Water (Surface, Eff., Ground)

Surrogates

n-Triacontane-d62 (surr) 93.8 60-120 %

Batch Information

Analytical Batch: XFC12847 Prep Batch: XXX36299
Analytical Method: AK103 Prep Method: SW3520C

Instrument: Agilent 7890B R Prep Date/Time: 9/15/2016 8:48:09AM

Analyst: CRA Prep Initial Wt./Vol.: 250 mL Analytical Date/Time: 9/15/2016 9:16:00PM Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:24AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [XXX36299]

Blank Spike Lab ID: 1352090 Date Analyzed: 09/15/2016 21:27 Spike Duplicate ID: LCSD for HBN 1165330

[XXX36299]

Spike Duplicate Lab ID: 1352091

Matrix: Water (Surface, Eff., Ground)

QC for Samples: 1165330013, 1165330014, 1165330015, 1165330016, 1165330017, 1165330018

Results by AK103

		Blank Spike (mg/L)			Spike Duplic	cate (mg/L)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Residual Range Organics	20	18.5	93	20	18.7	94	(60-120)	1.20	(< 20)
Surrogates									
n-Triacontane-d62 (surr)	0.4	99	99	0.4	104	104	(60-120)	4.50	

Batch Information

Analytical Batch: XFC12847 Analytical Method: AK103 Instrument: Agilent 7890B R

Analyst: CRA

Prep Batch: XXX36299
Prep Method: SW3520C

Prep Date/Time: 09/15/2016 08:48

Spike Init Wt./Vol.: 20 mg/L Extract Vol: 1 mL Dupe Init Wt./Vol.: 20 mg/L Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:26AM



Blank ID: MB for HBN 1743295 [XXX/36322]

Blank Lab ID: 1352676

QC for Samples:

1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007, 1165330008, 1165330009,

Matrix: Soil/Solid (dry weight)

1165330010, 1165330011

Results by AK102

 Parameter
 Results
 LOQ/CL
 DL
 Units

 Diesel Range Organics
 10.0U
 20.0
 6.20
 mg/Kg

Surrogates

5a Androstane (surr) 92.1 60-120 %

Batch Information

Analytical Batch: XFC12844 Prep Batch: XXX36322
Analytical Method: AK102 Prep Method: SW3550C

Instrument: Agilent 7890B R Prep Date/Time: 9/16/2016 9:12:25PM

Analyst: CRA Prep Initial Wt./Vol.: 30 g Analytical Date/Time: 9/19/2016 11:43:00AM Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:29AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [XXX36322]

Blank Spike Lab ID: 1352677

Date Analyzed: 09/18/2016 02:39

Spike Duplicate ID: LCSD for HBN 1165330

[XXX36322]

Spike Duplicate Lab ID: 1352678

Matrix: Soil/Solid (dry weight)

1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007, QC for Samples:

1165330008, 1165330009, 1165330010, 1165330011

Results by AK102

	E	Blank Spike	(mg/Kg)	S	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	Spike	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	CL	RPD (%)	RPD CL
Diesel Range Organics	167	146	88	167	139	83	(75-125)	5.10	(< 20)
Surrogates									
5a Androstane (surr)	3.33	90.5	91	3.33	88.6	89	(60-120)	2.10	

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102 Instrument: Agilent 7890B F

Analyst: CRA

Prep Batch: XXX36322 Prep Method: SW3550C

Prep Date/Time: 09/16/2016 21:12

Spike Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL Dupe Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:32AM



Billable Matrix Spike Summary

Original Sample ID: 1165330011 MS Sample ID: 1165330020 BMS MSD Sample ID: 1165330021 BMSD

QC for Samples:

Analysis Date: 09/18/2016 5:24 Analysis Date: 09/18/2016 5:35 Analysis Date: 09/18/2016 5:45 Matrix: Soil/Solid (dry weight)

Results by AK102

		Matrix Spike (mg/Kg)			Spike Duplicate (mg/Kg)				
<u>Parameter</u> Diesel Range Organics	Sample 9.55J	<u>Spike</u> 188	Result 152	Rec (%) 76	Spike 188	Result 170	Rec (%) 85	<u>CL</u> 60-140	RPD (%) RPD CL (< 50)
Surrogates 5a Androstane (surr)		3.76	3.17	84	3.76	3.60	96	50-150	12.90

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK102 Instrument: Agilent 7890B F

Analyst: CRA

Analytical Date/Time: 9/18/2016 5:35:00AM

Prep Batch: XXX36322

Prep Method: Sonication Extraction Soil AK102 Prep Date/Time: 9/16/2016 9:12:25PM

Prep Initial Wt./Vol.: 30.33g Prep Extract Vol: 1.00mL

Print Date: 09/23/2016 8:03:33AM



Method Blank

Blank ID: MB for HBN 1743295 [XXX/36322]

Blank Lab ID: 1352676

QC for Samples:

1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007, 1165330008, 1165330009,

Matrix: Soil/Solid (dry weight)

1165330010, 1165330011

Results by AK103

ParameterResultsLOQ/CLDLUnitsResidual Range Organics10.0U20.06.20mg/Kg

Surrogates

n-Triacontane-d62 (surr) 93.3 60-120 %

Batch Information

Analytical Batch: XFC12844 Prep Batch: XXX36322
Analytical Method: AK103 Prep Method: SW3550C

Instrument: Agilent 7890B R Prep Date/Time: 9/16/2016 9:12:25PM

Analyst: CRA Prep Initial Wt./Vol.: 30 g Analytical Date/Time: 9/19/2016 11:43:00AM Prep Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:35AM



Blank Spike Summary

Blank Spike ID: LCS for HBN 1165330 [XXX36322]

Blank Spike Lab ID: 1352677

Date Analyzed: 09/18/2016 02:39

Spike Duplicate ID: LCSD for HBN 1165330

[XXX36322]

Spike Duplicate Lab ID: 1352678

Matrix: Soil/Solid (dry weight)

QC for Samples: 1165330001, 1165330002, 1165330003, 1165330004, 1165330005, 1165330006, 1165330007,

1165330008, 1165330009, 1165330010, 1165330011

Results by AK103

	E	Blank Spike	(mg/Kg)	S	pike Duplic	ate (mg/Kg)			
<u>Parameter</u>	<u>Spike</u>	Result	Rec (%)	<u>Spike</u>	Result	Rec (%)	<u>CL</u>	RPD (%)	RPD CL
Residual Range Organics	167	158	95	167	145	87	(60-120)	8.30	(< 20)
Surrogates									
n-Triacontane-d62 (surr)	3.33	93.9	94	3.33	86.2	86	(60-120)	8.50	

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103 Instrument: Agilent 7890B F

Analyst: CRA

Prep Batch: XXX36322
Prep Method: SW3550C

Prep Date/Time: 09/16/2016 21:12

Spike Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL Dupe Init Wt./Vol.: 167 mg/Kg Extract Vol: 1 mL

Print Date: 09/23/2016 8:03:38AM



Billable Matrix Spike Summary

Original Sample ID: 1165330011 MS Sample ID: 1165330020 BMS MSD Sample ID: 1165330021 BMSD

QC for Samples:

Analysis Date: 09/18/2016 5:24 Analysis Date: 09/18/2016 5:35 Analysis Date: 09/18/2016 5:45 Matrix: Soil/Solid (dry weight)

Results by AK103

		Matı	rix Spike (n	ng/Kg)	Spike	Duplicate	(mg/Kg)		
Parameter Residual Range Organics	Sample 42.6	<u>Spike</u> 188	Result 178	Rec (%) 72	Spike 188	Result 209	Rec (%) 88	<u>CL</u> 60-140	RPD (%) RPD CL (< 50)
Surrogates n-Triacontane-d62 (surr)		3.76	3.16	84	3.76	3.88	103	50-150	20.30

Batch Information

Analytical Batch: XFC12843 Analytical Method: AK103 Instrument: Agilent 7890B F

Analyst: CRA

Analytical Date/Time: 9/18/2016 5:35:00AM

Prep Batch: XXX36322

Prep Method: Sonication Extraction Soil AK102 Prep Date/Time: 9/16/2016 9:12:25PM

Prep Initial Wt./Vol.: 30.33g

Prep Extract Vol: 1.00mL

Print Date: 09/23/2016 8:03:39AM

SGS North America Inc. CHAIN OF CUSTODY RECORD



CLIENT: Golder A	Golder Associates				Inst Past	Instructions: S Omissions m	Sections 1 -	1 - 5 mus the onse	structions: Sections 1 - 5 must be filled out. Omissions may delay the onset of analysis.		4. 1 se
CONTACT: Chris Valentine		PHONE #: 807-885-2516	5-2516		Section 3			Preservative	ē		
PROJECT Image R	Image Reflection Drive	Project PWSID/ PERMIT#:			Press:	O RAT	B.H. J.C.	104			\
2		E-MAIL:			2 F						
Chris Valentina (INVOICE TO: Golder Associates		QUOTE #:	336269		- X	2HO 2NAK 103)	Оня	02/AK103 1876X 01/80218)			REMARKS
RESERVED SAMP	SAMPLE IDENTIFICATION	DATE DM/dd/yy	TIME HH:MM	MATRIX		ORON (AK10	Юна	080	<u> </u>	-	roc in
(1) A-6 OP	4	2	0920	ν.	2 Cmb	(<u> </u>	-	╁╍┤ ╅┈	 		
╁	2 2	9/8/14	1020	\\\	1	×			-	-	
2 6 6 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	A 76 %	من ام	1020	N	d	<u>*</u>	\perp	+ - - -	 -		
+	V-7		0/01	3 -	V h	<u> </u>	-	X	-		
37		1/8/4	535	} ~	14	XX		,	+	 -	
	20-36	-r×	1055	}	 		×+	X	+	 	
27 27 6	P-24	7 8/6	1149	5	<u>- ا</u>	×× × ·	+	+	+		
╀	00.32	4/8/14	 - -	\ \	1 km	<u>مارا</u>	Section 4	Ļ.	DOD Project? Yes No	┝	Data Deliverable Requirements:
Relinquished By: (1)	(3)	Date 4 fs 1/	Time	Received By:	k		Cooler ID	غ ∏	· -		336289
Relinquished By: (2)	\	1/2/C		Preceived By:			Request	A Tumarout	d Time and/or	Requested Turnaround Time and/or Special Instructions:	jone:
Ge Reinquished By: (3)	(3)	Date	- Ime	Received By:				Temp Blank °C; 5.9 D	<u>6</u> _0[(Chell of	Custedy Seal
Relinquished By: (4)	(e)	Golf	17me	Received F	Received For Laboratory By:	J. Sala	- §	or Amk trached Sair	or Ambient [] (See attached Sample Receipt Form)		(Sec attached Sample Receipt Form)
 		2, 1011		1063-193 (000)			http://w	JWGD-808-WW	http://www.sgs.com/germs-and-conditions	ous	

[] 200 W. Porter Drive Anchorage, AK 99518 Tel: (907) 582-2343 Fax: (910) 561-5301 [] 5500 Businass Drive Wilmington, NC 26405 Tel: (910) 350-1903 Fax: (910) 350-1557

1083-8lank_CCC_Tempophys_2015-05-19



Ses





PROJECT China Valuadina Principle	CLIENT:	Golder Associates				L.	Instr	Instructions:	is: Se	Sections 1 -	1 - 51	5 must be filled out.	Filled	out.		.
Potestion Drive Potestion Potestion Potestion Potestican Potestion	_	nris Valentine	-	07-865-2516		Seci	E con				Presc	vative		<u> </u>]	₹
Comparison Com		nage Reflection Drive	Project ^o PWSIDA PERMITP:	·		• 00	Pres: Type:	1 1/10/24		/ /	N					
Clates	1 42		E-MAIL:			z	Corp			L	ı		<u> </u>	_		
Clates P.O. #: 1 1 1 1 1 1 1 1 1	_	rls Valentine				⊢ -	Ŝ			Λ.						
Clates P.O. #: NATRING National Na	1		QUOTE#:	336	692	٠ -	2	tec	(e	1 (60						
EIDENTIFICATION DATE TIME MATRIX F month of the part o	2	ler Associates	P.O. #:			z	-Hudili-	HNV			ХЗ					
-4A		SAMPLEIDENTIFICATI	<u> </u>		MATRIX MATRIX CODE	மைமை	(lanen	(AK102)			T8/0R2					REMARKS/ LOC ID
-4A -4B	1	012-23	13/6	1	├	لہ	245			×	×					
- 473 - 11 - 1205 - 5A - 11 - 1305 - 5A - 11 - 1305 - 5 - 5 - 7 - 7 - 84 - 11 - 1305 - 5 - 7 - 7 - 140 - 5 - 7 - 140 - 5 - 140 - 7 - 140 - 7 - 140 - 120 - 1	L	DP-4A	-	ı	~	d		٧	y y	-						
1305		5h-40	ĭ	1245	,5	ل م	_	×	\ \							
1		D P - 4	5	1305	3	₩				×	×					
1		DP-5A	=	1325	v	ч		×	×					-		
1 1 1 2 2 2 2 2 2 2		DP-58	=	0.40	\vdash	M		×	×			l			پ	150
		DP-5	e)	0077	>	۲	٠٩٠			×	\prec				_	
Date Time Received By: Time Received For Laporatory By: Or Ambient [] Order For Laporatory By: Or Ambient [] Order Form)	I	l	-	١	\$	-			X	•						
Date Time Received By: Date Time Received By: Date Time Received By: Date Time Received By: Date Time Received For Laboratory By: On Ambient [] (See attached Sample Receipt Form)	I I		ā	ı	}	٠					X					
Date Time Received By: Date Time Received By: Date Time Received By: Date Time Received By: Date Time Received For Laboratory By: Oate Time Received For Laboratory By: Oate Time Received For Laboratory By: Oate Time Received For Laboratory By: Or Ambient [] (See attached Sample Receipt Form)																
Date Time Received By: Date Time Received By: Date Time Received By: Date Time Received By: Temp Blank °C: S, 9 // (C) // (C	1 70	By: (1)	Date	Time	Received By	ا خ			٥,	section 4	├ -,	Project?	Yes No	Data	Deliverabl	e Requirements:
Date Time Received By: Date Time Received By: Date Time Received By: Temp Blank °C: \$\int 9 \int 1 \int 6 \int 4 \int 6 \int	1/	\ <i>\</i>	9/8//		1/	\				Cooler ID:					336	1269
Date Time Received By: Date Time Received For Laboratory By: Or Ambient [] Orly	-	By: (2)	Oate	Time	Received B	S.			ă	equested .	Unidaro	and Time	and/or Sp	eclal Instr	uctions:	
Date Time Received For Laporatory By: Or Ambient [] (See attached Sample Receipt Form)	lπ	By: (3)	Date	Time	Received By	¥.			┌							
Party Time Received For Laboratory By: or Ambient [1] Party		`	\-							imp Blank	ੋ <u>ੀ</u> ਨੂੰ	5.9 00	,,	**************************************	n of Custo	dy Seat: (Circle)
(See attached Sample Receipt Form)	77	By: (4)	O TO I	Time	Roceived FC	or Labor	atory By				PA PA	bient []		<u>x</u>	<u> </u>	
		/	70/		all	10	1	\		(See attac	hed San	uple Rece	ipt Form)		ached Sar	nple Receipt Form

http://www.sqs.com/terms-and-conditions

| 1 200 W. Potter Orive Anchorage, AK 98518 Tel: (907) 562-2343 Fax: (907) 561-5301 | 1 5500 Business Drive Wilmington, NC 28405 Tel: (910) 350-1903 Fax: (910) 350-1557

•

5083-Bunk COC, Tempui 62-201-743-19

Pennick, Victoria (Anchorage)

From: Valentine, Christopher [Christopher_Valentine@golder.com]

Sent: Friday, September 09, 2016 2:14 PM

To: Pennick, Victoria (Anchorage)

Subject: RE: 1165330 - Image Reflection Drive

Hi Tori,

The jar is correct, it's DP-3C.

Thanks,

Chris

Christopher Valentine, PE | Project Engineer | Golder Associates Inc.

2121 Abbott Road, Suite 100, Anchorage, Alaska, USA 99507

T: +1 (907) 344-6001 | D: +1 (907) 865-2516 | F: +1 (907) 344-6011 | C: +1 (907) 223 4776 | E: <u>CValentine@golder.com</u> | www.golder.com

Work Safe, Home Safe

This email transmission is confidential and may contain proprietary information for the exclusive use of the intended recipient. Any use, distribution or copying of this transmission, other than by the intended recipient, is strictly prohibited. If you are not the intended recipient, please notify the sender and delete all copies. Electronic media is susceptible to unauthorized modification, deterioration, and incompatibility. Accordingly, the electronic media version of any work product may not be relied upon.

Golder, Golder Associates and the GA globe design are trademarks of Golder Associates Corporation.

Please consider the environment before printing this email.

From: Pennick, Victoria (Anchorage) [mailto:Victoria.Pennick@sgs.com]

Sent: Friday, September 09, 2016 2:05 PM

To: Valentine, Christopher < Christopher valentine@golder.com>

Subject: 1165330 - Image Reflection Drive

Hi Chris,

One sample had a bit of a discrepancy on between the jar and COC.

DP-3A on the COC actually had DP-3C on the jars. We logged it per the COC... but I'd like to confirm the correct ID.

COC is attached. They logged the soils first, then the waters (easier on the login process not to be bouncing back and forth between tests or matrices), so the numbering is out of order.

Let me know if you have any questions?

Kindest regards,

Tori



	1	1165330		1 6 5 3 3 0	
Review Criteria	Y/N (yes/	no)	Exceptions Noted	d below	
		exemp	tion permitted if sampler h		
Were Custody Seals intact? Note # 8	k location Y		1F-1S		
COC accompanied	samples? Y				
**exemption perm	itted if chilled &	collected <8hrs ago or o	chlling not required (i.e., w	aste, oil)	
<u> </u>	Υ	Cooler ID: 1	@ 5.9	°C Therm ID:	D11
	Υ	Cooler ID:	@	°C Therm ID:	
Temperature blank compliant* (i.e., 0-6 °C a	after CF)? Y	Cooler ID:	@	°C Therm ID:	
	Υ	Cooler ID:	@	°C Therm ID:	
	Υ	Cooler ID:	@	°C Therm ID:	
*If >6°C, were samples collected <8 hor	urs ago? Y				
If <0°C, were sample containers	ice free? Y				
If samples received without a temperature blank, the "cooler temperature blank, the "cooler temperature blank & "COOLER TEMP" with noted to the right. In cases where neither a temp blank nor cooler temp blank nor cooler temp blank nor cooler temp blank note "ambient" or "chilled".	ill be				
Note: Identify containers received at non-compliant temperature. Us FS-0029 if more space is needed.	e form				
Were samples received within h	old time? Y	Note: Refer to form F-0	83 "Sample Guide" for hol	<u>d times.</u>	
Do samples match COC** (i.e.,sample IDs,dates/times co	ollected)? N				
**Note: If times differ <1hr, record details & login	per COC.	Sample 6, DP-3A on CO	C and DP-3C on Jar Logged	per COC	
Were analyses requested unam	biguous? Y				
		***Exe	mption permitted for met	als (e.g,200.8/6020A).	
Were proper containers (type/mass/volume/preservative*	**)used? Y				
IF APPLICABLE	<u> I</u>	[
Were Trip Blanks (i.e., VOAs, LL-Hg) in cooler with	samples? Y				
Were all VOA vials free of headspace (i.e., bubbles	≤ 6mm)? Y				
Were all soil VOAs field extracted with Me	OH+BFB? Y				
Note to Client: Any "no" answer above indicate	s non-complianc	e with standard procedu	ures and may impact data	quality.	
Addit	tional notes (if applicable):			



Sample Containers and Preservatives

Container Id	<u>Preservative</u>	Container Condition	Container Id	<u>Preservative</u>	Container Condition
1165330001-A	No Preservative Required	ОК	1165330016-D	HCL to pH < 2	ОК
1165330001-B	Methanol field pres. 4 C	ОК	1165330016-E	HCL to pH < 2	OK
1165330002-A	No Preservative Required	ОК	1165330017-A	HCL to pH < 2	OK
1165330002-B	Methanol field pres. 4 C	ОК	1165330017-B	HCL to pH < 2	OK
1165330003-A	No Preservative Required	ОК	1165330017-C	HCL to pH < 2	OK
1165330003-B	Methanol field pres. 4 C	ОК	1165330017-D	HCL to pH < 2	OK
1165330004-A	No Preservative Required	ОК	1165330017-E	HCL to pH < 2	OK
1165330004-B	Methanol field pres. 4 C	ОК	1165330018-A	HCL to pH < 2	ОК
1165330005-A	No Preservative Required	ОК	1165330018-B	HCL to pH < 2	ОК
1165330005-B	Methanol field pres. 4 C	ОК	1165330018-C	HCL to pH < 2	ОК
1165330006-A	No Preservative Required	ОК	1165330018-D	HCL to pH < 2	ОК
1165330006-B	Methanol field pres. 4 C	ОК	1165330018-E	HCL to pH < 2	OK
1165330007-A	No Preservative Required	ОК	1165330019-A	HCL to pH < 2	OK
1165330007-B	Methanol field pres. 4 C	ОК	1165330019-B	HCL to pH < 2	ОК
1165330008-A	No Preservative Required	ОК	1165330019-C	HCL to pH < 2	ОК
1165330008-B	Methanol field pres. 4 C	ОК	1165330020-A	No Preservative Required	OK
1165330009-A	No Preservative Required	ОК	1165330020-B	No Preservative Required	OK
1165330009-B	Methanol field pres. 4 C	ОК	1165330020-C	Methanol field pres. 4 C	OK
1165330010-A	No Preservative Required	ОК	1165330021-A	No Preservative Required	OK
1165330010-В	Methanol field pres. 4 C	ОК	1165330021-B	No Preservative Required	OK
1165330011-A	No Preservative Required	ОК	1165330021-C	Methanol field pres. 4 C	OK
1165330011-B	No Preservative Required	ОК			
1165330011-C	Methanol field pres. 4 C	ОК			
1165330012-A	Methanol field pres. 4 C	ОК			
1165330013-A	HCL to pH < 2	OK			
1165330013-B	HCL to pH < 2	ОК			
1165330013-C	HCL to pH < 2	ОК			
1165330013-D	HCL to pH < 2	ОК			
1165330013-E	HCL to pH < 2	OK			
1165330014-A	HCL to pH < 2	ОК			
1165330014-B	HCL to pH < 2	ОК			
1165330014-C	HCL to pH < 2	ОК			
1165330014-D	HCL to pH < 2	OK			
1165330014-E	HCL to pH < 2	OK			
1165330015-A	HCL to pH < 2	OK			
1165330015-B	HCL to pH < 2	OK			
1165330015-C	HCL to pH < 2	ОК			
1165330015-D	HCL to pH < 2	ОК			
1165330015-E	HCL to pH < 2	ОК			
1165330016-A	HCL to pH < 2	OK			
1165330016-B	HCL to pH < 2	ОК			
1165330016-C	HCL to pH < 2	ОК			

9/8/2016 71 of 72

 Container Id
 Preservative
 Container
 Container Id
 Preservative
 Container

 Condition
 Condition
 Condition

Container Condition Glossary

Containers for bacteriological, low level mercury and VOA vials are not opened prior to analysis and will be assigned condition code OK unless evidence indicates than an inappropriate container was submitted.

- OK The container was received at an acceptable pH for the analysis requested.
- BU The container was received with headspace greater than 6mm.
- DM- The container was received damaged.
- FR- The container was received frozen and not usable for Bacteria or BOD analyses.
- PA The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt and the container is now at the correct pH. See the Sample Receipt Form for details on the amount and lot # of the preservative added.
- PH The container was received outside of the acceptable pH for the analysis requested. Preservative was added upon receipt, but was insufficient to bring the container to the correct pH for the analysis requested. See the Sample Receipt Form for details on the amount and lot # of the preservative added.

9/8/2016 72 of 72

Data Path : Z:\09\SF\DATA\091716\

Data File : 17088.D Signal(s) : FID1A.ch

Acq On : 18 Sep 2016 3:41 am

Operator : NRO

Sample : 1165330003

Misc :

ALS Vial : 111 Sample Multiplier: 1

Integration File: autoint1.e
Quant Time: Sep 18 15:41:26 2016


Quant Method: Z:\09\SF\Method\SFF2016-083116E.M

Quant Title : DRO/RRO by Method AK 102/103 QLast Update : Thu Sep 01 17:51:04 2016

Response via : Initial Calibration

Integrator: ChemStation

Volume Inj. : Signal Phase : Signal Info :



Data Path : Z:\09\SF\DATA\091716\

Data File : 17090.D Signal(s) : FID1A.ch

Acq On : 18 Sep 2016 3:51 am

Operator : NRO

Sample : 1166533004

Misc

ALS Vial : 112 Sample Multiplier: 1

Integration File: autoint1.e
Quant Time: Sep 18 15:42:45 2016


Quant Method: Z:\09\SF\Method\SFF2016-083116E.M

Quant Title : DRO/RRO by Method AK 102/103 QLast Update : Thu Sep 01 17:51:04 2016

Response via: Initial Calibration

Integrator: ChemStation

Volume Inj. : Signal Phase : Signal Info :



Established in 1960, Golder Associates is a global, employee-owned organization that helps clients find sustainable solutions to the challenges of finite resources, energy and water supply and management, waste management, urbanization, and climate change. We provide a wide range of independent consulting, design, and construction services in our specialist areas of earth, environment, and energy. By building strong relationships and meeting the needs of clients, our people have created one of the most trusted professional services organizations in the world.

Africa + 27 11 254 4800
Asia + 852 2562 3658
Australasia + 61 3 8862 3500
Europe + 356 21 42 30 20
North America + 1 800 275 3281
South America + 56 2 2616 2000

solutions@golder.com www.golder.com

Golder Associates Inc. 2121 Abbott Road, Suite 100 Anchorage, AK 99507 USA

Tel: (907) 344-6001 Fax: (907) 344-6011



Lift Station Analysis and Drawings

Appendix N

Image Reflection Drainage Improvements - Lift Station Wet Well Design - Detentior Lift Station Cycle Time Calculations

Design Flow (10 Year):	5973.96	GPM	
Design Flow (5 Year)	3756.73	GPM	
Wet Well Diameter:	22.56758334		20x20 equivalent diameter
Height Pump 1 On:	3.5		
Wet Well Volume	1400.0	CF =	10472 Gal
Height Pump 2 On:	5		
Wet Well + Storage	2000.0	CF =	14960 Gal
Heigth Pump 3 On:	5.5		
High Volume Alarm (Max Storage)	2200.0	CF =	16456 Gal
Depth Pump Off to Alarm	6		
Max Capacity	2400.0	CF =	17952 Gal
Pump 1 Output	2000	GPM	
Pump 2 Output	2000	GPM	
Pump 3 Output	2000	GPM	Pump 3 on at 5 year? NO

Lift Station 5 year Storm Event				
		Min Cycle Time	10.00	Min
Design Flow 5-year (gpm)	3756.73	Max Cycle Time	197.50	Min
Flow In From Cell (gpm)	3756.729	Avg Starts Per Hr.	2.875	
Flow Out Through Pump (gpm)	4000			
Maximum Water Voume in LS	16087.05	Starts in Less than 10 Mir	0.00	
Maximum Volume Allowed	17952			

Lift Station 10 year Storm Event				
		Min Cycle Time	176.00	Min
Design Flow 10 year (gpm)	5973.961	Max Cycle Time	197.50	Min
Flow In From Cell (gpm)	5973.961	Avg Starts Per Hr.	1.666667	
Flow Out Through Pump (gpm)	6000	Starts in Less than 5 Min	0.00	Alt Pumps
Maximum Water Voume in LS	16087.05	Starts in Less than 10 Min	2.00	1
Maximum Volume Allowed	17952	•		1



www.cranepumps.com

Series 10SHD

28 Frame Driver 4" Spherical Solids Handling

Solids Handling Submersible Pumps

Specifications:

DISCHARGE10", 125 lb. Horizontal Flange

Slotted to accommodate 200mm ISO Flanges

LIQUID TEMPERATURE 104°F (40°C) Continuous

VOLUTE Cast Iron ASTM A-48, Class 30

WEAR RING...... C954 Lead-Free Bronze

MOTOR HOUSING Cast Iron ASTM A-48. Class 30

MOTOR HOUSING Cast Iron ASTM A-48, Class 30 SEAL PLATE Ductile Iron ASTM A-536, 65-45-12 IMPELLER:

Vanes on Back Side. Dynamically Balanced ISO G6.3

Material Ductile Iron ASTM A-536, 65-45-12

Design Enclosed Dual Vane, With Pump Out

SHAFT416 Stainless Steel

"O" RINGS......Buna-N

PAINTAxalta™ Corlar® Epoxy, Two Coats
SEAL: DesignTandem Mechanical, Oil Filled Reservoir.

Material: Inboard..... Rotating Faces - Carbon Stationary Faces - Ceramic

Material: Outboard ... Rotating Faces - Silicon Carbide

Stationary Faces - Silicon Carbide

Elastomer - Buna-N Hardware - 300 Series Stainless

CORD ENTRY......50 ft. (12.1m) Cord. Rigid quick change epoxy-potted

housing

POWER CORD CSA Certified Submersible Power

Cable 2000V - Ordered Separately

SPEED 1150 or 870 RPM

UPPER BEARING:

DesignSingle Row, Ball, Oil Lubricated

LoadRadial

LOWER BEARING:

Design Double Row, Ball, Oil Lubricated

Load.....Radial & Thrust

MOTOR: DesignNEMA B Three Phase Torque Curve.

Oil-Filled, Squirrel Cage Induction, Inverter Duty

rated per NEMA MG1

Insulation Class H Varnish & Magnet Wire

THREE PHASE Requires overload protection to be included in

control panel.

MOISTURE SENSOR Normally Open (N/O), Requires

Relay in Control Panel

TEMPERATURE SENSOR Three Normally Closed (N/C).

To be wired in series with control circuit.


OPTIONAL EQUIPMENT...... Seal Material, Impeller Trims, Cord Length, Leg Kit

ARKINGS CSA

RECOMMENDED:

Accessories Break Away Fitting (BAF)

Check Valve Control Panel



Series: 10SHD 25 - 100HP, 1150RPM, 60Hz 10 - 30HP, 870RPM, 60Hz





Canadian Standards Association File No. LR16567

Sample Specifications: Section 0.1J Page F.

DESCRIPTION:

SUBMERSIBLE NON-CLOG SEWAGE PUMP DESIGNED FOR RAW SEWAGE APPLICATIONS.



A Crane Co. Company

PUMPS & SYSTEMS

SECTION 0.1J PAGE 1 DATE 3/17

USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598


Series 10SHD

32 Frame Driver
4" Spherical Solids Handling



www.cranepumps.com

Solids Handling Submersible Pumps



Series: 10SHD 50 - 100HP, 1150RPM, 60Hz 40 - 50HP, 870RPM, 60Hz





Sample Specifications: Section 0.1J Page F.

DESCRIPTION:

SUBMERSIBLE NON-CLOG SEWAGE PUMP DESIGNED FOR RAW SEWAGE APPLICATIONS.

Specifications:

DISCHARGE10", 125 lb. Horizontal Flange Slotted to accommodate 200mm ISO Flanges LIQUID TEMPERATURE 104°F (40°C) Continuous VOLUTE Cast Iron ASTM A-48, Class 30 WEAR RING......C954 Lead-Free Bronze MOTOR HOUSING Cast Iron ASTM A-48, Class 30 **SEAL PLATE** Ductile Iron ASTM A-536, 65-45-12 IMPELLER: Design Enclosed Dual Vane, With Pump Out Vanes on Back Side. Dynamically Balanced ISO G6.3 Material Ductile Iron ASTM A-536, 65-45-12 SHAFT416 Stainless Steel "O" RINGS...... Buna-N HARDWARE 300 Series Stainless Steel LIFTING BAIL 300 Series Stainless Steel PAINTAxalta™ Corlar® Epoxy, Two Coats SEAL: DesignTandem Mechanical, Oil Filled Reservoir. Material: Inboard..... Rotating Faces - Carbon Stationary Faces - Ceramic Material: Outboard... Rotating Faces - Silicon Carbide Stationary Faces - Silicon Carbide Elastomer - Buna-N Hardware - 300 Series Stainless CORD ENTRY......50 ft. (12.1m) Cord. Rigid quick change epoxy-potted housing POWER CORDCSA Certified Submersible Power Cable 2000V - Ordered Separately **SPEED**1150 or 870 RPM UPPER BEARING: DesignSingle Row, Ball, Oil Lubricated LoadRadial LOWER BEARING: Design Double Row, Ball, Oil Lubricated Load......Radial & Thrust MOTOR: DesignNEMA B Three Phase Torque Curve. Oil-Filled, Squirrel Cage Induction, Inverter Duty rated per NEMA MG1 Insulation Class H Varnish & Magnet Wire THREE PHASE Requires overload protection to be included in control panel. MOISTURE SENSOR Normally Open (N/O), Requires Relay in Control Panel TEMPERATURE SENSOR Three Normally Closed (N/C). To be wired in series with control circuit. OPTIONAL EQUIPMENT...... Seal Material, Impeller Trims, Cord Length, Leg Kit MARKINGS......CSA

RECOMMENDED:

Accessories Break Away Fitting (BAF)

WEIGHT 1876 lbs (851 Kg) **SUBMERGENCE** Max Depth 66ft (20m)

Check Valve Control Panel

SECTION 0.1J PAGE 2 DATE 3/17






BARNES[®]


www.cranepumps.com

Series 10SHDW

4" Spherical Solids Handling

Solids Handling Submersible Pumps





IMPORTANT!

- 1.) MOISTURE AND TEMPERATURE SENSORS MUST BE CONNECTED TO VALIDATE THE CSA LISTING.
- 2.) A SPECIAL MOISTURE SENSOR RELAY IS REQUIRED IN THE CONTROL PANEL FOR PROPER OPERATION OF THE MOISTURE SENSORS. CONTACT BARNES PUMPS FOR INFORMATION CONCERNING MOISTURE SENSING RELAYS FOR CUSTOMER SUPPLIED CONTROL PANELS.
- 3.) THESE PUMPS ARE CSA LISTED FOR PUMPING WATER AND WASTEWATER. DO NOT USE TO PUMP FLAMMABLE LIQUIDS.
- 4.) INSTALLATIONS SUCH AS DECORATIVE FOUNTAINS OR WATER FEATURES PROVIDED FOR VISUAL ENJOYMENT MUST BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE ANSI/NFPA 70 AND/OR THE AUTHORITY HAVING JURISDICTION. THIS PUMP IS NOT INTENDED FOR USE IN SWIMMING POOLS, RECREATIONAL WATER PARKS, OR INSTALLATIONS IN WHICH HUMAN CONTACT WITH PUMPED MEDIA IS A COMMON OCCURRENCE.
- 5.) THIS PUMP IS NOT APPROPRIATE FOR THOSE APPLICATIONS SPECIFIED AS CLASS 1 DIVISION 1 HAZARDOUS LOCATIONS.



PUMPS & SYSTEMS

SECTION 0.1J PAGE 3 DATE 5/17


Series 10SHDX


4" Spherical Solids Handling



www.cranepumps.com

Solids Handling Submersible Pumps





IMPORTANT!

- 1.) MOISTURE AND TEMPERATURE SENSORS MUST BE CONNECTED TO VALIDATE THE CSA LISTING.
- 2.) A SPECIAL MOISTURE SENSOR RELAY IS REQUIRED IN THE CONTROL PANEL FOR PROPER OPERATION OF THE MOISTURE SENSORS. CONTACT BARNES PUMPS FOR INFORMATION CONCERNING MOISTURE SENSING RELAYS FOR CUSTOMER SUPPLIED CONTROL PANELS.
- 3.) THESE PUMPS ARE CSA LISTED FOR PUMPING WATER AND WASTEWATER. DO NOT USE TO PUMP FLAMMABLE LIQUIDS.
- 4.) INSTALLATIONS SUCH AS DECORATIVE FOUNTAINS OR WATER FEATURES PROVIDED FOR VISUAL ENJOYMENT MUST BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE ANSI/NFPA 70 AND/OR THE AUTHORITY HAVING JURISDICTION. THIS PUMP IS NOT INTENDED FOR USE IN SWIMMING POOLS, RECREATIONAL WATER PARKS, OR INSTALLATIONS IN WHICH HUMAN CONTACT WITH PUMPED MEDIA IS A COMMON OCCURRENCE.
- 5.) THIS PUMP IS NOT APPROPRIATE FOR THOSE APPLICATIONS SPECIFIED AS CLASS 1 DIVISION 1 HAZARDOUS LOCATIONS.

SECTION 0.1J PAGE 4 DATE 5/17



D

P

Ш

www.cranepumps.com

Spherical Solids Handling

Solids

Handling

Submersible

Pumps

SERVICE LOCKED **NEMA FULL** MODEL SERVICE **DRIVER** CORD **PART RPM CORD FACTOR** HP VOLT PH Hz **START** LOAD **ROTOR** NO NO (Nom) **FACTOR FRAME** P/N A SIZE CODE **AMPS AMPS AMPS** 75.2 1.2 90.8 208 3 60 10SHDW25096 139428 25.0 1150 G 354.0 28 138319 2/4 - 18/4 230 70.8 1.2 82.6 10SHDW25046 25.0 35.4 1.2 41.3 139429 460 3 60 1150 G 177.0 28 138317 8/4 - 18/4 G 10SHDW25056 139430 25.0 575 3 60 1150 28.3 1.2 33.0 141.6 28 138317 8/4 - 18/4 90.8 1.2 114.9 208 10SHDW30096 139431 30.0 3 60 Ε 354.0 28 138319 2/4 - 18/4 1150 230 82.6 99.7 1.2 10SHDW30046 139432 30.0 460 3 60 1150 Ε 41.3 1.2 49.9 177.0 28 138317 8/4 - 18/4 575 Е 33.0 28 10SHDW30056 139433 30.0 3 60 1150 1.2 39.9 141.6 138317 8/4 - 18/4 10SHDW40036 139434 40.0 230 3 60 1150 Ε 110.4 1.2 131.8 476.0 28 138319 2/4 - 18/4 60 Ε 238.0 28 10SHDW40046 139435 40.0 460 3 1150 55.2 1.2 65.9 138318 6/4 - 18/4 10SHDW40056 139436 40.0 575 3 60 1150 Ε 44.2 1.2 52.7 190.4 28 138317 8/4 - 18/4 10SHDW50046 139437 50.0 460 3 60 1150 Н 76.4 1.15 84.0 400.0 32 138318 6/4 - 18/4 10SHDW50056 139438 575 3 60 Н 1.15 67.2 320.0 32 138318 6/4 - 18/4 50.0 1150 61.2 F 32 460 3 60 1.15 96.8 138319 2/4 - 18/4 10SHDW60046 139639 60.0 1150 86.7 400.0 Pump 10SHDW60056 139640 60.0 575 3 60 1150 F 69.4 1.15 77.4 320.0 32 138318 6/4 - 18/4 SHDW 208 37.2 42.0 10SHDW10098 139439 10.0 3 60 870 L 230.0 28 138317 1.2 8/4 - 18/4 230 38.6 42.2 21.1 10SHDW10048 139440 10.0 460 3 60 870 L 19.3 1.2 115.0 28 138317 8/4 - 18/4 10SHDW10058 139441 10.0 575 3 60 870 L 15.4 1.2 16.9 92.0 28 138317 8/4 - 18/4 208 50.4 59.0 139442 15.0 3 60 870 G 1.2 230.0 28 138317 8/4 - 18/4 10SHDW15098 230 48.4 55.6 15.0 460 3 60 G 24.2 27.8 28 138317 8/4 - 18/4 10SHDW15048 139443 870 1.2 115.0 G 139444 15.0 575 3 60 19.4 1.2 22.2 92.0 28 8/4 - 18/4 10SHDW15058 870 138317 208 69.0 76.0 139445 10SHDW20098 20.0 3 60 870 J 1.2 400.0 28 138318 6/4 - 18/4 230 79.0 75.1 10SHDW20048 139446 20.0 460 60 870 37.6 1.2 41.1 200.0 28 138317 8/4 - 18/4 3 J 20.0 575 3 60 30.1 1.2 32.9 160.0 28 138317 8/4 - 18/4 10SHDW20058 139447 870 J 208 82.3 98.8 3 60 10SHDW25098 139448 25.0 870 Н 1.2 400.0 28 138319 2/4 - 18/4 230 84.0 94.5 10SHDW25048 139449 25.0 460 3 60 870 Н 42.0 1.2 47.2 200.0 28 138317 8/4 - 18/4 25.0 8/4 - 18/4 10SHDW25058 139450 575 3 60 870 Н 33.6 1.2 37.8 160.0 28 138317 **IMPORTANT!**

Moisture and Temperature sensor leads are integral to power cord. Pump rated for operation at ± 10% voltage at motor.

- ▲ Cord Suffix: XC 30 Feet, XF 50 Feet, XJ 75 Feet, or XL 100 Feet.
- ▲ Cord sold separately.

SECTION PAGE DATE 0.1J 5 2/16

International: (937) 615-3598

SECTION PAGE DATE

0.1J 6 2/16

CRAN

Ш

A Crane Co. Company

4" Spherical Solids Handling

Solids Handling

Submersible Pumps

	MODEL NO	PART NO	НР	VOLT	РН	Hz	RPM (Nom)	NEMA START CODE	FULL LOAD AMPS	SERVICE FACTOR	SERVICE FACTOR AMPS	LOCKED ROTOR AMPS	DRIVER FRAME	CORD P/N A	CORD SIZE
	10SHDX40036	139423	40.0	230	3	60	1150	Е	110.4	1.2	131.8	476.0	28	138319	2/4 - 18/4
	10SHDX40046	139493	40.0	460	3	60	1150	Е	55.2	1.2	65.9	238.0	28	138318	6/4 - 18/4
	10SHDX40056	140056	40.0	575	3	60	1150	Е	44.2	1.2	52.7	190.4	28	138317	8/4 - 18/4
	10SHDX50046	139618	50.0	460	3	60	1150	Н	76.4	1.15	84.0	400.0	32	138318	6/4 - 18/4
	10SHDX50056	139619	50.0	575	3	60	1150	Н	61.2	1.15	67.2	320.0	32	138318	6/4 - 18/4
	10SHDX60046	139620	60.0	460	3	60	1150	F	86.7	1.15	96.8	400.0	32	138319	2/4 - 18/4
	10SHDX60056	139621	60.0	575	3	60	1150	F	69.4	1.15	77.4	320.0	32	138318	6/4 - 18/4
	10SHDX75046	139622	75.0	460	3	60	1150	Н	109.3	1.15	119.5	612.0	32	138319	2/4 - 18/4
	10SHDX75056	139623	75.0	575	3	60	1150	Н	87.4	1.15	95.6	489.6	32	138319	2/4 - 18/4
	10SHDX100046	139624	100.0	460	3	60	1150	Е	135.0	1.0	135.0	612.0	32	138319	2/4 - 18/4
	10SHDX100056	139625	100.0	575	3	60	1150	Е	108.0	1.0	108.0	489.6	32	138319	2/4 - 18/4
_	10SHDX15098	139990	15.0	208 230	3	60	870	G	50.4 48.4	1.2	59.0 55.6	230.0	28	138317	8/4 - 18/4
Pump	10SHDX15048	139991	15.0	460	3	60	870	G	24.2	1.2	27.8	115.0	28	138317	8/4 - 18/4
P	10SHDX15058	139992	15.0	575	3	60	870	G	19.4	1.2	22.2	92.0	28	138317	8/4 - 18/4
хднѕ	10SHDX20098	139626	20.0	208 230	3	60	870	J	69.0 75.1	1.2	76.0 79.0	400.0	28	138318	6/4 - 18/4
0,	10SHDX20048	139627	20.0	460	3	60	870	J	37.6	1.2	41.1	200.0	28	138317	8/4 - 18/4
	10SHDX20058	139628	20.0	575	3	60	870	J	30.1	1.2	32.9	160.0	28	138317	8/4 - 18/4
	10SHDX25098	139629	25.0	208 230	3	60	870	Н	82.3 84.0	1.2	98.8 94.5	400.0	28	138319	2/4 - 18/4
İ	10SHDX25048	139630	25.0	460	3	60	870	Н	42.0	1.2	47.2	200.0	28	138317	8/4 - 18/4
. 🔺	10SHDX25058	139631	25.0	575	3	60	870	Н	33.6	1.2	37.8	160.0	28	138317	8/4 - 18/4
	10SHDX30098	139632	30.0	208 230	3	60	870	F	98.8 94.5	1.2	124.1 108.6	400.0	28	138319	2/4 - 18/4
İ	10SHDX30048	139633	30.0	460	3	60	870	F	47.2	1.2	54.3	200.0	28	138317	8/4 - 18/4
İ	10SHDX30058	139634	30.0	575	3	60	870	F	37.8	1.2	43.5	160.0	28	138317	8/4 - 18/4
İ	10SHDX40048	139635	40.0	460	3	60	870	F	62.2	1.15	69.4	275.0	32	138318	6/4 - 18/4
	10SHDX40058	139636	40.0	575	3	60	870	F	49.8	1.15	55.5	220.0	32	138317	8/4 - 18/4
Ì	10SHDX50048	139637	50.0	460	3	60	870	D	74.5	1.15	84.9	275.0	32	138318	6/4 - 18/4
					_	-				i	-				

59.0

D

67.4

1.15

220.0

32

138317

8/4 - 18/4

IMPORTANT!

Moisture and Temperature sensor leads are integral to power cord.

50.0

575

3 60 870

Pump rated for operation at ± 10% voltage at motor.

139638

- ▲ Cord Suffix: XC 30 Feet, XF 50 Feet, XJ 75 Feet, or XL 100 Feet.
- ▲ Cord sold separately.


10SHDX50058



Series 10SHDW

Performance Curve 25 - 60HP, 1150RPM, 60Hz

Solids Handling Submersible Pumps





PUMPS & SYSTEMS


SECTION 0.1J PAGE 7 DATE 2/16

Series 10SHDW

Performance Curve 10 - 25HP, 870RPM, 60Hz



Solids Handling Submersible Pumps



SECTION 0.1J PAGE 8 DATE 2/16






Series 10SHDX

Performance Curve 40 - 100HP, 1150RPM, 60Hz

Solids Handling Submersible Pumps





PUMPS & SYSTEMS


SECTION 0.1J PAGE 9 DATE 2/16

Series 10SHDX

Performance Curve 15 - 50HP, 870RPM, 60Hz



Solids Handling Submersible Pumps



SECTION 0.1J PAGE 10 DATE 2/16





8401 BRAYTON DRIVE • ANCHORAGE, ALASKA 99507 • PHONE: (907)563-3424 • FAX: (907)562-5449 November 16, 2017

ATTN: Jonathan Capua - CRW Engineering

QUOTE: AKP17-1173
Project: CRW Barnes Pumps

PH: 907-646-5680

Email: jcapua@crweng.com

We are pleased to provide pricing for the following equipment:

Qty	Part #	Description	Each	Total
3	10SHDX30098	BARNES 10SHD 28 FRAME 10 INCH DISCHARGE, CAST IRON VALUTE, CAST IRON MOTOR HOUSING, ENCLOSED DUAL VAIN DUCTILE IRON IMPELLER, CARBON/CERAMIC X SILICON CARBIDE/SILICON CARBIDE MECHANICAL SEAL & BUNA-N ELASTOMERS, NORMALLY OPEN MOISTURE SENSOR, (3) NORMALLY CLOSED THERMAL SENSORS, 50 FEET OF CABLE	\$ 19,351.00	\$ 58,053.00
Please i	reference AKP17-1173 w	hen placing order.	Tota	l: \$58,053.00

Subject to Alaska Pumps Terms & Conditions of Sale. Net Thirty (30) Terms are subject to Alaska Pumps' credit department approval.

F.O.B: Alaska Pump Ships: 7-9 Weeks

Regards,

John Murphy Sales / Projects

DXP | Alaska Pump & Supply, Inc.

Direct: (907) 793-4819 FAX: (907) 562-5449 John.Murphy@dxpe.com Job Name: CRW Barnes Pumps DXP | Alaska Pump & Supply, Inc.
Date: 11/16/2017 AKP17-1173

DXP | ALASKA PUMP & SUPPLY, INC. STANDARD TERMS & CONDITIONS OF SALE

<u>Terms of Payment</u>: Payment is due thirty (30) days after the date of the invoice. Interest on the unpaid balance will be charged on all overdue monies at the rate of 18% per annum or the highest rate allowable by law, whichever is less. Customer agrees to pay all collection costs, including actual reasonable attorney's fees incurred in collecting monies due hereunder. Seller reserves the right to require payment in advance or provide other credit terms if Buyer's credit is not acceptable to Seller.

<u>Identification and Risk of Loss</u>: The products, goods and/or equipment shall be identified to the contract and risk of loss shall pass to Buyer when the products, goods and/or equipment are placed in the hands of the carrier.

<u>Freight</u>: All prices are FOB point of manufacture and do not include freight unless specifically listed as included. Seller shall not be responsible for actions, inactions or delays by the carrier.

<u>Conditions</u>: All orders are accepted with the understanding that they are subject to Seller's ability to obtain the necessary products, goods and/or equipment.

Not Included: Unless specifically provided herein, the products, goods, equipment, and/or services listed do not include freight, haulage, unloading, freight claims, installation, erection, concrete, grout, water, utilities, lubricating grease and oil, power, tools, labor, controls, conduit, wiring, meters, main disconnects, piping, valves, fittings, gaskets, hardware, taxes, covers, field painting, insurance, testing, royalties, maintenance, operation, erection supervision, start-up services, personnel transportation, anchor bolts, welding rod, or asset.

<u>Inspection</u>: Buyer shall inspect Seller's products, goods and/or equipment upon receipt and if Buyer's inspection reveals any defects, Buyer shall notify the Seller within three (3) days after receipt of the products, goods and/or equipment of any claim Buyer might have concerning such defects or of any claim discovered by Buyer. Buyer's failure to notify Seller within such three day period shall constitute a waiver by Buyer of all claims covering such defects.

Errors: Seller reserves the right to correct any clerical and/or stenographic error or omission.

Cancellation: Buyer may cancel this order only upon written notice and payment to Seller of reasonable cancellation charges.

<u>Returns</u>: Seller will not accept returns of chemicals, electrical items or special orders. Seller will not accept returns of any products, goods and/or equipment after ninety (90) days from the date of the invoice. Buyer will be assessed a reasonable restocking fee on any accepted returns.

<u>Approvals</u>: Buyer is responsible for obtaining any required engineers', owners', and/or governmental agencies' approval of the products, goods, equipment and/or services. Seller does not warrant that the products, goods, equipment and/or services will meet any such approvals or specifications.

<u>Limitation of Liability</u>: In no event shall Seller be liable for any lost profits, down time, lost sales, operating or maintenance costs, or for any other special, indirect, incidental or consequential damages of Buyer.

Warranties: SELLER MAKES NO EXPRESS WARRANTIES WITH RESPECT TO ANY PRODUCT, GOODS AND/OR EQUIPMENT SOLD OR SERVICES PERFORMED AND SELLER SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Seller does not authorize anyone to make a warranty of any kind on its behalf and Buyer should not rely on any statement to that effect. Seller is not the manufacturer of the products, goods and/or equipment warrants the products, goods and/or equipment that Buyer has purchased, Buyer shall have whatever manufacturer's warranty there is subject to the terms and conditions of the warranty. The Buyer's sole and exclusive remedy, if any, shall be against the manufacturer and not Seller.

<u>Integration</u>: These Terms and Conditions constitute the entire agreement between Buyer and Seller with respect to this transaction and supercede and replace all prior negotiations agreements, and representation, oral or written. These Terms and Conditions may not be amended or modified except pursuant to a written document signed by both parties.

Governing Law: The terms of this agreement and all rights and obligations of the parties hereunder shall be governed by the laws of the State of Alaska.

<u>Binding Effect</u>: These Terms and Conditions shall be binding on the parties hereto and their heirs, personal representatives, successors, and assigns. The undersigned acknowledges and agrees to Alaska Pump & Supply, Inc. terms and conditions of sale/quote as referenced in our quote AKP17-1173 and is subject to Alaska Pump & Supply Inc.'s Standard Terms and Conditions of Sale which are outlined above and agrees to be bound by said Terms and Conditions. No other conditions previous or after date below apply.

<u>Letters and Quotes</u>: Notwithstanding any language to the contrary, nothing contained in our letters or quotes constitutes or is intended to constitute engineering work requiring a stamp or engineering seal by Alaska Pump & Supply, Inc.. We neither convey nor imply that the company or persons are practicing engineering herein.

Customer Name Printed	Company Name Printed
X	
Customer Signature	Date:

